QXC10S-R/QXC10S-S CEILING SERIES 10" CEILING SPEAKER - AVAILABLE WITH EITHER ROUND OR SQUARE GRILLE





 R Size
 12.64 dia x 7.6 d (in)

 321 dia x 193 d (mm)

 321 dia x 193 d (mm)

 depth w/grille 7.70 d(in) 196(mm)

 S Size
 12.64 h x 12.64 w x 7.6 d (in)

 321 h x 321 w x 193 d (mm)

 depth w/grille 7.70 d(in) 196(mm)

 321 h x 321 w x 193 d (mm)

 depth w/grille 7.70 d(in) 196(mm)

 Freq Response
 35Hz-120Hz± 3dB

 Impedance
 8 ohms

 Sensitivity
 87dB 2.83V / 1m

 Power req.
 150-500W

 Woofer
 (1) 10" (254 mm) Aluminum

 Finishes
 White Paintable Grille

 PCB
 QXC10S-R-PBF / QXC10S-S-PBF



2185 Park Place, Minden, NV 89423 Ph: 775-461-7500 www.jamesloudspeaker.com



(1) 10" (254 mm) Laminated Aluminum Honeycomb

The QXC Series ceiling loudspeakers from James include performance that is second to none, and introduce a low-profile exterior grille for subtle visual design. All woofers are James designed with aluminum cones and Santoprene[™] surrounds to allow marine use while maintaining the highest quality sound.

All enclosures are constructed with aircraft grade 5052 aluminum and include white paintable aluminum grilles and use the James marine rated magnetic grille fasteners.

Perfect for any in-ceiling application where a James SA Series speaker is not necessary, installation could not be easier for either retro-fit or new construction projects. The QXC series uses a unique 3-piece installation method employing a lightweight frame, independent speaker body, and a border-less aluminum grille that protrudes less than 3/16" (5 mm) from the wall which can be painted based on the application – or completely flush with the addition of a pre-construction board.

For marine applications, please use the QXC10S-RM or QXC10S-SM, 70V options available.

Please specify if grilles should come paintable ready when ordering. Grilles are available in either round or square.

*Suggested for use with Atmos, Auro 3D, or DTS:X applications.

Ordering Notes: QXC10S-R for the round grille. QXC10S-S for the square grille. QXC10S-R-PBF or QXC10S-S-PBF for flush mount pre-construction board. PBF Flush mount pre-construction board available, allow 3-business days for delivery after order.



Borderless aluminum grille protrudes less than 3/16" (5 mm) from wall.