


Gemstone



Colors





White VTL GMWH



Cream VTL GMCR




Light Gray VTL GMLG




Greige VTL GMGG




Blush VTL GMBS




Blue VTL GMBU



Pewter VTL GMPW




Dark Grey VTL GMDG



Navy VTL GMNV


Sizes



6" x 7" x 8.6mm
Hexagon



3" x 12" x 8.6mm



Green VTL GMGN

GEMSTONE

Field Tiles*

SIZE	ACTUAL	THICKNESS	FINISH
6" x 7" Hexagon Glossy	5.91" x 6.81"	8.6mm	Gloss
3" x 12" Glossy	2.95" x 11.81"	8.6mm	Gloss

* Not all sizes/trims are available in all colors and finishes, scan QR code for product details.

Mosaics & Coordinating Trims*

SIZE	ACTUAL	FINISH
1" x 12" Quarter Round Glossy	0.35" x 11.81"	Gloss

Recommended Grout Joint: 1/8" - Rectified
3/16" - Non Rectified

Product Characteristics

	GLOSS
Breaking Strength (ASTM C648 or ISO 10545-4)	>240lbf
Chemical Resistance (ASTM C650 or ISO 10545-13)	B
DCOF	
Deep Scratch Resistance - Unglazed (ISO 10545-6)	N/A
Frost Resistance (ASTM C1026 or ISO 10545-12)	Not Resistant
Mohs Hardness - EN101	2
Water Absorption (ASTM C373 or ISO 10545-3)	10-18%
Certifications	N/A
Country of Origin	
Shade Variation Code	V2

Application**

		WALL	FLOOR
Interior	Residential	•	
Interior	Commercial	•	
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial		

** These recommendations are not defined by ANSI Standards

Material


Glazed Ceramic




V2 Slight Variation



Frost Resistant



Water Absorption: 10-18%



Must be Sealed



Scan QR Code for
Product Information and
Installation Images

Request samples.

www.vitlsurfaces.com
samples@vitlsurfaces.com



VITL
COMMERCIAL SURFACES