Specifications

Eaton FCF10RN

Catalog Number: FCF10RN

Eaton Bussmann Series UL Class CF, FCF fuse, fast-acting, single-element cube fuse, 10 A, non-idicating fuse, interrupting rating of 50 kA at 600 Vdc and 300 kA at 600 Vac



General specifications

Product Name	**Catalog Number**
Eaton Bussmann series FCF fuse	FCF10RN
UPC	**Product Length/Depth**
051712362443	1.88 in
Product Height	**Product Width**
1.75 in	0.75 in
Product Weight	**Warranty**
0.08 lb	Not Applicable
Compliances	**Certifications**
CE Marked RoHS Compliant	UL Listed CSA Certified

Powering Business Worldwide

Electrical rating

Amperage Rating

10 A

Frequency rating - max

60 Hz

Frequency rating - min

50 Hz

Interrupt rating

50 kAIC at 600 Vdc

300 kAIC at 600 Vac

Response time

4 min at 200%

Voltage rating

600 Vac, 600 Vdc

Physical details

Color

Black

Fuse type

Class CF

Fast acting

Material

Glass filled PES

Number of elements

1

Operating Temperature

-40° to 80°C

Packaging type

Standard

Terminal material

Electroless tin plated copper alloy terminal

General information

Class

Class CF

Connection

Blade end

Fuse indicator

Non-indicating

Special features

Superior overload and cycling capabilities

Used with

TCFH30N, CCP2-3-30CF

Resources

Catalogs

Low Voltage Branch Circuit Fuse Chapter

Bussmann Full Line Catalog

Compliance information

RoHS Search Tool

Multimedia

The Power of Space

Bussmann series Fuseology

Technical data sheets

Bussmann series Fast-acting CUBEFuse data sheet no. 2147



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia