



Supercut

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 15/10/2024 Revision date: 27/08/2024 Supersedes version of: 08/03/2024 Version: 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Supercut
UFI : Y91Y-6802-8007-9TG6
Product code : BDS002293AE
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Professional use
Use of the substance/mixture : Lubricants

1.3. Details of the supplier of the safety data sheet

Supplier

CRC Industries Europe B.V.
Touwslagerstraat 1
9240 Zele
Belgium
T +32(0)52/45.60.11, F +32(0)52/45.00.34
hse@crcind.com, www.crcind.com

1.4. Emergency telephone number

Emergency number : +32(0)52/45.60.11
Office hours: 9-17h CET

Country/Area	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Brussels	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 2 H223;H229
Skin sensitisation, Category 1 H317
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Flammable aerosol. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Supercut

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

	GHS02	GHS07
Signal word (CLP)	: Warning	
Contains	: Polysulfides, di-tert-dodecyl; Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts; Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	
Hazard statements (CLP)	: H223 - Flammable aerosol. H229 - Pressurised container: May burst if heated. H317 - May cause an allergic skin reaction.	
Precautionary statements (CLP)	: P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapours/spray. P280 - Wear protective gloves/protective clothing. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents/container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.	
Extra phrases	: This product contains a fluorinated greenhouse gas.	

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified (Note L)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25	5 – 10	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated light paraffinic; Baseoil— unspecified (Note L)	CAS-No.: 64742-55-8 EC-No.: 265-158-7 EC Index-No.: 649-468-00-3 REACH-no: 01-2119487077-29	1 – 5	Asp. Tox. 1, H304
Polysulfides, di-tert-dodecyl	CAS-No.: 68425-15-0 EC-No.: 270-335-7 REACH-no: 01-2119540516-41	1 – 5	Skin Sens. 1, H317
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	CAS-No.: 70024-69-0 EC-No.: 274-263-7 REACH-no: 01-2119492616-28	< 1	Skin Sens. 1, H317
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	CAS-No.: 68584-23-6 EC-No.: 271-529-4 REACH-no: 01-2119492627-25	< 1	Skin Sens. 1B, H317

Supercut

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Carbon dioxide (CO ₂) (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 124-38-9	< 1	Press. Gas (Comp.), H280
2,2'-(octadec-9-enylimino)bisethanol	CAS-No.: 25307-17-9 EC-No.: 246-807-3 REACH-no: 01-2119510876-35	< 0,1	Acute Tox. 4 (Oral), H302 (ATE=1260 mg/kg bodyweight) Skin Corr. 1, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)

Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	CAS-No.: 68584-23-6 EC-No.: 271-529-4 REACH-no: 01-2119492627-25	(10 ≤ C < 100) Skin Sens. 1B; H317

Note L: The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If signs/symptoms develop, get medical attention.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention. Seek medical attention if irritation develops.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Seek medical attention if irritation develops.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: May cause an allergic skin reaction.
-------------------------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.

Supercut

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous decomposition products in case of fire : During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Firefighting instructions : Move containers from fire area if it can be done without personal risk. Use standard firefighting procedures and consider the hazards of other involved materials.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment : Wear appropriate protective equipment and clothing during clean-up.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to remove residual contamination.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For disposal of contaminated materials refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment. Avoid prolonged exposure. Handle in accordance with good industrial hygiene and safety procedures.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool. Keep container closed when not in use.

7.3. Specific end use(s)

No additional information available

Supercut

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

Carbon dioxide (CO ₂) (124-38-9)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Carbon dioxide
IOEL TWA	9000 mg/m ³
	5000 ppm
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Belgium - Occupational Exposure Limits	
Local name	Carbone (dioxyde de) # Koolstofdioxide
OEL TWA	9131 mg/m ³
	5000 ppm
OEL STEL	54784 mg/m ³
	30000 ppm
Remark	A: la mention "A" signifie que l'agent libère un gaz ou une vapeur qui n'ont en eux-mêmes aucun effet physiologique mais peuvent diminuer le taux d'oxygène dans l'air. Lorsque le taux d'oxygène descend en dessous de 17-18 % (vol/vol) le manque d'oxygène provoque des suffocations qu'aucun symptôme préalable n'annonce. # A: de vermelding "A" betekent dat dit agens gas of damp vrijgeeft dat of die op zich geen fysiologische werking heeft, maar het zuurstofgehalte in de lucht verlaagt. Wanneer het zuurstofgehalte daalt onder de 17-18 % (vol/vol), veroorzaakt het zuurstoftekort verstikking, die zich manifesteert zonder dat er een waarschuwing aan voorafgaat.
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023

DNEL and PNEC

Distillates (petroleum), hydrotreated light paraffinic; Baseoil— unspecified (64742-55-8)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	0,97 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2,73 mg/m ³
Long-term - local effects, inhalation	5,58 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	0,74 mg/kg bodyweight/day
PNEC (Oral)	
PNEC oral (secondary poisoning)	9,33 mg/kg food
Polysulfides, di-tert-dodecyl (68425-15-0)	
PNEC (Sediment)	
PNEC sediment (freshwater)	3,85 mg/kg dwt
PNEC sediment (marine water)	0,385 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	66,7 mg/kg food

Supercut

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Polysulfides, di-tert-dodecyl (68425-15-0)	
PNEC (STP)	
PNEC sewage treatment plant	1 g/l
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	3,33 mg/kg bodyweight/day
Long-term - local effects, dermal	1,03 mg/cm ²
Long-term - systemic effects, inhalation	11,75 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	0,8333 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2,9 mg/m ³
Long-term - systemic effects, dermal	1,667 mg/kg bodyweight/day
Long-term - local effects, dermal	0,513 mg/cm ²
PNEC (Water)	
PNEC aqua (freshwater)	1 mg/l
PNEC aqua (marine water)	1 mg/l
PNEC aqua (intermittent, freshwater)	10 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	226000000 mg/kg dwt
PNEC sediment (marine water)	226000000 mg/kg dwt
PNEC (Soil)	
PNEC soil	271000000 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	16,667 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	1000 mg/l
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts (68584-23-6)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	3,33 mg/kg bodyweight/day
Long-term - local effects, dermal	1,03 mg/cm ²
Long-term - systemic effects, inhalation	11,75 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	0,8333 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2,9 mg/m ³
Long-term - systemic effects, dermal	1667 mg/kg bodyweight/day
Long-term - local effects, dermal	0,513 mg/cm ²
PNEC (Water)	
PNEC aqua (freshwater)	1 mg/l
PNEC aqua (marine water)	1 mg/l

Supercut

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts (68584-23-6)	
PNEC aqua (intermittent, freshwater)	10 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	226000000 mg/kg dwt
PNEC sediment (marine water)	226000000 mg/kg dwt
PNEC (Soil)	
PNEC soil	271000000 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	16667 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	1000 mg/l
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified (64742-54-7)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	0,97 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2,73 mg/m ³
Long-term - local effects, inhalation	5,58 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	0,74 mg/kg bodyweight/day
PNEC (Oral)	
PNEC oral (secondary poisoning)	9,33 mg/kg food
2,2'-(octadec-9-enylimino)bisethanol (25307-17-9)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	0,42 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2,96 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	0,15 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0,522 mg/m ³
Long-term - systemic effects, dermal	0,15 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0,214 µg/l
PNEC aqua (marine water)	0,0214 µg/l
PNEC aqua (intermittent, freshwater)	0,87 µg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	1,692 mg/kg dwt
PNEC sediment (marine water)	0,1692 mg/kg dwt
PNEC (Soil)	
PNEC soil	5 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	2 mg/kg food

Supercut

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2,2'-(octadec-9-enylimino)bisethanol (25307-17-9)

PNEC (STP)

PNEC sewage treatment plant

1500 µg/l

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protection equipment

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Neoprene or nitrile rubber gloves.

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: A

Thermal hazards

Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Amber.
Appearance	: Propelled liquid.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Flammable aerosol.
Explosive properties	: Pressurised container: May burst if heated.
Lower explosion limit	: Not available
Upper explosion limit	: Not available

Supercut

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Flash point	: 170 °C
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: Not available
pH	: Not applicable
Viscosity, kinematic	: 26,27 mm ² /s at 40 °C
Viscosity, dynamic	: 23,09 mPa·s at 40 °C
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not applicable
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 0,879 g/cm ³ at 20 °C
Relative density	: 0,88 at 20 °C
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

Information with regard to physical hazard classes

% of flammable ingredients : 0 %

Other safety characteristics

VOC content : 50 g/l

Additional information : For aerosols data for the product without propellant.

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Distillates (petroleum), hydrotreated light paraffinic; Baseoil— unspecified (64742-55-8)

LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rabbit	> 2000 mg/kg

Supercut

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0)	
LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg bodyweight
LC50 Inhalation - Rat	> 1,9 mg/l/4h
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts (68584-23-6)	
LD50 oral rat	> 16000 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified (64742-54-7)	
LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg
2,2'-(octadec-9-enylimino)bisethanol (25307-17-9)	
LD50 oral rat	1260 mg/kg
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: Not applicable
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0)	
pH	8,1
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: Not applicable
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0)	
pH	8,1
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Distillates (petroleum), hydrotreated light paraffinic; Baseoil— unspecified (64742-55-8)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0,98 mg/l air
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0)	
NOAEL (oral, rat, 90 days)	500 mg/kg bodyweight OECD Guideline 407
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight OECD Guideline 410
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts (68584-23-6)	
NOAEL (oral, rat, 90 days)	500 mg/kg bodyweight
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Supercut	
Vaporizer	Aerosol
Viscosity, kinematic	26,27 mm ² /s at 40 °C

Supercut

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2. Information on other hazards

Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic) : Not classified (Based on available data, the classification criteria are not met)

Distillates (petroleum), hydrotreated light paraffinic; Baseoil— unspecified (64742-55-8)

LC50 - Fish [1] > 5000 mg/l

EC50 - Crustacea [1] > 1000 mg/l

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0)

LC50 - Fish [1] > 1000 mg/l *Cyprinodon variegatus*

EC50 - Crustacea [1] > 1000 mg/l *Daphnia magna*

EC50 72h - Algae [1] > 1000 mg/l *Pseudokirchneriella subcapitata*

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts (68584-23-6)

LC50 - Fish [1] 10000 mg/l

EC50 72h - Algae [1] > 1000 mg/l

EC50 96h - Algae [1] > 1000 mg/l

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified (64742-54-7)

EC50 - Crustacea [1] > 1000 mg/l

EC50 96h - Algae [1] > 1000 mg/l

2,2'-(octadec-9-enylimino)bisethanol (25307-17-9)

LC50 - Fish [1] 0,1 mg/l *Danio rerio*

EC50 - Crustacea [1] 0,043 mg/l *Daphnia magna*

EC50 72h - Algae [1] 0,0538 mg/l *Pseudokirchneriella subcapitata*

12.2. Persistence and degradability

Supercut

Persistence and degradability Not established. No data is available on the degradability of this product.

12.3. Bioaccumulative potential

Supercut

Partition coefficient n-octanol/water (Log Kow) Not applicable

Supercut

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), hydrotreated light paraffinic; Baseoil— unspecified (64742-55-8)	
Partition coefficient n-octanol/water (Log Pow)	3,9 – 6
Polysulfides, di-tert-dodecyl (68425-15-0)	
Partition coefficient n-octanol/water (Log Pow)	12,46
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0)	
Partition coefficient n-octanol/water (Log Pow)	> 5,47
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts (68584-23-6)	
Partition coefficient n-octanol/water (Log Pow)	> 4,46
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified (64742-54-7)	
Partition coefficient n-octanol/water (Log Pow)	3,9 – 6
2,2'-(octadec-9-enylimino)bisethanol (25307-17-9)	
Partition coefficient n-octanol/water (Log Pow)	6,6
Carbon dioxide (CO₂) (124-38-9)	
Partition coefficient n-octanol/water (Log Pow)	0,83

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Supercut	
Results of PBT assessment	Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

12.7. Other adverse effects

Additional information : No other effects known
Global warming potential (GWP) : 0.13 (Fluorinated greenhouse gases - (EC) No 2024/573)

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
European List of Waste (LoW, EC 2000/532) : According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.






SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

Supercut

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-D EmS-No. (Spillage): S-U	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP200
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203

Supercut

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Supercut

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

VOC Directive (2004/42)

VOC content : 50 g/l

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant

Supercut

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 2	Aerosol, Category 2
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H223	Flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Skin Corr. 1	Skin corrosion/irritation, Category 1
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.