



T-501G

Horizontal Swing, Threaded Connection, 200 WOG, Class 125



PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-103G	1/2"	120	10	54
105-104G	3/4"	100	10	47
105-105G	1"	72	6	60
105-106G	1-1/4"	60	5	59
105-107G	1-1/2"	32	4	54
105-108G	2"	20	2	55
105-109G	2-1/2"	12	2	58
105-110G	3"	6	1	43
105-111G	4"	4	1	43

- Dezincification Resistant Brass Alloy
- Residential and Commercial Applications
- Truesdail Certified - NSF/ANSI/CAN 61 & NSF 372
- Wetted Surfaces Contain Less than .25% Lead Content



S-501G

Horizontal Swing, Solder Connection, 200 WOG, Class 125



PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-203G	1/2"	120	10	48
105-204G	3/4"	100	10	60
105-205G	1"	72	6	63
105-206G	1-1/4"	40	5	59
105-207G	1-1/2"	32	4	57
105-208G	2"	24	2	70
105-209G	2-1/2"	10	1	48
105-210G	3"	8	1	54

- Dezincification Resistant Brass Alloy
- Residential and Commercial Applications
- Truesdail Certified - NSF/ANSI/CAN 61 & NSF 372
- Wetted Surfaces Contain Less than .25% Lead Content



P-501G

Horizontal Swing, Press Connection, 200 WOG, Class 125



PART NUMBER	SIZE	CASE	CARTON	WEIGHT
105-003G	1/2"	160	10	68
105-004G	3/4"	120	10	77
105-005G	1"	60	5	51
105-006G	1-1/4"	40	5	45
105-007G	1-1/2"	30	5	53
105-008G	2"	24	2	62

- Dezincification Resistant Brass Alloy
- Residential and Commercial Applications
- One-Piece Body Design
- Heavy Pattern Cast Brass Construction
- EPDM O-Ring Seal
- Metal-to-Metal Disc Seal
- Truesdail Certified - NSF 61 & NSF 372
- Wetted Surfaces Contain Less than .25% Lead Content

