






# SYMMONS® Visu-Temp®

## Location:

1-210VT  
Tub/Shower System  
**Specification Submittal**



<b>Model Numbers</b>	<b>Feature Highlights</b>
<input type="checkbox"/> <b>1-210VT</b> Visu-Temp Tub/Shower System	<ul style="list-style-type: none"> <li>• Visu-Temp Pressure-Balancing mixing valve with integral thermometer</li> <li>• Adjustable stop screw to limit handle turn</li> <li>• Push-button diverter with volume control for shower head</li> <li>• Super shower head with arm and flange</li> <li>• Tub spout</li> <li>• Standard flow rate 2.0 gpm (7.6 L/min)</li> </ul>
<b>Options/ Modifications</b>	
<input type="checkbox"/> <b>1.5</b> <b>1.5 gpm (5.7 L/min) flow restrictor</b> <input type="checkbox"/> <b>X</b> <b>Integral service stops—allows water shut-off at valve for service</b>	
<b>Note:</b> Append appropriate -suffix to model number.	
<b>Compliance</b>	<b>Warranty</b>
- ASME A112.18.1/CSA B125.1  	<b>Limited Lifetime</b> - to the original end purchaser in consumer/residential installations. <b>10 Years</b> - for commercial/industrial installations. Refer to <a href="http://www.symmons.com/warranty">www.symmons.com/warranty</a> for complete warranty information. 

## Architectural/ Engineering Specification

Symmons Visu-Temp Tub and Shower System \_\_\_\_\_ Includes Visu-Temp Pressure-Balancing mixing valve with integral thermometer, Adjustable stop screw to limit handle turn, Push-button diverter with volume control for shower head, Super shower head with arm and flange, Tub spout, Standard flow rate 2.0 gpm (7.6 L/min). 10 Year Commercial Warranty. ASME A112.18.1/CSA B125.1 compliant. Available options: "1.5 - 1.5 gpm (5.7 L/min) flow restrictor", "X - Integral service stops—allows water shut-off at valve for service".



# SYMMONS® Visu-Temp®

1-210VT

## Dimensions

