

Parallel Jaw Grips

HDPE-Coated Cable

- Securely pulls HDPE-coated cable commonly known as "tree wire"
- Innovative high-traction surface grips the cable without damaging the outer jacket
- Tough carbide grit technology withstands even the harshest jobsite conditions



Cat. No.	Cable Type	Cable Diameter	Hot Latch	Spring	Locking Handle	Jaw Type	Jaw Length	Weight
4,000 lbs. (1,814 kg) Maximum Safe Load								
1716-70	HDPE-Coated	0.625" to 1.362" (15.9 to 34.6 mm)	●	●	—	Round	4.5" (114.3 mm)	5.10 lb (2.31 kg)
1716-71	HDPE-Coated	0.625" to 1.362" (15.9 to 34.6 mm)	●	●	●	Round	4.5" (114.3 mm)	5.10 lb (2.31 kg)
12,000 lbs. (5,443 kg) Maximum Safe Load								
1716-60	HDPE-Coated	0.70" to 1.30" (17.78 to 33.02 mm)	—	●	—	Round	5.125" (130.2 mm)	8.1 lb (3.7 kg)

KT Series

- Versatile grips hold a wider range of ACSR cable sizes reducing the number of grips needed
- Round jaw provides maximum contact with the cable minimizing deformation
- Large opening in handle accommodates a wide variety of hooks on hoists, winches, and tackle blocks
- Hot latch closes automatically to guard against grip accidentally disengaging from wire
- Spring closes grip on cable helping to maintain initial position
- Locking handle keeps jaw open while grip is placed on cable with a hot stick



KT4500



KT4602



KT4650

Cat. No.	Cable Type	Cable Diameter	Hot Latch	Spring	Locking Handle	Jaw Type	Jaw Length	Weight
5,000 lbs. (2,268 kg) Maximum Safe Load								
KT4500	ACSR	0.18" to 0.60" (4.57 to 15.20 mm)	—	●	—	Round - Serrated	4" (101.6 mm)	3.8 lb (1.7 kg)
KT4501	ACSR	0.18" to 0.60" (4.57 to 15.20 mm)	●	●	●	Round - Serrated	4" (101.6 mm)	3.8 lb (1.7 kg)
KT4502	ACSR	0.18" to 0.60" (4.57 to 15.20 mm)	●	●	—	Round - Serrated	4" (101.6 mm)	3.8 lb (1.7 kg)
KT4650	ACSR	0.16" to 0.90" (4.06 to 22.86 mm)	—	●	—	Round - Serrated	4.5" (114.3 mm)	4.4 lb (2.0 kg)
KT4652	ACSR	0.16" to 0.90" (4.06 to 22.86 mm)	●	●	—	Round - Serrated	4.5" (114.3 mm)	4.9 lb (2.2 kg)
10,000 lbs. (4,536 kg) Maximum Safe Load								
KT4600	ACSR	0.30" to 0.80" (7.62 to 20.3 mm)	—	●	—	Round - Serrated	5" (127.0 mm)	7.0 lb (3.2 kg)
KT4601	ACSR	0.30" to 0.80" (7.62 to 20.3 mm)	●	●	●	Round - Serrated	5" (127.0 mm)	7.0 lb (3.2 kg)
KT4602	ACSR	0.30" to 0.80" (7.62 to 20.3 mm)	●	—	—	Round - Serrated	5" (127.0 mm)	7.0 lb (3.2 kg)
12,000 lbs. (5,443 kg) Maximum Safe Load								
KT4800	ACSR	0.70" to 1.25" (17.78 to 31.75 mm)	—	●	—	Round - Serrated	5.125" (130.2 mm)	9.0 lb (4.1 kg)
KT4801	ACSR	0.70" to 1.25" (17.78 to 31.75 mm)	●	●	●	Round - Serrated	5.125" (130.2 mm)	9.0 lb (4.1 kg)
KT4802	ACSR	0.70" to 1.25" (17.78 to 31.75 mm)	●	—	—	Round - Serrated	5.125" (130.2 mm)	9.0 lb (4.1 kg)