

# LEAD FREE BRASS BALL VALVES



## T-412G MIP x Crimp

2 Piece, Standard Port, Threaded MIP x Crimp Pex Connection, 400 WOG

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
LEVER HANDLE				
103-534MPG	3/4"	120	10	59
T-HANDLE				
103-534MPG-TH	3/4"	120	10	54

- Dezincification Resistant Brass Alloy
- Gland Follower and Single O-Ring Stem Design
- Blow-Out Proof Stem
- 100% Leak Tested
- IAPMO Certified - NSF 61 & NSF 372 & NSF 14
- ASTM F1807
- Wetted Surfaces Contain Less than .25% Lead Content



LEVER HANDLE



T-HANDLE



## T-412G FIP x Crimp

2 Piece, Standard Port, Threaded FIP x Crimp Pex Connection, 400 WOG

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
LEVER HANDLE				
103-554PG	3/4"	120	10	53
103-555PG	1"	54	6	43
T-HANDLE				
103-554PG-TH	3/4"	120	10	53
103-555PG-TH	1"	54	6	53

- Dezincification Resistant Brass Alloy
- Gland Follower and Single O-Ring Stem Design
- Blow-Out Proof Stem
- 100% Leak Tested
- IAPMO Certified - NSF 61 & NSF 372 & NSF 14
- ASTM F1807
- Wetted Surfaces Contain Less than .25% Lead Content



LEVER HANDLE



T-HANDLE



## T-412G Press x Crimp

2 Piece, Standard Port, Press x Crimp Pex Connection, 250 CWP

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
103-563PG	1/2"	100	10	43
103-564PG	3/4"	60	10	41
103-565PG	1"	40	8	46

- Dezincification Resistant Brass Alloy
- Gland Follower and Single O-Ring Stem Design
- Blow-Out Proof Stem
- 100% Leak Tested
- IAPMO Certified - NSF 61 & NSF 372 & NSF 14
- ASTM F1807
- Wetted Surfaces Contain Less than .25% Lead Content

