

Swiss II™ radiates sophisticated beauty highlighting the soft veining of natural stone in a porcelain tile.

# SWISS II™

*Glazed Porcelain*



FLOOR / WALL 

RESIDENTIAL 

COMMERCIAL 

INDOOR 

OUTDOOR 

POOL 



Rhone

Sizes



32" x 32"  
31.50" x 31.50"

Thickness

10mm

Faces

20

Finish

Polished

Edge

Rectified

Grout Joint Recommendation

3/16"

**Product and Installation Details | ANSI A108.02**  
Section 4.3.8.2 - For running bond/brick jointing patterns utilizing tiles (square or rectangular) where the side being offset is greater than 18" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the tile manufacturer. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage.

Testing

Abrasion Resistance  
C1027

Breaking Strength  
C648

Chemical Resistance  
C650

Water Absorption  
C373

DCOF ANSI  
A1371

Scratch Hardness  
MOHS

Shade Variation  
Rating

Results\*

III

>700 lbf

Resistant

<0.50%

>0.55 (Matte)  
<0.42 (Polished)

5 (Matte)  
5 (Polished)

V2



Recommended 33% Offset\*

 Sustainability Attributes

- Red List Free
- Health Product Declaration (HPD) provided upon request
- Product Packaging is 100% recyclable
- VOC Free
- Recycled Content 0% Pre- & Post-Consumer

\*For more information visit [www.emser.com](http://www.emser.com). Always consult a professional for proper usage and installation.