



PDU15M2F8R METERED PDU



Engineered to distribute UPS, generator or utility AC power to multiple devices, servers and network/telecom equipment.

The CyberPower PDU15M2F8R, a ten-outlet (two front, eight rear), rackmount metered power distribution unit (PDU), provides 100-125V 15A output. It distributes power to ten NEMA 5-15R receptacles from a single NEMA 5-15P input with unfiltered electrical pass-through. The current draw for connected equipment is displayed in amps on the front LCD for real-time load monitoring.

Designed for datacenters and other electrically demanding applications, the PDU15M2F8R has rugged, industrial-grade metal housing and a 15-foot AC power cord. It can be mounted either horizontally or vertically. The PDU15M2F8R comes with a cord retention tray and is ETL/RoHS certified. A limited lifetime warranty covers defects in materials and workmanship in the product under normal use and conditions.

TYPICAL APPLICATIONS

- Corporate Servers
- Network Closets
- Data Centers

FEATURES

- Digital meter: Displays Amperage
- Phase: Single
- Amps: 15A (Derated to 12A)
- Volts: 100-125V
- Frequency: 50Hz/60Hz
- Plug type: NEMA 5-15P
- Outlets: 10 x NEMA 5-15R
- Outlet location: 2 Front / 8 Rear
- Size: 1U Rackmount
- Dimensions (in.): 17.5W x 1.75H x 2.25D
- Cord length (ft.): 15
- Warranty: Limited Lifetime

SPECIFICATIONS

INPUT	
Cord Length (ft.)	15 ft (4.6 m)
Derated Input Current	12 A
Input Frequency Range	50Hz - 60Hz
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Nominal Input Voltage	100 - 125 VAC
Phase	Single Phase
Plug Style	Straight

OUTPUT	
Meter Readout	Amperage
Nominal Output Voltage	100 - 125 VAC
Outlet Type	10 x NEMA 5-15R
Outlets - Number of Banks	1
Outlets - Front	2
Outlets - Rear	8
Outlets - Total	10
Overload Protection	15 A

PDU15M2F8R

METERED PDU



SPECIFICATIONS

PHYSICAL	
Adjustable Mounting Brackets	2 sets (L-Short, L-Long)
Color	Black
Cord Retention Tray/ Cord Organizers	Yes
External Site Ground Pin	Yes
Form Factors Supported	Horizontal or Vertical Wallmount Racks Horizontal or Vertical Mount in a Variety of Other Surface Types
Material of Construction	Metal
Rack Height	1U
PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	44.45 x 4.45 x 5.72 cm
Physical Dimensions - Width/Height/Depth (mm)	445 x 44 x 57 mm
Physical Dimensions - Width/Height/Depth (in.)	17.5 x 1.75 x 2.25 in.
Weight (kg)	1.81 kg
Weight (lbs.)	4.0 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	18.11 x 6.63 x 51.13 cm
Shipping Dimensions - Width/Height/Depth (mm)	181.1 x 66.29 x 511.3 mm
Shipping Dimensions - Width/Height/Depth (in.)	7.13 x 2.61 x 20.13 in.
Shipping Weight (kg)	2.72 kg
Shipping Weight (lbs.)	6.0 lbs.
ENVIRONMENTAL	
Operating Elevation	0 - 10,000 ft (0 - 3,048 m)
Operating Relative Humidity	0 - 95% (non-condensing)
Operating Temperature	32 - 95 °F (0 - 35 °C)
Storage Elevation	0 - 50,000 ft (0 - 15,239 m)
Storage Temperature	5 - 113 °F (-15 - 45 °C)
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL62368 UL60950-1 FCC Class A
WARRANTY	
Product Warranty	Limited Lifetime Warranty