



U4667-X-8013



7 Terminal Bolt-in Large Closing Plate Link Bypass 3-double
Connector 6-350kcmil 5-double Connector 4-350kcmil

SPECIFICATIONS

Brand Name	Milbank
Type	Bolt On Meter Socket
Application	Meter Socket
Standard	UL Listed;Type 3R
Voltage Rating	600 Volts Alternating Current
Amperage Rating	480 Continuous Ampere
Phase	3 Phase
Frequency Rating	60 Hertz
Size	6L x 20.25W x34H
Number of Main Breakers	0
Main Breaker Size	No Main Breaker
Cable Entry	Overhead or Underground
Terminal	1/2 Inch Stud Line Side

Insulation	Glass Polyester
Mounting	Surface Mount
Material	G90 Galvanized Steel with Powder Coat Finish
Number of Jaws	7 Terminal
Bypass Provision	Link Bypass
Number of Meter Positions	1 Position
Equipment Ground	2 Barrel Ground Lug
Hub/Closing Plate	Large Closing Plate
Line Side Wire Range	Two 6 AWG - 350 kcmil
Number of Receptacles	0
Height	34 IN
Length	6 IN
Width	20.25 IN

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility, and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.