



### TECHNICAL INFORMATION



V2 Slight Variation



Ready Ship



Recommend offset pattern  $\leq 33\%$



DCOF:  $> 0.42$



Frost Resistant



Water Absorption:  $\leq 0.5\%$



Made in USA



### COLORS



Coal  
AUS HRCL




Cord  
AUS HRCR




Lead  
AUS HRLD



Night  
AUS HRNT



Silver  
AUS HRSL



Snow  
AUS HRSN

### Performance Characteristics

Breaking Strength	$\geq 350$ LBF
Chemical Resistance	Resistant
DCOF	$> 0.42$
Deep Scratch Resistance - Unglazed	N/A
Frost Resistance	Resistant
Mohs Hardness - EN101	N/A
Water Absorption	$\leq 0.5\%$
Certifications	N/A
Country of Origin	USA
Shade Variation Code	V2

### Tiles, Mosaic and Trim\*

SIZE	ACTUAL	THICKNESS	FINISH
24" x 48" Rectified	23.62" x 47.24"	9mm	Matte/Natural
12" x 24"	11.81" x 23.62"	9mm	Matte/Natural
3" x 12"	2.76" x 11.81"	9mm	Matte/Natural
12" x 12" Linear Mosaic	11.81" x 11.81"	9mm	Matte/Natural
2" x 2" Mosaic	11.81" x 11.81"	9mm	Matte/Natural
6" x 12" Cove Base	5.91" x 11.81"	8.5mm	Matte/Natural
3" x 24" Bullnose	2.83" x 23.62"	9mm	Matte/Natural

\* Not all sizes are available in all colors and finishes.

### Application\*\*

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	

\*\* These recommendations are not defined by ANSI Standards



Please see [virginiatile.com](http://virginiatile.com) for details