

# Cable, Cord and Hose Reels



## Features and Benefits


### inREACH™ Industrial Weatherproof Cord Reels

- UL Type 4 environmental listing
- 600V AC, SOW Type Cable
- Durable, corrosion resistant cast aluminum construction
- Multi-position guide arm can be mounted in two positions
- Ratchet lock can be disengaged in field for constant tension applications



### inREACH™ Industrial Weatherproof Cord Reels

HBLW45103



HBLW45123W



HBLW35143



HBLW45103



HBLIMB



HBLI340PB



HBLIMBJ



HBLI10BS

Amps	Volts AC	Cable Length Feet (m)	Cable Type	Weight Lbs. (kg)	Yellow Reel	White Reel
10	600	45 (13.7)	16/3 SOW	23.6 (10.7)	<b>HBLW45163</b>	<b>HBLW45163W</b>
			16/4 SOW	25.6 (11.6)	<b>HBLW45164</b>	<b>HBLW45164W</b>
		35 (10.7)	16/3 SOW	22.5 (10.2)	<b>HBLW35163</b>	<b>HBLW35163W</b>
			16/4 SOW	23.1 (10.5)	<b>HBLW35164</b>	<b>HBLW35164W</b>
		25 (7.6)	16/3 SOW	21.4 (9.7)	<b>HBLW25163</b>	<b>HBLW25163W</b>
			16/4 SOW	21.8 (9.9)	<b>HBLW25164</b>	<b>HBLW25164W</b>
15	600	45 (13.7)	14/3 SOW	28.2 (12.8)	<b>HBLW45143</b>	<b>HBLW45143W</b>
			14/4 SOW	30.0 (13.6)	<b>HBLW45144</b>	<b>HBLW45144W</b>
		35 (10.7)	14/3 SOW	25.1 (11.4)	<b>HBLW35143</b>	<b>HBLW35143W</b>
			14/4 SOW	26.5 (12.0)	<b>HBLW35144</b>	<b>HBLW35144W</b>
		25 (7.6)	14/3 SOW	22.5 (10.2)	<b>HBLW25143</b>	<b>HBLW25143W</b>
			14/4 SOW	24.3 (11.0)	<b>HBLW25144</b>	<b>HBLW25144W</b>
18	600	80 (24.4)	12/3 SOW	97.5 (44.2)	—	<b>HBLW80123W*</b>
		75 (22.9)	12/4 SOW	107.4 (48.7)	—	<b>HBLW75124W*</b>
20	600	45 (13.7)	12/3 SOW	31.3 (14.2)	<b>HBLW45123</b>	<b>HBLW45123W</b>
			12/4 SOW	32.2 (14.6)	<b>HBLW40124</b>	<b>HBLW40124W</b>
		40 (12.2)	12/3 SOW	28.9 (13.1)	<b>HBLW35123</b>	<b>HBLW35123W</b>
			12/4 SOW	30.6 (13.9)	<b>HBLW35124</b>	<b>HBLW35124W</b>
		35 (10.7)	12/3 SOW	24.9 (11.3)	<b>HBLW25123</b>	<b>HBLW25123W</b>
			12/4 SOW	27.6 (12.5)	<b>HBLW25124</b>	<b>HBLW25124W</b>
25	600	75 (22.9)	10/3 SOW	103.8 (47.1)	—	<b>HBLW75103W*</b>
		75 (22.9)	10/3 SOW	116.2 (52.7)	—	<b>HBLW75104W*</b>
30	600	40 (12.2)	10/3 SOW	33.3 (15.1)	<b>HBLW40103</b>	<b>HBLW40103W</b>
			10/4 SOW	34.2 (15.5)	<b>HBLW35104</b>	<b>HBLW35104W</b>
		35 (10.7)	10/3 SOW	31.7 (14.4)	<b>HBLW35103</b>	<b>HBLW35103W</b>
			10/4 SOW	34.2 (15.5)	<b>HBLW35104</b>	<b>HBLW35104W</b>
		25 (7.6)	10/3 SOW	28.4 (12.9)	<b>HBLW25103</b>	<b>HBLW25103W</b>
			10/4 SOW	30.2 (13.7)	<b>HBLW25104</b>	<b>HBLW25104W</b>
40	600	45 (13.7)	8/3 SOW	106.5 (48.3)	—	<b>HBLW4583W*</b>
		60 (18.3)	8/3 SOW	123.2 (55.9)	—	<b>HBLW6083W*</b>
		45 (13.7)	8/3 SOW	122.8 (55.7)	—	<b>HBLW4584W*</b>
55	600	45 (13.7)	6/3 SOW	123.0 (55.8)	—	<b>HBLW4563W*</b>
		45 (13.7)	6/4 SOW	126.7 (57.5)	—	<b>HBLW4564W*</b>
14	600	45 (13.7)	12/8 SOW	107.4 (48.7)	—	<b>HBLW45128W*</b>
		45 (13.7)	14/12 SOW	113.5 (51.5)	—	<b>HBLW451412W*</b>

### inREACH™ Accessories

Description	Weight Lbs. (kg)	Catalog Number
Mounting bracket	2.5 (1.1)	<b>HBLIMB</b>
Mounting bracket with junction box mount	3.0 (1.4)	<b>HBLIMBJ</b>
Mounting bracket	3.5 (1.6)	<b>HBLIACMB*</b>
Mounting bracket with junction box mount	4.0 (1.8)	<b>HBLIACMBJ*</b>
340° pivot base	3.5 (1.6)	<b>HBLI340PB</b>
Replacement stop	.2 (.09)	<b>HBLI16BS</b> <b>HBLI14BS</b> <b>HBLI12BS</b> <b>HBLI10BS</b>

Note: \*Compatible with cord reel models marked with a single asterisk (\*)