



**CPA**



**CHICAGO PROTECTIVE APPAREL**

# QUESTIONS TO ASK YOUR CUSTOMERS TO HELP ASSIST IN SELECTING PROPER PPE:



- How high is the temperature you're working with?
- How heavy is the object being held?
- How long is the exposure time?
- What is the abrasion factor?
- What was being used before and how effective was it?

## FOUNDRY PROTECTION



Foundry applications might require primary and/or secondary protective clothing. Primary clothing should be worn when subjected to significant exposure to molten splash, radiant heat or flame. Secondary protective clothing is designed for continuous wear for work activities with intermittent exposure or where exposure to sparks and flame would be less likely. If primary protective clothing is required, secondary clothing should be worn under it.

### Primary Protection

Aluminized CarbonX®	Aluminized carbon Kevlar®
Aluminized Kevlar®	2 ply Twaron® Micro fiber
Aluminized Rayon®	Carbon Kevlar®

### Secondary Protection

CarbonX®	Oasis™
FR cotton (Indura® or Proban®)	
Vinex® (non ferrous metals)	

## WELDING PROTECTION



We provide welding protection in the form of clothing, blankets and screens. The intensity of welding will help determine the fabrics needed for protection. TIG welding would require less protection than high amp welding. Below are a list of materials that would protect from heavy, medium and light intensity welding.

### Clothing

Leather (heavy)
Tuff Weld® (medium)
FR cotton, Indura® or Proban® (light)

### Blankets

36 oz Silica (heavy)
35 oz Glass cloth (medium)
18 oz Heat cleaned glass (light)

## FLAME PROTECTION



Government reports note that the majority of severe and fatal burn injuries are due to the individual's clothing igniting and continuing to burn, not by the exposure itself. Below are a list of flame resistant fabrics that are appropriate to be used as secondary protection from flame. The level of protection typically rests in the fabric weight and composition.

Indura® Ultra Soft® 7 oz, 9 oz or 12 oz	CarbonX® 7.7 oz, 10 oz or 11 oz
Indura® 7 oz, 9 oz or 12 oz	Nomex IIIA® 4.5 oz, 6 oz or 9.5 oz
Proban® 7 oz, 9 oz or 11 oz	

## ARC FLASH PROTECTION



For Arc flash protective clothing we offer fabrics that have been tested to NFPA 70E specifications. Fabric weights and number of layers will dictate the level of protection that a fabric or fabric system offers. The end user must supply us with the level of protection they require. We do not calculate that for them.

Indura® Ultra Soft® (88% cotton, 12% Nylon) 8 cal, 12 cal, 20 cal, 32 cal, 43 cal
Twaron® Micro fiber and CarbonX®
Master series 44 cal and 74 cal

## CHEMICAL PROTECTION



We offer a variety of chemical resistant fabrics for aprons, sleeves, clothing and spats. Chemicals react very differently depending on their solution strength and temperature. Sample swatches of our fabrics are available for your own testing.

Hycar®, medium weight nitrile	VCF, Vinyl coated fiberglass
Neoprene, yellow	VCN, Vinyl coated Nylon
PVC, 16 oz green	

## CUT PROTECTION



Our line of cut protective garments include jackets, aprons, sleeves and leggings.

Kevlar® twill 8 oz	Nylon cane mesh
Kevlar® mesh 10 oz	Tubular knit Kevlar®



## Aluminized Clothing

Pages 2-5



## Flame Resistant Work Wear

Pages 6-7



## Arc Flash Clothing

Pages 8-19



## Nomex, CarbonX, FR Clothing

Pages 20-25



## Aprons

Pages 26-29



## Leggings, Chaps, Spats

Pages 30-33



## Sleeves and Arm Guards

Pages 34-35



## Hoods, Head Protection

Pages 36-38



## Heat Resistant Gloves

Pages 39-41



## Welding Gloves

Pages 42-43



## Glass Protection

Page 44



## Reinforced Gloves/Mitts

Page 45



## Hand Protection/Mechanics

Page 46-49



## Snakebite/Finger Guards

Page 50



## Foot Guards

Page 51



## Chemical Protection

Page 52



## Non FR, Bags, Screens, Blankets

Pages 53-55



## High Visibility Products

Page 56

## Approach Suit

Approach to within a few yards of flames and radiant heat up to 2000°F.

Jumpsuits and coats may also be adapted to be worn with breathing apparatus.

- |               |            |              |           |
|---------------|------------|--------------|-----------|
| 0647-(Fabric) | Hood       | 671-(Fabric) | Overshoes |
| 600-(Fabric)  | Jacket 30" | 234-(Fabric) | Gloves    |
| 606-(Fabric)  | Pants      |              |           |

Aluminized clothing has a wide range of applications in the industrial setting, especially where such hazards as high heat or molten metal exist. Along with the ability to reflect 95% of radiant heat, aluminized fabrics reduce the flow of ambient heat by 50% versus non aluminized fabric. Aluminized clothing helps shed both ferrous and non ferrous molten metals.

### A WORD OF CAUTION: DO NOT CONFUSE AMBIENT, CONDUCTIVE AND RADIANT HEAT!

The following definitions are given as a reference as well as vital assistance in selecting the proper clothing for heat protection:

**Ambient Heat** is the surrounding atmospheric temperature in a given situation. Examples: 65°-70°F in an office; 2000°F in a fire walk.

**Conductive Heat** is generated by direct contact with a hot surface. Examples: picking up a burner block at 600°F; leaning against a furnace wall at 1000°F.

**Radiant Heat** is generated by the sun or a source of fire, such as a fireplace or furnace, and is absorbed by masses of material struck by the heat's rays. (This is why it is cooler in the shade on a hot day.)



## Garment Styles

Jacket-30"

Coat-40"

Coat-45"



600-(Fabric)



601-(Fabric)



602-(Fabric)

# Aluminized Clothing

	30" JACKET	40" COAT	45" COAT	50" COAT	PANT	COVERALL	40" OPEN BACK COAT	HOOD	39" APRON
19 oz KEVLAR® BLEND	600-AKV	601-AKV	602-AKV	603-AKV	606-AKV	605-AKV	564-AKV-40	0647-AKV	539-AKV
19 oz RAYON	600-ARH	601-ARH	602-ARH	603-ARH	606-ARH	605-ARH	564-ARH-40	0647-ARH	539-ARH
15 oz RAYON	600-AR	601-AR	602-AR	603-AR	606-AR	605-AR	564-AR-40	0647-AR	539-AR
17 oz CARBON KEVLAR®	600-ACK	601-ACK	602-ACK	603-ACK	606-ACK	605-ACK	564-ACK-40	0647-ACK	539-ACK
10 oz CARBONX®	600-ACX10	601-ACX10	602-ACX10	603-ACX10	606-ACX10	605-ACX10	564-ACX10-40	0647-ACX10	539-ACX10
16 oz FIBERGLASS	600-AG	601-AG	602-AG	603-AG	606-AG	605-AG	564-AG-40	0647-AG	539-AG
11 oz KEVLAR® TWILL	600-AKT	601-AKT	602-AKT	603-AKT	606-AKT	605-AKT	564-AKT-40	0647-AKT	539-AKT
7 oz PBI®	600-APBI	601-APBI	602-APBI	603-APBI	606-APBI	605-APBI	564-APBI-40	0647-APBI	539-APBI
8.5 oz NOMEX®	600-AN	601-AN	602-AN	603-AN	606-AN	605-AN	564-AN-40	0647-AN	539-AN

## Primary Protective Clothing Data

Protective clothing designed to be worn for work activities during which significant exposure to molten substance splash, radiant heat, and flame is likely to occur.

Such work activities include charging, taping, and pouring, during which work is carried out in close proximity to molten substances and hot surfaces and contact with either is likely.

## Secondary Protective Clothing Data

Protective clothing designed for continuous wear for work activities in designated locations in which intermittent exposure to molten substance splash, radiant heat, and flame sources is possible.

Secondary protective clothing is designed so that it will not continue to burn after exposure to and removal of a source of ignition. Protection against metal splash and radiant heat are secondary in intent.

## Garment Styles

Coat-50"

Aluminized Pants

Aluminized Coverall

40" Open Back Coat

Combo Coat



603-(Fabric)



606-(Fabric)



605-(Fabric)



564-(Fabric)-40  
30", 45" and 50" available



600-Combo-(Fabric)



# Entry Suits

## Fire Entry Suit #FE2000-XB

The ultimate insulated suit constructed of ZETEX PLUS® high temperature fabric for maximum protection in total flame entry.

**HOOD:** Designed to be used with air mask. Inner drape flame seals. Underarm adjustment straps. Built-in shell for structural support. Hard cap with ratchet headgear. Speedy clip for hard cap support. Hardened aluminum window frame with two tempered glass lenses, plus two gold plated lenses for thermal protection.

**COAT:** Designed to be worn with a breathing apparatus. Double storm fly front. Flame seal with drawstring at coat bottom.

**PANTS:** High waist design. 2-inch wide adjustable suspenders. Adjustment straps on leg bottoms.

**BOOTS:** Designed to fit over work shoes. Rear entry with overlap snap closure and adjustable take-up straps. Insulated wire reinforced sole of flame resistant neoprene fiberglass riveted to boot cover. All straps and bindings are ZETEX PLUS®.

**MITTS:** Heavyweight all ZETEX PLUS® construction.

**WEIGHT:** 48 lbs (22 kg)

## Kiln Suit #KL850-XB

Highly insulated suit with aluminized ZETEX® fabric outer shell and internal vapor barrier.

**HOOD:** Designed like the fire entry hood. Hardened aluminum window frame with tempered glass lenses.

**COAT:** Designed to be worn with a breathing apparatus. Double storm fly front. Flame seal with drawstring at coat bottom.

**PANTS:** High waist design. 2-inch wide adjustable suspenders. Adjustable straps on leg bottoms. ZETEX PLUS® reinforced knee pads.

**BOOTS:** Designed to fit over work shoes. Heavy insulated upper boot cover with zipper and storm fly. Adjustable tightening straps. 1-inch wooden sole with anti-skid bottoms. Inside leather toe and ankle adjustable straps. ZETEX PLUS® binding.

**MITTS:** ZETEX PLUS® palm and thumb. Aluminized back and cuff.

## Proximity Suit #PR750-(XB)

Insulated suit with aluminized ZETEX® fabric outer shell and double vapor barrier.

**HOOD:** Full shoulder length drape. Adjustable underarm straps. Built-in shell for structural support. Hard cap with ratchet adjustment. Speedy clip for hard cap support. 6" x 9¼" gold window and aluminum retainer. Two side wing locks for holding lens and retainer in place.

**COAT:** Available with or without breathing apparatus accommodation. Double storm fly front. Flame seal with drawstring at coat bottom.

**PANTS:** High waist design. 2-inch wide adjustable suspenders. Adjustment straps on leg bottoms.

**BOOTS:** Designed to fit over work shoes. Leather insulated soles. Adjustment tightening straps. ZETEX PLUS® binding.

**MITTS:** ZETEX PLUS® palm and thumb. Aluminized back and cuff.

## Approach Suit #AP550-(XB)

Vapor barrier lining of flame retardant neoprene coated FR poly-cotton.

**HOOD:** Designed like proximity hood with built-in shell for structural support. Hard cap with ratchet adjustment. Speedy clip for hard cap support. Full-length drape is not insulated.

**COAT:** Tailored sleeves with snap adjustment. Covered front snaps. Available with or without breathing apparatus accommodation.

**PANTS:** High waist design. 8-point all elastic adjustable suspenders (firefighter's type). Snapped triangular storm fly front. Snap adjustment on leg bottoms.

**BOOTS:** Designed to fit over work shoes. Leather soles and heels. Adjustment tightening straps.

**GLOVES:** Gauntlet style with leather palms. S.E.F. lining in fingers.



## APPLICATIONS

Our suits are used in industries where protection from high heat sources, including steam and hot liquids or vapors, is required. Examples would be refineries, petrochemical plants, foundries and casting plants, basic steel and aluminum industries, glass and ceramic plants, and laboratories.

Our FIRE ENTRY suit is an essential safety measure for industries dealing with volatile or highly flammable materials. The KILN and PROXIMITY suits are used for maintenance tasks in high heat areas such as kiln or oven maintenance and repair. The Proximity suit, with its double vapor barrier, should be used when steam and volatile materials present an additional hazard. The Kiln suit is suitable for short duration in ambient heat up to 1000°F (530°C) and the Proximity suit in ambient heat up to 500°F (260°C).

# Proximity Suits/Cooling Vests

Proximity Suit

Approach Suit, Lined



The non-insulated APPROACH suit is used in just about every industry requiring heat protective clothing. It is suitable where ambient temperatures do not exceed 200°F (93°C).

All suits with aluminized ZETEX® outer shell fabric are suitable for exposure to radiant heat up to 2000°F (1093°C).

Breathing apparatus is required for the Kiln and Entry suits, and is optional for the Proximity and Approach suits. We do, however, recommend that Proximity suits be ordered with breathing apparatus accommodation.

ALWAYS have two people suited with Fire Entry, Kiln and Proximity suits to work in relays and to aid each other.

Gel Pack Cooling Vest



## FR-7A® Cooling Vest #CV-VEST

One size fits all. Requires 6 each polyethylene gel packs per vest. Three each in front and 3 each in back. Packs are frozen and then placed in the foil insulated pockets to keep wearer cool in hot environments.

Gel Packs #GCS

Vortex Cooling Vest



## Vortex Cooling Vest #HCBV-VEST

Vortex head and body cooling system uses 70-100 psi (4.8-6.9 bar) compressed air to cool a worker up to 60°F differential from the air inlet temperature. Vest makes most efficient use of cooling power by properly distributing tempered air over the body.



# Flame Resistant Cotton Workwear

## PROBAN®/FR-7A®

Proban® / FR-7A® 100% cotton fabrics by Westex are guaranteed to retain their flame resistance to 25 industrial or 50 home launderings. FR-7A® fabrics are offered as an economical alternative for garments not expected to wear beyond the certification point.

**Weight:** 9 - 9½oz sateen, 11oz twill.

**Most popular colors:** Visual green, navy, yellow, orange, and red.

	30" COAT	40" COAT	45" COAT
9 oz GREEN	600-GR	601-GR	602-GR
9 oz NAVY	600-NS	601-NS	602-NS
9 oz ORANGE	600-OS	601-OS	602-OS
9 oz RED	600-RS	601-RS	602-RS
11 oz GREEN	600-GW	601-GW	602-GW
11 oz NAVY	600-NW	601-NW	602-NW
11 oz ORANGE	600-OW	601-OW	602-OW
11 oz RUSSET	600-RRT	601-RRT	602-RRT
7 oz GREEN	600-GR7	601-GR7	602-GR7

## Garment Styles

30" Jacket & Pant

40" Coat

45" Coat

50" Coat



600-(Fabric) and 606-(Fabric)



601-(Fabric)



602-(Fabric)



603-(Fabric)

# Flame Resistant Cotton Workwear

	50" COAT	COVERALL	PANT	SHIRT	CAPE SLEEVE	19" BIB	BIB OVERALL
9 oz GREEN	603-GR	605-GR	606-GR	625-GR	577-GR	BIB-GR-19	618-GR
9 oz NAVY	603-NS	605-NS	606-NS	N/A	577-NS	BIB-NS-19	618-NS
9 oz ORANGE	603-OS	605-OS	606-OS	N/A	577-OS	BIB-OS-19	618-OS
9 oz RED	603-RS	605-RS	606-RS	N/A	577-RS	BIB-RS-19	618-RS
11 oz GREEN	603-GW	605-GW	606-GW	N/A	577-GW	BIB-GW-19	618-GW
11 oz NAVY	603-NW	605-NW	606-NW	N/A	577-NW	BIB-NW-19	618-NW
11 oz ORANGE	603-OW	605-OW	606-OW	N/A	577-OW	BIB-OW-19	618-OW
11 oz RUSSET	603-RRT	605-RRT	606-RRT	N/A	577-RRT	BIB-RRT-19	618-RRT
7 oz GREEN	603-GR7	N/A	N/A	625-GR7	N/A	N/A	N/A

## Garment Styles

Coverall

Cape Sleeve

Bib Overall

Shirt & Pant



605-(Fabric)

577-(Fabric)  
Bib-19-(Fabric)

618-(Fabric)

625-(Fabric) and 606-(Fabric)

# HRC2 DAILY WEAR



## ULTRA SOFT® Medium Blue Work Shirt

7 oz Ultra Soft®  
Medium Blue, 8.7 ATPV  
**Part #625-USB-(size)**

Category 2



## ULTRA SOFT® Khaki Work Shirt

7 oz Ultra Soft®  
Khaki, 8.7 ATPV  
**Part #625-USK-(size)**

Category 2



## ULTRA SOFT® Navy Work Pant

9 oz Navy Ultra Soft®,  
12.4 ATPV  
**Part # 606-USN-(waist x inseam)**

Category 2

# COVERALLS, SHIRTS, PANTS



## INDURA® Navy Coverall

9 oz Navy Indura®  
10 ATPV

**Part # 605-IND-N-(size)**

Category 2

## ULTRA SOFT® Khaki or Navy Coverall

7 oz Khaki Ultra Soft®, 8.7 ATPV

**Part # 605-USK-(size)**

9 oz Navy Ultra Soft®, 12 ATPV

**Part # 605-USN-(size)**

Category 2

## DENIM RUGGED TWILL Relaxed Jean

12 oz Denim Inherently FR

14.2 ATPV

**Part # 606-DFR-(waist x inseam)**

Category 2

# SWEATSHIRTS/T-SHIRTS



## ULTRA SOFT® Fleece Full Zip Hooded Sweatshirt

Ultra Soft® Fleece. Sewn with  
Nomex® Thread. Navy, 21.8 EBT  
**Part # 615-USFN-(size)**

Category 2



## ULTRA SOFT® Fleece Hooded Sweatshirt

Ultra Soft® Fleece. Sewn with  
Nomex® Thread. Navy, 21.8 EBT  
**Part # 617-USFN-(size)**

Category 2



## ULTRA SOFT® Fleece Crewneck Sweatshirt

Ultra Soft® Fleece. Sewn with  
Nomex® Thread. Navy, 21.8 EBT  
**Part # 620-USFN-(size)**

Category 2



## FR TREATED COTTON Interlock Short Sleeve Shirt

Sizes: S-5XL Colors: Navy, Orange, Gray  
10.9 ATPV  
**Part # 610-FRC-SS-(color)-(size)**


Category 2



## FR TREATED COTTON Interlock Long Sleeve Shirt

Sizes: S-5XL Colors: Navy, Orange, Gray  
10.9 ATPV  
**Part # 610-FRC-LS-(color)-(size)**

Category 2



## Insulated Coverall

Royal part # 605-CC-USRB-(size) S-4XL in regular  
 Red part # 605-CC-USR-(size) LT-4XLT in tall

Sizes available  
 S-4XL in regular  
 LT-4XLT in tall

Our Indura® Ultra Soft® Deluxe cold climate FR work wear with wind barrier has proven warmth and flame resistance.



## Insulated Parka & Bib

Royal part # 600-CC-USRB-(size)  
 Royal part # 618-CC-USRB-(size)

Red part # 600-CC-USR-(size)  
 Red part # 618-CC-USR-(size)

## Durable FR Winter liners



9 oz woven Indura® Ultra Soft® fleece lined.  
**Cape style (pictured)**  
 # EL-29D  
**Short no cape style**  
 # EL-27D



Knited Indura® Ultra Soft® Unlined, napped side to skin.  
**Cape style (pictured)**  
 # WL-29D

# ARC FLASH PROTECTION KITS



Clothing in our HRC2 kits is manufactured using single layers of Ultra Soft®.

Choose between 8, 12, and 20 cal/cm² kits.

Plug 8, 12, or 20 into below kit part numbers when ordering.



## COVERALL KIT

### Part # AG12-CV-(size) Components


- Coverall (SW-605-12)
- Hard Cap (E2RW-SLT)
- Face Shield (WV-ARC-XL-CN)
- Chin Cup (SW-CN-G)
- Cap Bracket (HB-2-CAP)
- Knit Nomex Hood (KN-51-NFPA)
- Rubber Gloves (LRIG-0-11)
- Leather Protector Gloves (PG-0-ADJS)
- 12" Glove Bag (GB-12)
- Gear Bag (909-ARC)
- Safety Glasses (SW-SG)
- Ear Plugs (SW-EAR)



## JACKET & BIB KIT

### Part # AG12-(size) Components

- Jacket (SWJ-12)
- Bib Overall (SWB-12)
- Hard Cap (E2RW-SLT)
- Face Shield (WV-ARC-XL-CN)
- Chin Cup (SW-CN-G)
- Cap Bracket (HB-2-CAP)
- Knit Nomex Hood (KN-51-NFPA)
- Rubber Gloves (LRIG-0-11)
- Leather Protector Gloves (PG-0-ADJS)
- 12" Glove Bag (GB-12)
- Gear Bag (909-ARC)
- Safety Glasses (SW-SG)
- Ear Plugs (SW-EAR)



PROTECTION  
SELECT  
8,12,20  
ATPV  
FROM CPA



**COAT & LEGGING KIT**  
Part # AG12-CL-(size) Components

- Coat (SWC-12)
- Leggings (SW-401-12)
- Hard Cap (E2RW-SLT)
- Face Shield (WV-ARC-XL-CN)
- Chin Cup (SW-CN-G)
- Cap Bracket (HB-2-CAP)
- Knit Nomex Hood (KN-51-NFPA)
- Rubber Gloves (LRIG-0-11)
- Leather Protector Gloves (PG-0-ADJS)
- 12" Glove Bag (GB-12)
- Gear Bag (909-ARC)
- Safety Glasses (SW-SG)
- Ear Plugs (SW-EAR)

**JACKET & PANT KIT**  
Part # AG12-JP-(size) Components

- Jacket (SWJ-12)
- Pant (SWP-12)
- Hard Cap (E2RW-SLT)
- Face Shield (WV-ARC-XL-CN)
- Chin Cup (SW-CN-G)
- Cap Bracket (HB-2-CAP)
- Knit Nomex Hood (KN-51-NFPA)
- Rubber Gloves (LRIG-0-11)
- Leather Protector Gloves (PG-0-ADJS)
- 12" Glove Bag (GB-12)
- Gear Bag (909-ARC)
- Safety Glasses (SW-SG)
- Ear Plugs (SW-EAR)

# ARC FLASH PROTECTION KITS



Clothing in these HRC3 & 4 kits is manufactured using multiple layers of Ultra Soft®.

Choose between 32 and 43 cal/cm² kits.

Plug 32 or 43 into below kit part numbers when ordering.



## COVERALL KIT

### Part # AG43-CV-(size) Components

- Coverall (SW-605-43)
- Hood (SWH-43)
- Hard Cap (E2RW-SLT)
- Rubber Gloves (LRIG-2-14)
- Leather Protector Gloves (LLPG-12)
- 15" Glove Bag (GB-15)
- Gear Bag (909-ARC)
- Safety Glasses (SW-SG)
- Ear Plugs (SW-EAR)



## JACKET & PANT KIT

### Part # AG43-JP-(size)

- Jacket (SWJ-43)
- Over Pant (SWP-43)
- Hood (SWH-43)
- Hard Cap (E2RW-SLT)
- Rubber Gloves (LRIG-2-14)
- Leather Protector Gloves (LLPG-12)
- 15" Glove Bag (GB-15)
- Gear Bag (909-ARC)
- Safety Glasses (SW-SG)
- Ear Plugs (SW-EAR)



**JACKET & BIB KIT**

**Part # AG43-(size) Components**

- Jacket (SWJ-43)
- Bib Overall (SWB-43)
- Hood (SWH-43)
- Hard Cap (E2RW-SLT)
- Rubber Gloves (LRIG-2-14)
- Leather Protector Gloves (LLPG-12)
- 15" Glove Bag (GB-15)
- Gear Bag (909-ARC)
- Safety Glasses (SW-SG)
- Ear Plugs (SW-EAR)

**COAT & LEGGING KIT**

**Part # AG43-CL-(size) Components**

- Coat (SWC-43)
- Leggings (SW-401-43)
- Hood (SWH-43)
- Hard Cap (E2RW-SLT)
- Rubber Gloves (LRIG-2-14)
- Leather Protector Gloves (LLPG-12)
- 15" Glove Bag (GB-15)
- Gear Bag (909-ARC)
- Safety Glasses (SW-SG)
- Ear Plugs (SW-EAR)

# ARC FLASH PROTECTION KITS



44 and 74 cal/cm<sup>2</sup> kits are manufactured using inherently FR materials.

Choose between 44 and 74 cal/cm<sup>2</sup> kits and plug into below kit part numbers when ordering.

Lightweight options for HRC4.



## MASTER SERIES JACKET & PANT KIT Part # AG44-JP-(size) Components

- Jacket (SWJ-MS44)
- Over Pant (SWP-MS44)
- Hood (SWH-44)
- Hard Cap (E2RW-SLT)
- Rubber Gloves (LRIG-2-14)
- Leather Protector Gloves (LLPG-12)
- 15" Glove Bag (GB-15)
- Gear Bag (909-ARC)
- Safety Glasses (SW-SG)
- Ear Plugs (SW-EAR)


## COAT & LEGGING KIT Part # AG44-CL-(size) Components

- Coat (SWC-44)
- Leggings (SW-401-44)
- Hood (SWH-44)
- Hard Cap (E2RW-SLT)
- Rubber Gloves (LRIG-2-14)
- Leather Protector Gloves (LLPG-12)
- 15" Glove Bag (GB-15)
- Gear Bag (909-ARC)
- Safety Glasses (SW-SG)
- Ear Plugs (SW-EAR)

HRC4: 44 & 74 CAL/CM<sup>2</sup>

# Refresh™

## AIR FLOW SYSTEM



### JACKET & BIB KIT

#### Part # AG44-(size) Components

Jacket (SWJ-44)

Bib Overall (SWB-44)

Hood (SWH-44)

Hard Cap (E2RW-SLT)

Rubber Gloves (LRIG-2-14)

Leather Protector Gloves (LLPG-12)

15" Glove Bag (GB-15)

Gear Bag (909-ARC)

Safety Glasses (SW-SG)

Ear Plugs (SW-EAR)

Increase your comfort and productivity with CPA's Refresh™ air flow system.

Full Kit	part # RF-KIT
Rechargeable battery	part # RF-BATT
Bag of 3 filters	part # FR-FLTR

CPA's waist belt unit minimizes stagnant air in your hood by delivering a steady stream of ambient air flow.

- ◆ Our Refresh™ system can be used with any CPA Arc hood as well as with any of our HRC2 face shields.
- ◆ Refresh™ fans are not NIOSH approved and do not provide breathable air filtration. They are a means to provide ambient air flow only.
- ◆ Refresh™ full kit includes: Fan belt unit with FR cover, hose with FR cover, hard cap with diffuser, rechargeable battery, AC power adapter and two filters.

# GLOVES



## CLASS 0 GLOVE KIT

Class 0 Rubber Glove

**LRIG-0-11-(size)**

Leather Protector

**PG-0-ADJS-(size)**

Glove Bag

**GB-12**

COMPLETE KIT

**GK-0-11-(size)**

## CLASS 2 GLOVE KIT

Class 2 Rubber Glove

**LRIG-2-14-(size)**

Leather Protector

**LLPG-12-(size)**

Glove Bag

**GB-15**

COMPLETE KIT

**GK-2-14-(size)**

## GLOVE TALC

An accessory for gloves, the 5 oz squirt bottle talc helps absorb moisture and perspiration. Facilitates donning and doffing of gloves.

**Style # TALC-5-OZ**

## INSULATED RUBBER GLOVES

	11" Length	14" Length	16" Length	18" Length
<b>Class 00</b>	<b>LRIG-00-11-(size)</b>	<b>LRIG-00-14-(size)</b>	n/a	n/a
<b>Class 0</b>	<b>LRIG-0-11-(size)</b>	<b>LRIG-0-14-(size)</b>	n/a	n/a
<b>Class 1</b>	n/a	<b>LRIG-1-14-(size)</b>	<b>LRIG-1-16-(size)</b>	<b>LRIG-1-18-(size)</b>
<b>Class 2</b>	n/a	<b>LRIG-2-14-(size)</b>	<b>LRIG-2-16-(size)</b>	<b>LRIG-2-18-(size)</b>
<b>Class 3</b>	n/a	<b>LRIG-3-14-(size)</b>	<b>LRIG-3-16-(size)</b>	<b>LRIG-3-18-(size)</b>
<b>Class 4</b>	n/a	n/a	n/a	<b>LRIG-4-18-(size)</b>

## LEATHER PROTECTOR GLOVES

	10" Length	12" Length	14" Length	16" Length
<b>Low Voltage</b>	<b>PG-0-ADJS</b>	n/a	n/a	n/a
<b>High Voltage</b>	<b>LLPG-10-(size)</b>	<b>LLPG-12-(size)</b>	<b>LLPG-14-(size)</b>	<b>LLPG-16-(size)</b>

## 14" SWITCHING GLOVES

Not Electrically Insulated

<b>SW-234-12</b>	12 Cal/cm <sup>2</sup> Gloves
<b>SW-234-20</b>	20 Cal/cm <sup>2</sup> Gloves
<b>SW-234-32</b>	32 Cal/cm <sup>2</sup> Gloves
<b>SW-234-43</b>	43 Cal/cm <sup>2</sup> Gloves
<b>SW-234-74</b>	74 Cal/cm <sup>2</sup> Gloves

Class	Proof-test [A_C]	Max. use Voltage [A_C]
00	2,500	500
0	5,000	1,000
1	10,000	7,500
2	20,000	17,000
3	30,000	26,500
4	40,000	36,000



## 10 CAL FACE SHIELD UNIT

Face Shield	WV-ARC-XL
Cap Bracket	HB-2-CAP
Hard Cap	E2RW-(Color)
COMPLETE KIT	SW-WVK-(Color)

## 12 CAL CHIN FACE SHIELD UNIT

Face Shield	WV-ARC-XL-CN
Chin Cup	SW-CN-G
Cap Bracket	HB-2-CAP
Hard Cap	E2RW-(Color)
COMPLETE KIT	SW-WVCK-(Color)

## BRACKETS

Description	Part Number
Universal Cap Bracket	HB-2-CAP
Slotted Cap Bracket	HB-2-SLT
Universal Hat Bracket	HB-2-UNV

## ACCESSORIES

Chin Guard	SW-CN-G
Hard Cap	E2RW-(Color)
Hard Hat	E1RW-(Color)
Safety Glasses	SW-SG



## STORAGE BAG

Fleece lined storage bag with drawstring. Sized to accommodate face shield with hard cap.

Style # SW-SB



## CARBONX<sup>®</sup> ULTIMATE HOOD

The CarbonX<sup>®</sup> Ultimate flared style hood provides maximum coverage. Our hood features flat stitching and seamless chin area for better fit and comfort. The 2-Ply version has an ATPV of 23 cal/cm<sup>2</sup> square. Our 3-ply version has an ATPV of 53 cal/cm<sup>2</sup>.

Style # KCF-51 2 Ply  
Style # KC3-51 3 Ply



## NOMEX<sup>®</sup> BLEND

Our Nomex<sup>®</sup> blend hood offers economy and 10 cal/cm<sup>2</sup> protection. One size.

Style # KN-51-NFPA



# Nomex® Clothing

Nomex® IIIA from DuPont is an inherently flame resistant fabric. This aramid and static dissipative fiber blend helps shield the wearer from flames, flash fires and electric arcs. Nomex® IIIA clothing is extremely durable, light weight and inherently flame resistant. We offer Nomex® IIIA garments in 3 weights; 4.5oz, 6oz, and 9.5oz. Nomex® IIIA is available in a variety of colors.

Coats available in 30", 40", 45" and 50" lengths.

## Garment Styles

### Coveralls



605-(Fabric)

### Nomex® IIIA Coveralls

Standard coverall features six pockets: 2 breast, 2 rear, 2 front; covered snap front and elasticized waistband.

**605-NMX-4.5 oz.-Orange** (shown)

**605-NMX-6 oz.-Royal Blue** (shown)

Additional colors and weights available.

**605-XK-NMX-6 oz.-Khaki** (shown)

**605-IFRB-NMX-6 oz.-Royal Blue** (shown)

## Nomex® Product Numbers

	30" JACKET	50" COAT	COVERALL	PANT	SHIRT
4.5 oz NAVY	600-NMX-4.5-N	603-NMX-4.5-N	605-NMX-4.5-N	N/A	625-NMX-4.5-N
4.5 oz ORANGE	600-NMX-4.5-O	603-NMX-4.5-O	605-NMX-4.5-O	N/A	625-NMX-4.5-O
6 oz NAVY	600-NMX-6-N	603-NMX-6-N	605-NMX-6-N	606-NMX-6-N	625-NMX-6-N
6 oz ROYAL BLUE	600-NMX-6-RB	603-NMX-6-RB	605-NMX-6-RB	606-NMX-6-RB	625-NMX-6-RB
9.5 oz GREEN	600-NMX-9.5	603-NMX-9.5	605-NMX-9.5	606-NMX-9.5	N/A

### Knit Nomex® Undergarments



**KN-53** Turtleneck long sleeve shirt

**KN-54** Crew neck long sleeve shirt (shown)

**KN-55** Ankle length bottoms (shown)

**KN-56** Crew socks 11" length (sizes 8-15)

### Knit Hoods

Knit Nomex® and Nomex®-blend hoods.



**KN-52** Short style, 1-ply, 6 oz. (shown)

**KN-50** Short style, 2-ply, 6 oz.



**2001** NFPA firefighter's hood. Knit PBI outer, knit wool inner. Cold weather protection.



**PBI-51** PBI fabric, (shown)

**FL-KN-51** Long style, 2-ply top, 1-ply bib, 6 oz. Not NFPA approved.



**KN-51-NFPA** 2-ply knit hood. Meets 70E NFPA specs.

### Hot Not™

Heat resistant glove and sleeve of Nomex® III for constant handling of materials up to 500°F, intermittently up to 700°F. For hot solid surfaces, not for heavy welding or molten materials.

**HNG** Glove

**HNS** Sleeve






CarbonX® fabrics provide superior flame resistance in an inherently flame resistant fabric.

Our line of work wear is available in an 11oz. black woven or a 10oz. deep navy abrasion resistant twill. This revolutionary new fabric has the following properties:

- Higher Limited Oxygen Index (LOI)
- UV Resistance
- Non-shrinking
- Non-melting
- Odor absorbing



**CALL FOR BROCHURE**

## Garment Styles

Bib Overall

Coverall

30" Jacket/Pant



618-(Fabric)

605-(Fabric)

600-(Fabric) and 606-(Fabric)

# CarbonX® Workwear

	30" JACKET	45" COAT	50" COAT	PANT	COVERALL	BIB OVERALL
11 oz BLACK	600-CX11	602-CX11	603-CX11	606-CX11	605-CX11	618-CX11
10 oz NAVY	600-CX10	602-CX10	603-CX10	606-CX10	605-CX10	618-CX10



## Undergarment Styles

Short Top/Short Pant | Long Top/Long Pant

### Undergarments

Undergarments are made of a single layer of 7.7 oz interlock knit. The fabric has a TPP rating of 14.7 and an ATPV of 12.3 cal/cm2. Tops and bottoms are available in sizes S-4XL. Socks are one size only.

- Long sleeve top **CX-54-(size)**
- Short sleeve top **CX-64-(size)**
- Long pant **CX-55-(size)**
- Short Pant **CX-65-(size)**
- Socks **CX-56-22**
- 16" Sleeves **CX-16**
- 18" Sleeves **CX-18-TH**





# Flame Retardant Clothing



## VINEX

### Vinex® • FR9B

Vinex® flame and aluminum splash resistant fabrics by Westex are a blend of 85% vinyl and 15% polyynosic rayon.

Vinex® fabrics are inherently flame resistant and have been used extensively and continuously since 1985 for protective clothing for workers exposed to molten aluminum in major aluminum producing facilities throughout the world. Vinex® shows a unique ability to shed molten aluminum.

**Weights/Color:**

6 oz., Medium blue shirt weight  
8½ oz., Navy pant, jacket, and shirt weight.

### Oasis™

A molten metal splash resistant fabric from Southern Mills combines comfort and protection in a fabric that is inherently flame resistant.

Oasis is made from a blend of fibers including Lenzing FR for enhanced comfort and Nylon for added durability. Oasis™ is available in three weights:

7.5 oz, 10 oz, and 12 oz.

### Vinex® Product Numbers

	30" JACKET	45" COAT	50" COAT	COVERALL	PANT	SHIRT
6 oz MEDIUM BLUE	N/A	N/A	N/A	N/A	N/A	625-FR9B-MB
8.5 oz NAVY	600-FR9B	602-FR9B	603-FR9B	605-FR9B	606-FR9B	625-FR9B-N

### Oasis™ Product Numbers

	30" JACKET	45" COAT	50" COAT	COVERALL	PANT	SHIRT
7.5 oz COOL BLUE	N/A	N/A	N/A	N/A	N/A	625-ON7
10 oz NAVY	600-ON	602-ON	603-ON	605-ON	606-ON	625-ON
12 oz NAVY	600-ON12	602-ON12	603-ON12	605-ON12	606-ON12	625-ON12

# Leather Welder's Clothing



Our leather welder's clothing is made from garment quality side split leather. Its soft and pliable feel keeps it a favorite choice for welders to protect against heat, sparks and splatter. Jackets and cape sleeves are available in sizes S-5XL.

	30" JACKET	CAPE SLEEVE	19" BIB	COVERALL	PANT	CHAP	48" SPLIT LEG APRON
RUST SPLIT LEATHER	600-CL	577-CL	BIB-CL-19	605-CL	606-CL	555-CL	550-CL-48

## Garment Styles

30" Jacket

Cape Sleeve & Bib

Chaps

Split Leg Apron



600-CL

577-CL  
BIB-CL-19

555-CL

550-CL-48

Safety aprons are available in all fabrics with your choice of length and closure. Standard apron closure is snap or eyelet. Please specify any other option desired. (See pages 55-56 for complete fabric list.)

**How to Order Aprons**    Length **536** — Fabric **GR**

**Apron Lengths**

<b>530</b>	30"
<b>536</b>	36"
<b>539</b>	39"
<b>542</b>	42"
<b>548</b>	48"
<b>W24</b>	18" waist

**Apron Fabric**

<b>AKV</b>	Aluminized Kevlar® blend
<b>ARH</b>	Aluminized rayon heavy
<b>CL</b>	Chrome leather gray or rust
<b>BD</b>	Blue denim, non-FR
<b>FRD</b>	Fire resistant duck, non-durable
<b>GR</b>	Green FR-7A cotton
<b>GW</b>	Green FR-7A twill
<b>HY</b>	Hycar
<b>KTW</b>	Kevlar® twill
<b>KV</b>	22 oz. aramid-glass blend
<b>NMX-9.5</b>	9.5 oz. Nomex® III A
<b>NS</b>	FR-7A navy cotton

(Additional fabrics available.)



## Closures



1. Snap Buckle and Webbing
2. Eyelets and Leather Ties
3. Eyelets and Cotton Ties
4. Eyelets and Nylon Ties
5. Snap Hook and D-Ring
6. Velcro® Tabs and Velcro® Straps
7. Nexus Clip

## Waist Aprons

- W24** Standard size 24" x 18"
- 560** 30" x 18" with 20" x 14" steel-stapled patch
- 561** Machinist apron—24" x 18". Has quick-release fasteners for safety when working near rotating parts.
- 563** 24" x 24" waist apron
- 830** 24" x 18" with 10" x 14" plain patch
- 832** 24" x 18" with 10" x 14" steel-stapled patch
- 835** 24" x 18" entirely steel-stapled—no patch



## Chrome Leather Reinforced Aprons

### 42" Apron

Chrome leather bib apron with belly patch reinforced with steel staples, or plain as shown.

#### Steel-Stapled (10" x 14") Belly Patch

- 825** 24" x 30"
- 826** 24" x 36"
- 827** 24" x 42"
- 828** 24" x 48"

#### Plain Leather (10" x 14") Belly Patch

- 820** 24" x 30"
- 821** 24" x 36"
- 822** 24" x 42"
- 823** 24" x 48"



## Split Leg Apron (waist type)

**P-829 Plain** (as shown) 24" x 24". Two straps at leg. Adjustable web belt at waist.

**S-829 Steel-Stapled** 24" x 24". Same as above with full steel stapled reinforcement throughout for further abrasion resistance.



## Kick-Back Apron

Protects lower abdomen, stomach, groin and chest from kick-back and similar hazards.

(See photographs for individual apron coverage.) Constructed of heavy wool and Kevlar® sewn between 2 layers of chrome leather. Fastens with an adjustable web belt. Aprons are not puncture proof, and should not be tested on wearer.

KBA-bib type 16" x 28"    KBA-standard 24" x 18"    KBA-tapered 16" x 13"    KBA-tapered 21" x 17"

### Garment Styles



#### KBA-High Waist

19" long x 28" wide duck. 8" x 14" fiber "arch" withstands heavy blows. Heavy felt quilted between two layers of duck, above and below fiber. Adjustable web fasteners at bib and waist. Excellent protection against lumber kick-back from rip saws.



#### Carpenter's Apron

Bib type 19" x 26" or waist type 18" x 9" standard with 2 pockets. 10 oz. fire resistant duck (FRD) or non-fire resistant denim (BD). Custom pocket design available.



# Denim Aprons

## Denim Shop Apron

### 532-2P (Most popular)

General purpose blue denim apron. Not flame retardant. 28" x 36" two-pocket style, one bib and one waist. Hemmed on all sides and has sewn on ties.



#### No Pocket

#532-NP 28"W x 36"H  
Old #NP-532-BD No pockets.  
Sewn denim neck tie &  
sewn nylon waist ties.



#### ONE Pocket

#532-1PE 28"W x 36"H  
1 waist pocket.  
Sewn denim neck  
& waist ties.



#### ONE Pocket

#532-1P 28"W x 36"H  
1 waist pocket,  
Sewn denim neck tie &  
sewn nylon waist ties.



#### TWO Pocket

#532-2PE 28"W x 36"H  
1 bib and 1 waist pocket.  
Sewn denim neck  
& waist ties.



#### TWO Pocket

#532-2P 28"W x 36"H  
Old #532-BD 1 bib & 1 waist  
pocket. Sewn denim neck tie  
& sewn nylon waist ties.



#### THREE Pocket

#532-3PE 28"W x 36"H  
3 pockets.  
Sewn denim neck  
& waist ties.



# Split Leg Aprons and Hip Leggings

Our split leg aprons, chaps and hip leggings are available in a variety of styles, lengths and fabrics. See page 27 for many of our most popular styles. Please specify or call us if you require unique closures or features.



**550-FRD-48-EL**  
Additional lengths available

No need to go to Holland for wood shoes.

## "Hot Foot" Wood Sole That Bends!



#CPA-351-(size)  
Men's sizes:  
S (7-8)  
M (9-10)  
L (11-12)  
XL (13-14)  
XXL (15-16)

MADE IN USA

- Made of 1 1/8 inch thick seasoned wood
- Two strong sole leather hinges
- Straps on quickly over any shoe
- Heat-resistant and puncture-resistant

### Attached Hip Leggings



#### HL-777-(Fabric)

Attached hip legging with adjustable belt top. 36" outseam. Please specify if snap or Velcro® closure is needed at back of leg.

### Hip Leggings



#### 470-(Fabric)

Slip-on hip leggings are interchangeable for either leg. 36" outseam. Standard with flare. Adjustable snap strap loops at top accommodates your belt. Specify for eyelet option (shown).

	SPLIT LEG APRON 48"	ATTACHED HIP LEGGINGS	HIP LEGGINGS	COWBOY STYLE CHAP	CHAP PANTS	"STEP-IN" CHAP
19 oz ALUMINIZED KEVLAR®	550-AKV-48-SW	HL777-AKV	470-AKV	555-AKV	CP777-AKV	778-AKV
19 oz ALUMINIZED RAYON	550-ARH-48-SW	HL777-ARH	470-ARH	555-ARH	CP777-ARH	778-ARH
CHROME LEATHER	550-CL-48-SW	HL777-CL	470-CL	555-CL	CP777-CL	778-CL
14.9 oz FIRE RESISTANT DUCK	550-FRD14.9-48-SW	HL777-FRD14.9	470-FRD14.9	555-FRD14.9	CP777-FRD14.9	778-FRD14.9
9 oz GREEN FR COTTON	550-GR-48-SW	HL777-GR	470-GR	555-GR	CP777-GR	778-GR
8 oz KEVLAR® TWILL	550-KTW-48-SW	HL777-KTW	470-KTW	555-KTW	CP777-KTW	778-KTW
9 oz NAVY FR COTTON	550-NS-48-SW	HL777-NS	470-NS	555-NS	CP777-NS	778-NS

## Garment Styles

Cowboy Style Chap

Chap Pants

"Step-In" Chap



### 555-(Fabric)

Adjustable belt top. Rear leg straps. 39" outseam. Open back.



### CP-777-(Fabric)

Adjustable belt top. 32" inseam. No flare.



### 778-(Fabric)

Step-in cuffs, adjustable rear leg straps, adjustable belt top, 39" outseam.



# Leggings and Overshoes

## Standard Spring Leggings

**300**

Spring frame permits instant adjustment and removal. Wide rear flap provides full protection to the back of the leg.

**14" height, 6" flare**



300-CL



300-KV

## Side Bar Leggings

**1310**

Unique combination of adjustable snap top and vertical metal side bar allows quick release at bottom of legging. Two fiber shin shields inside front of legging protect against minor blows. **14" height, 5½" flare**



1310-CL



1310-FRD

## Replaceable Cover Leggings

**333-CL**

Deluxe style with removable cover for economical replacement cost. Snap out steel spring frame assures full time comfortable fit. Metal instep bar forms and holds flare to shoe. (Thick rubber flare standard with leather legging, as shown.)

**14" height, 7" flare**



## Full Vertical Velcro™ Closure Leggings

**401**

Full Velcro® closure. Fast removal, lightweight protection. Metal instep bar standard. **14" height, 8½" flare**



401-AKV



401-CL

## Overshoe

**671-AKV**

Overshoes are designed to be worn over workshoes. Sole is ¼" thick, skid resistant, treated neoprene belting. Two adjustable leather straps close front of overshoe.

**Standard height: 12"**  
**Also available in 8" and 16" heights**

One size fits most.



All leggings and spats available in your choice of fabric.

# Spats/Knee pads/Pants Guards

## Elastic Top Spat

**E485**

Elastic top spat. Rear snap closure. Adjustable instep strap. **7" height, 6" flare**



## Safety Spat

**485**

Standard safety spat. Rear Velcro® closure. Easily adjusted or removed. **7" height, 6" flare**



## Closed Toe Style Spat

**E485-CL-8**

Closed toe style spat. Elastic top. Rear snap closure. Flare cups toe of shoe. **7" height, Closed toe flare**



## Legging-Spat

**400**

Legging-spat. Two-position side snap closures. Snap-on elastic instep strap. **9" height, 8½" flare**



## Short Side Bar Leggings

**375**

Short side bar leggings. Snap top and vertical metal side bar. Two fiber shin shields inside front of legging. Adjustable instep strap. **9" height, 5½" flare**



## Pant Leg Cuff Guards

**PLCG-1-S**

**PLCG-2-S**

**PLCG-1-V**

**PLCG-2-V**

Elastic construction with your choice of Velcro® or snap button fasteners. Available in widths of 1" or 2".



## Knee Pads

**390-CL**

Heavyweight leather knee pad. Wool felt lined for cushion. Adjustable leather strap. **10" length**



**EC-390-CL**

Economy style foam lined leather knee pad. Elastic snap strap. **Approx. 5" x 5"**



**395-CL**

Wool felt lined leather knee pad with three adjustable straps. **17" length**



**394**

Contoured rubber knee pad. Two adjustable straps.



**KP**

High-impact two-piece plastic outer shell jointed at the knee for full range of motion. Half shock-reducing inner pad and unique grip strip. Quick release straps. Replacement parts available.



Cushioned knee pads (not shown) can be sewn into knee areas on pants.

Safety sleeves are available in all fabrics with your choice of length and closure. Standard sleeve closure is snap at wrist and open top. Please specify any other option desired. (See pages 2 and 3 for complete fabric list.)

**How to Order Sleeves**

Length      Fabric      Wrist Option  
**593 - GR - AA**

**Sleeve Lengths**

<b>589</b>	7"
<b>590</b>	9"
<b>591</b>	12"
<b>592</b>	14"
<b>593</b>	18"
<b>595</b>	23"
<b>1529</b>	(cap sleeve) 29"

**Sleeve Fabric**

<b>AKV</b>	Aluminized Kevlar®
<b>ARH</b>	Aluminized rayon heavy
<b>CL</b>	Chrome leather
<b>BD</b>	Blue denim, non-FR
<b>FRD</b>	Fire resistant duck
<b>GR</b>	Green FR-7A cotton
<b>GW</b>	Green FR-7A twill
<b>HY</b>	Hycar
<b>KTW</b>	Kevlar® twill
<b>KV</b>	22 oz. aramid blend
<b>NMX-9.5</b>	9.5 oz. Nomex® III A
<b>NS</b>	FR navy sateen

**Sleeve Options**

<b>A</b>	2 1/4" blue-gold elastic, one end
<b>B</b>	1/2" white serged elastic, one end
<b>C</b>	Hidden elastic, one end
<b>D</b>	Adjustable snap
<b>E</b>	2 1/2" x 1" Velcro® tab closure, one end
<b>F</b>	Adjustable Velcro® strap, one end
<b>G</b>	Full Velcro® closure running length of sleeve
<b>H</b>	Adjustable arm strap
<b>I</b>	Two-ply black wool knit cuff
<b>J</b>	Two-ply cotton knit cuff
<b>K</b>	Two-ply Kevlar® knit cuff
<b>L</b>	Split snap wrist



	18" LONG	18" LONG	18" LONG	23" LONG	23" LONG	23" LONG
	3/8" White elastic at each end	2 1/4" Blue/gold elastic at each end	Kevlar® knit wrist with thumb hole and 2 1/4" elastic top	3/8" White elastic at each end	2 1/4" Blue/gold elastic at each end	Kevlar® knit wrist with thumb hole and 2 1/4" elastic top
9 oz GREEN FR-7A®	593-GR-BB	593-GR-AA	593-GR-KWTHA	595-GR-BB	595-GR-AA	595-GR-KWTHA
12 oz GREEN FR-7A®	593-GW-BB	593-GW-AA	593-GW-KWTHA	595-GW-BB	595-GW-AA	595-GW-KWTHA
BLUE DENIM	593-BD-BB	593-BD-AA	593-BD-KWTHA	595-BD-BB	595-BD-AA	595-BD-KWTHA
8 oz KEVLAR®	593-KTW-BB	593-KTW-AA	593-KTW-KWTHA	595-KTW-BB	595-KTW-AA	595-KTW-KWTHA
8 oz TUFFWELD®	593-TW-BB	593-TW-AA	593-TW-KWTHA	595-TW-BB	595-TW-AA	595-TW-KWTHA
11 oz CARBONX®	593-CX-BB	593-CX-AA	593-CX-KWTHA	595-CX-BB	595-CX-AA	595-CX-KWTHA

## Nylon Cane Mesh Sleeves


Cut resistant. Two-ply nylon mesh sleeve.  
Quick-release Velcro® fasteners provide adjustability.

**When ordering, specify 692-length-color-size.**

Lengths available: **6", 7", 8", 9", 10", 12", 18"**

Colors available: **Black or white**

Sizes available: **S, M, L, XL, XXL**



## Nylon Cane Mesh Sleeves Sizing Chart

Size	Wrist Circumference	Forearm Circumference in 7" Sleeve Length	Forearm Circumference in 9" Sleeve Length
S	8"	12"	13"
M	9"	13"	14"
L	10"	14"	15"
XL	11"	15"	16"
XXL	12"	16"	17"

## Steel Reinforced Arm Protectors

**Wool-Lined Leather Sleeve.**

**785** With steel-stapled patch (shown)

**786** With plain leather patch

**Steel-stapled leather sleeve (unlined).**

**586** 7"

**587** 9"

**588** 11"

Specify Velcro® or buckle fasteners.



## Tubular Knit Kevlar® Sleeve

Two-ply knit Kevlar® sleeve provides superficial cut and burn protection for the forearms. Washable with minimal shrinkage and virtually no loss of their protective properties.

**When ordering, specify TKK-length-thumb option.**

Lengths available: **10", 14", 18"**

Specify option: **TKK=plain, TKK-T=thumb slot,**

**TKK-A=thumb hole**

Also available in two-ply NON-FR cotton.



## H-9 Arm Protector

Heavy woven cotton (hose material) arm guard.

**Style: H-9 for 9"**

**H-11 for 11"**



## Plastic Arm Guards

High impact, transparent plastic arm guards. No straps, buckles or snaps to get in the way. Sizes small, medium, large and extra large.

**Style A Regular 7 1/2" Turned at wrist only**

**Style B Regular 7 1/2" Turned at both ends**

**Style C Boner 10" Full forearm, turned at both ends.**





# Knitted Hoods



### Nomex® Blend

NFPA 70E current edition approved hood. 2-ply Nomex®/Lenzing FR® blend. Standard long cut style to meet NFPA, or Flared style for greater coverage.

**Style KN-51-NFPA (pictured)**  
**Style FL-KN-51**



### Nomex® Blend

Short style hood in 1-ply or 2-ply Nomex®/Lenzing FR® blend.

**Style KN-52 (pictured, 1-ply)**  
**Style KN-50 (2-ply)**



### CarbonX® Classic

Classic cut meets NFPA 70E requirements. Superior protection. Non-flammable, non-melting. ATPV of 23 cal/cm<sup>2</sup>.

**Style KC-51**



### CarbonX® Ultimate

Ultimate cut meets NFPA 70E requirements. Superior protection. Non-flammable, non-melting. ATPV of 23 cal/cm<sup>2</sup>. Additional chest and shoulder coverage.

**Style KCF-51**



### PBI® Blend

NFPA 70E current edition approved hood. 2-ply PBI®/Lenzing FR® blend. Standard long cut style to meet NFPA (pictured), or Flared style for greater coverage.

**Style PBI-51 (pictured)**  
**Style FL-PBI-51 (flared)**



### Cold Weather

PBI® blend external and Lenzing FR® blend internal. Provides both flame resistance and protection from cold weather.

**Style 2001**



# Hats, Hoods and Spark Deflectors

All spark deflectors are available in any of our fabrics. Most popular are FR cottons (which are pictured), Nomex® and aluminized fabrics.

**ESD-690**



**ESD-690**

Economy strap design spark deflector. Four webbing straps loop over hard cap suspension and snap in place.

**690**



**690**

Deluxe Velcro™ design spark deflector. Four Velcro™ straps attach FR green band to inside of hard cap suspension. The removable deflector attaches to the green band with Velcro™.

**688**



**688**

Spark deflector fits over hard cap and is held in place with an elastic band.

## Spray Sock



**SS-PH**

Painters' Hoods, Spray Socks. 100% cotton, not fire resistant. 16" length. Packed 72 ea. per box.

## Caps



**646**

Baseball style caps. Available in assorted cut and flame resistant fabrics. Also available with Legionnaire-style back flap.

## Tally Hoods



**648-GW-SP**

Open face hood, Velcro® front. Available in a variety of fabrics. Standard design is 1-ply. Pictured (left) is our special 2-ply with button holes. (Style 648-GW-SP)



**648**

Velcro® front

**Aluminized Hoods**



**0647-(Fabric)**

Complete head and shoulder coverage. Large 7" x 11" window opening with replaceable gold film and Lexan® window.



**220-(Fabric)**

7" x 11" lift front window and shoulder slits.



**647-(Fabric)**

4½" x 5¼" window. Comes standard with Pyrex® glass and a polycarbonate inner plate.

**Hood Information**

Hoods on this page are constructed around a hard shell which provides both structure and a head ratchet. Windows are replaceable and positioned far enough away from the face to allow room to wear safety glasses or a face mask underneath. Air fed supplies can be fitted into the hoods. Hard hat or cap clips can be installed, please specify.

**Wide View Aluminized Hood**

**WV-647**

Provides maximum peripheral vision. Hood is designed to be worn over a hard cap. Excellent for radiant heat. Not recommended for areas exposed to heavy molten splash. 40% greater peripheral view than standard 7" x 11" hoods.



**Welding Helmet**

**647-A**

Thermal welding helmet with 4½" x 5¼" window.



**Sandblast Hood**

**647-GFRD**

Canvas duck material fabricated over a welding helmet with ratchet headgear. Lexan® window with 50 mesh screen front. Protects head and shoulders from rebounding particles and abrasives.

Approved respirator must be used in conjunction with the Sandblast Hood.



**Short Cape Leather Welding Helmet**

**222-CL**

2" x 4¼" nylon lift front. Retainer and drop down ratchet headgear. Complete with shade #10 green glass window and protector plates.



# Liberty Heat Resistant Gloves

Unique heat resistant gloves for use in Foundries, Heat Treating Departments, Molding, Casting, Steel Mills, Welding and Assembly lines etc. Durable, Pliable, Comfortable and Economical protection up to 500°F.

All gloves are full fourchette construction. The excess fourchette leather stretches out like an accordion as heat exposed finger and palm leather shrinks. This design maintains pliability and comfort.



2-PLY

## Style 111-GL & 113-GL

2-Ply construction combines special tan leather and a full wool liner to provide momentary 500°F protection. These lightest weight designs offer the most dexterity in the Liberty series of gloves.

11 Inch 2 ply glove Style # 111-GL

13 Inch 2 ply glove Style # 113-GL



3-PLY

## Style 211-GL & 213-GL

3-Ply construction provides 500°F protection for extended periods. Our 3-ply gloves are made with a layer of self extinguishing heat resistant fabric between the leather shell and the wool lining.

11 Inch 3 ply glove Style # 211-GL

13 Inch 3 ply glove Style # 213-GL




4-PLY

## Style 213-DW

4-Ply construction provides similar heat protection for extended time. This is one of our most popular gloves to protect against heat associated with casting operations. The unique design of our pattern allows good dexterity even in a 4 layer system.

13 inch 4 ply glove Style # 213-DW





# High Heat Gloves

## GLOVE OPTIONS

	SINGLE LAYER	LEATHER REINFORCED PALM	KEVLAR® REINFORCED PALM
11" GLOVE	231-(fabric choice)	FA-231-(fabric choice)	FB-231-(fabric choice)
14" GLOVE	234-(fabric choice)	FA-234-(fabric choice)	FB-234-(fabric choice)
18" GLOVE	238-(fabric choice)	FA-238-(fabric choice)	FB-238-(fabric choice)
23" GLOVE	243-(fabric choice)	FA-243-(fabric choice)	FB-243-(fabric choice)

## MITTEN OPTIONS

	SINGLE LAYER	QUILTED PALMS	DOUBLE LAYER PALMS
11" MITT	171-(fabric choice)	Q171-(fabric choice)	184-11-(fabric choice)
14" MITT	174-(fabric choice)	Q174-(fabric choice)	184-14-(fabric choice)
18" MITT	178-(fabric choice)	Q178-(fabric choice)	184-18-(fabric choice)
23" MITT	183-(fabric choice)	Q183-(fabric choice)	184-23-(fabric choice)

All gloves and mittens are available in 11", 14", 18", and 23".



### 22 oz. Heat Blend

22 oz. Para-Aramid and fiberglass blend. 400-600°F working temperature. Abilities to resist higher temperature intermittently. Good abrasion resistance. Fully wool lined.

Part #

- 234-KV** 14" Glove **MOST POPULAR**
- FA-234-KV** 14" Glove with Leather Reinforcement
- 174-KV** 14" Mitten
- 184-KV** 14" Mitten with Double Palm

### 22 oz. PBI® Blend

22 oz. Polybenzamidazole blend offers higher working temperatures, near fiberglass levels, with superior abrasion resistance. Fully wool lined.

Part #

- 234-PBI22** 14" Glove
- FA-234-PBI22** 14" Glove with Leather Reinforcement
- 174-PBI22** 14" Mitten
- 184-PBI22** 14" Mitten with Double Palm

Also available in 45 oz. Please call for pricing.



**234-AKV-ZP** Combo glove. 19 oz. aluminized Kevlar®-aramid fiber blend on back for up to 2000°F radiant protection. 35 oz. Zetex Plus® palm for short duration up to 1800°F. Moderate to poor abrasion resistance.



**234-AZ-Z** Combo glove. 35 oz. Zetex® glass on palm for short durations up to 1000°F. 25 oz. aluminized Zetex® for up to 2000°F radiant protection on back side. Moderate to poor abrasion resistance.



**234-AKV-KV** Combo glove. 19 oz. aluminized Kevlar®-aramid blend on back for near 2000°F radiant protection. 22 oz. Kevlar®-aramid blend palm for working temperature of 400°F-600°F and good abrasion resistance.



# Gloves and Mittens

**234-Z** 35 oz. Zetex® fiberglass. Short durations up to 1000°F. Moderate to poor abrasion resistance.



**234-ZP** 35 oz. Zetex Plus® treated fiberglass. Short duration up to 1800°F. Moderate abrasion resistance.  
**FD-234-ZP** Double layered palm gloves are recommended when working with higher heats.



**234-V** 36 oz. Vertex™ vermiculite coated fiberglass. Short durations up to 2000°F. Moderate abrasion resistance. (Shown with steel mesh reinforcement for better abrasion resistance. 234-V-SSM.)



**234-GL** 26 oz. white generic glass fabric. Short durations up to 1000°F. Poor abrasion resistance.



**234-KTW** 8 oz. Kevlar® twill. Working temperature of approx 500-600°F. Superior abrasion resistance. Good dexterity.



**234-KT** 22 oz. Kevlar® terry. Working temperature of approx. 600°F. Superior abrasion resistance.



**234-PBI™** Polybenzamidazole blend available in 22 oz. or 45 oz. Higher working temperatures near fiberglass levels with superior abrasion resistance. 45 oz. PBI offers a thick barrier for longer heat duration but less dexterity.



**234-MT** Terry cotton "mock twist" glove for lower temperatures. Can be used as a baker's glove.



**234-THL** Brown thermal leather withstands premature hardening up to 500°F. Good abrasion resistance. Wool lined.



**234-AKV** 19 oz. aluminized Kevlar®-aramid fiber blend. Up to 2000°F radiant heat. Some sparks and molten splash. Good abrasion resistance.



**234-AZ** 25 oz. aluminized Zetex®. Up to 2000°F radiant heat. Some spark and splash. Moderate abrasion resistance.



**234-ARH** 19 oz. aluminized rayon. Up to 2000°F radiant heat. Some sparks and molten splash. Moderate abrasion resistance.



## Cover Mitts

Economical slip-on glove and mitten savers. Reversible unlined cover mitts.

**105-CTJ** 9" closed top jumbo cover mitt. For over mittens.



**105-OTJ** 8" open top jumbo cover mitt. For over gloves.



**WM-105-CTJ-10-V** Wire mesh covered closed top Vertex™ cover mitt for over mittens. For high heat and abrasion resistance.





# Domestic Welding Gloves

**901-Alum** Gunn cut, aluminized leather back. Wing thumb with welting. Aluminized back radiates away a percentage of heat to keep hand cooler. 14" length.



### Wool Lined Welder's Glove

Welted, wool lined, Kevlar® sewn.

Part 901-CL

**125-WS** Gunn cut, side split cowhide. Wing thumb with welting. Cotton lined. Size large. Specify length: 14", 18" or 23".



### Glove Protector

### SN-901-ALUM & SN-88 PAD

Designed for hand protection under severe heat of heavy MIG welding arc gouging, multiple passes or preheated weldments. Replaceable snap-off back pad for extended wear. SN-88 Kevlar® blend pad radiates up to 2000°F radiant heat.



**WSOF-Alum** One finger mitt version of our 901-ALUM. Mitten style with freed trigger finger. 14" length.



**88-Alum** Two-ply glove protector economizes by extending the wear of your gloves, while adding protection from radiant heat and splatter.



### Spark Cuff

A practical, comfortable way to keep sparks out of glove or mitten cuffs. We can attach cuff to our gloves or yours. Specify fabric. Specify glove.



### Welding Beanies

**640** Welding beanies for head protection from sparks. Available in leather or flame retardant cottons. Specify material and size.



### Rod Holder

**RH-CL** Reinforced bottom with leather loop and snap hook (rust leather).



# Imported Welding Gloves



## Gray Deer Skin

Insulated deer split back, unlined reverse grain leather palm. Superior dexterity and comfort. Reinforced palm. Kevlar® stitched.

**Part # SA3-D**



## Side Split Cowhide

Heat-resistant cow split leather. Gunn pattern, wing thumb, one-piece back. Welting in vulnerable seams. Kevlar® stitched. **\*\*Most Popular\*\***

**Part # SA3-1000**



## Side Split Cowhide

Reinforced thumb and palm area. Fully sock lined. Kevlar® stitched.

**Part # SA3-B**



## Side Split Cowhide

Thumb Strap. Fully sock lined. Kevlar® stitched.

**Part # SA2-R**



## Shoulder Split Cowhide

Fully sock lined. Fully welted seams.

**Part # SA1-GY**



## Aluminized Back & Thumb

Reflects radiant heat. Fully sock lined. Reinforced palm. Kevlar® stitched.

**Part # SA2-ALUM**



## 18" Long

Cowhide split. Fully sock lined. Protects forearm to elbow. Velcro® strap at cuff. Reinforced palm. Kevlar® stitched.

**Part # SA2-18**



## Jumbo Welder's

Cowhide split. Fully sock lined. Wing thumb. Fully welted. Kevlar® stitched.

**Part # SA2-JMB**



## Kid Grain

Style	Size	Part #
Short 2" cuff	S-XL	TIG-KG-2
Long 4" cuff	S-XL	TIG-KG-4



# Glass Handler's Kevlar® Clothing

## Wrist Guard

### 36-KTW-9

Double layer of 8 oz. Kevlar® twill protects wrist from cuts and lacerations. Thumb hole keeps wrist protector in place. Velcro® closure.



- 36-KTW-9 9" sleeve
- 36-KTW-11 11" sleeve
- 36-KTW-18 18" sleeve

## Cape Sleeve 577-KM-KTW

Glacier Wear™ cape sleeve helps keep you cool while providing the cut resistance of 100% Kevlar®.



577-KM-KTW

## 646-KTW



## Glacier Wear™

Glacier Wear™ safety clothing provides a unique combination of cut resistance and comfort. So unique, it's patented. Strategically positioned Kevlar® mesh fabric provides a cool venting effect and cut resistance. No metal on the product eliminates scratching. Custom designed to your specification or use our popular standard designs. Glacier Wear™ is available as a jacket, cape sleeve, surgical style coat, bib apron, or sleeve. Glacier Wear™ is an economical alternative to eyelet-studded products.

## Split Leg Apron and Ball Cap

### 550-KTW-40-SP

100% Kevlar® twill split leg apron with replaceable belly patch. Adjustable Velcro® leg and webbing neck and waist straps provides a "one size fits most" apron. Available in 40", 48", 52" and 56" lengths.

### 646-KTW

100% Kevlar® twill baseball cap available with or without back "legionnaire style" flap.

## Eyelet Ventilated Cap Sleeve

- EV-1529-KTW 1-ply Kevlar® twill
- EV-1529-WJC 2-ply white jean cloth NOT-FR
- EV-1529-GR 2-ply green sateen cotton  
Lengths available: 21", 23", 25", 27", 29", 31", 33" and 35".



# Steel Reinforced Gloves/Mitts



**Style 4" Gauntlet**  
Part # 1644 (shown)

Style 2" Band  
Part # 1604



**Style 4" Gauntlet**  
w/ Heavy Nylon Strips

Part # 1644-NY



Exceptionally strong because it is reinforced with steel ribbons over strips of tough leather, with thumb patch, closed with steel thread.

Part # 1681



**Hand Pads** Cool protection with the fit of a mitten, split leather construction. For bare hand or over thin gloves.

Part # 715 Open back, plain, no patch

Part # 717 Open back, plain patch

Part # 716 Open back, steel-stapled patch

# Anti-Vibration & Fingerless Gloves



## Cable Former's

Grain leather half gloves with adjustable wrist strap. Thumb free style. Available with or without split leather palm reinforcement.

Sizes S-XL Part #

21 Plain Palm  
23 Reinforced Palm



## Anti-vibration pad

Anti-vibration – reversible – curved palm and heel pad with elastic back straps. Available in grain, pig, or split leather.


One Size	Part #
SX-02	Split Leather
GX-02	Grain Leather (shown)
PX-02	Pig Leather



## Fingerless Anti-vibration

Durable pig leather shell with anti-vibration palm. Tailored patterns provide unique comfort.

Size	Part #
S-XL	24SPA





# Hand Protection

## Fingerless Gloves & Cable Former's Gloves

Grain leather half-gloves with adjustable wrist strap.


- 21 No thumb
- 22 With thumb
- 23 Split leather patch on palm, no thumb
- 24 Split leather patch on palm and thumb with thumb



## Open-Back Hand Pads, Thumb Type

Cool protection with the fit of a mitten, split leather construction. For bare hand or over thin gloves.

- 715 Plain
- 716 Steel stapled patch
- 717 Plain patch
- 27 Double leather, steel reinforcement on palm and thumb. Wool lined. Adjustable strap.



## Oval Hand Pads with Slit

For handling hot, rough and abrasive materials. Available in 3 sizes, with or without steel staple reinforcement, and single-layer or multi-layered.



	Plain 1-ply	Steel Stapled 1-ply	Plain 2-ply	Steel Stapled 2-ply
7½" x 10¾"	711	S-711	2P-711	2P-SS-711
7" x 9"	707	S-707	2P-707	2P-SS-707
6" x 8½"	700	S-700	2P-700	2P-SS-700

## Square Hand Pads

One layer of wool quilted between two layers of fabric, i.e. Fabric-Wool-Fabric.

Specify fabric: Kevlar®, Zetex Plus®, Zetex®, Blackflex, leather or other.

Available in 4 sizes.

- 709-6 6" x 6"    709-10 10" x 10"
- 709-8 8" x 8"    709-12 12" x 12"



## Reversible Hand Pad

Split leather hand pad 6" long. Reversible style gives double life.

- 44 Plain (shown)
- SR44 Steel staple reinforced
- P44 Plain patch reinforced



## Baker's Pad—Terry

8" x 12", two-ply 24 oz. terry serged (loop out) sewn around outer edges.

- BP-1 With slit
- BP-2 With 2 elastic straps (shown)



# Hand Protection

## Thumb Type Hand Pad

**097** Grain leather pad with split leather palm and thumb patch. Elastic back strap. Steel sewn.



## Reinforced Hand Pad

Split leather hand pad with palm patch. Steel sewn thumb type. Elastic back strap.

**83** (shown)  
**J-83** Jumbo, fits over gloves



## Palm Guard

Split leather palm guard. No thumb or fingers. Steel sewn. Elastic back strap.

**82** (shown)  
**J-82** Jumbo, fits over gloves  
**JS-82** Jumbo, steel reinforced



## Anti-Vibration

Anti-vib-Viscolas® or Sorbothane® hand and wrist protection. See price list for complete list of products.

**SX-01** Reversible oval shock pad with elastic; for palm area  
**25** Bundler's style anti-vib guard  
**GX-04** Grain leather fingerless glove style anti-vib



\*Sorbothane® is a plastic polymer based on propylene oxide and possesses some unique properties: It distorts readily and has retarded recovery, absorbs up to 95% of impact energy with virtually no recoil and behaves like a fluid, being capable of accepting and absorbing multi-axial and torsional stress.

## Bundler's Hand Guards

Quilted leather patch over palm. Ideal protection where the free use of fingers is required. Protects against cuts and burns from handling bundles, crates, paper, and twine. Adjustable Velcro® closure standard; snap buttons available.

**BHG** Regular (shown)  
**SR-BHG** Steel staple reinforced  
**NP-BHG** No patch



**MOST POPULAR**

## Machine-Knitted Gloves

Insulating materials give protection against heat or cold. Knit wrist, reversible style. Can be worn under other gloves. Excellent dexterity. (Shown left to right)


**W-100** Wool glove liner  
**K-100** Kevlar® for added abrasion resistance  
**C-100** Cotton, general purpose  
**K-100-PD** Kevlar® with plastic dots for added grip



## Glove Protector

Split leather glove saver. Use over cotton, hot mill, or leather work gloves. Extra protection for index finger, palm, and thumb. Elastic back.

**84-1** One finger (shown)  
**84-2** Two finger—index and second





# Mechflex™ Mechanic's Gloves



## IMPACT-X

- Durable synthetic leather palm & fingers
- Shock-absorbing gel padded palm
- Neoprene knuckle protector
- Anti-slip palm and fingertip patches
- **Style # MX-52-(size)**, available S-2XL



## SYNTHETIC

- Durable synthetic leather palm & fingers
- Anti-slip palm patches
- Reinforced thumb area
- Ventilated finger walls
- **Style # MX-50-(size)**, available S-2XL



## GOATSKIN

- Durable goat grain leather palm and fingers
- Anti-slip palm and fingertip patches
- Leather reinforcement on thumb crotch
- **Style # MX-56-(size)**, available S-2XL



## GOATSKIN

- Supple goat leather palm and fingers
- Anti-slip palm patch
- Leather reinforcement on thumb crotch
- **Style # MX-55-(size)**, available S-2XL



## SLIP-ON

- Supple goat grain leather palm
- Easy slip-on style
- Leather reinforcement on thumb crotch
- **Style # MX-57-(size)**, available S-2XL



## HI-VIS

- Hi-Vis back
- Goat skin palm and fingers
- **Style # MX-80-(size)**, available S-2XL



## HI-VIS

- Hi-Vis back
- Goat skin palm and fingers
- **Style # MX-80G-(size)**, available S-2XL



## WINTER

- Pig skin palm and fingers
- Water and wind resistant
- Reinforcement on thumb crotch
- **Style # MX-90-(size)**, available S-2XL

# Cold Climate/Freezer Work Driver's Gloves



## DEER PALM, FLEECE BACK

Full sock insulated. Elasticized wrist.  
Style: Deer Split Palm Fleece Back  
Part # CC4-DS-FB



## SUPPLE PIG GRAIN

Full sock insulated. Elasticized wrist.  
Style: Pig Grain Drivers  
Part # CC4-PGD



## PIG GRAIN PALM

Full sock insulated. Knit wrist.  
Style: Pig Leather Palm  
Part # CC4-PLP



## HIGH VISIBILITY

Brushed pig skin palm, reflective knuckle strap, full sock insulated, high-vis safety cuff and knit wrist.  
Style: High Visibility Brushed Pig Skin  
Part # CC4-HV-BP



## DEER SPLIT LEATHER

Full sock insulated. Heavy foam lined. Knit wrist.  
Style: Deer Split Freezer Glove  
Part # FG4-DS  
Available with Latex Palm  
Part # FG4-DLTX



## REVERSE GOAT GRAIN

Full sock insulated. Heavy foam lined. Knit wrist. Double insulated back.  
Style: Reverse Goat Freezer Mitt  
Part # FG5-RG



## DOUBLE PALM

Style: Double Palm  
Part # WK-DP



## BUCK SKIN DRIVER'S

Keystone thumb, unlined, elastic back.  
Style: Buck Skin S-XL  
Part # DG-BS



## COW GRAIN DRIVER'S

Durable soft-top grain. Keystone thumb, unlined, shirred elastic back.  
Style: Cow Grain S-XL  
Part # DG-CG



# Snakebite Protection/Finger Guards

Heavy shoes are recommended for foot and ankle protection.



### Snakeproof Chaps



**13045—Inseam**  
Cordura® nylon available in regular (25" thigh) or husky (28" thigh) and 27"- 30", 30"- 33", 33"- 36" inseams.

### Plastic Snake Leggings



**130464**  
19" front, 15" back.  
Hard plastic. Molded in shape.  
Olive color.

### Canvas Snake Leggings



**130460**  
17" front, 12" back.  
With webbing and buckles.

## Finger Guards

### A G-7018-CE

Grain leather, closed end, wrap around

### B S-7018-CE

Split leather, closed end, wrap around

### C G-7002-OE

Grain leather, open end

### D SF-7000-657-OE

Split leather, open end

### E G-7012-CE

Grain leather, closed end, flat

### F S-7012-CE

Split leather, closed end



A B C



D E F

### Steel-Studded Guards

From left to right, below

### H-7005-OE

Grain leather, horizontal steel studding

### V-7007-OE

Grain leather, vertical steel studding

### D-7022-OE

Grain leather, diagonal steel studding



**SF-7000-657-OE**  
Split leather, open end

### Thumb Guards

(Not pictured)

### ST-7000-OE

Split leather, open end

### S-7019-CE

Split leather, closed end, wrap around

### GT-7000-OE

Grain leather, open end

### G-7019-CE

Grain leather, closed end, wrap around

Finger guards are available in a variety of fabrics and styles. For example Kevlar®, wool, rubber and cotton. Please call our customer service department with any questions you may have.



# Chainsaw Protection

## Chainsaw Chap

Multi-layered Kevlar® with Cordura® nylon outer shell. Two-inch wide heavy nylon belt with adjustable quick release Nexus® clip. Five-compartment tool pocket with snap flap closure. Designed to clog and block the cutting chain. Added protection is provided if the Kevlar® material is pulled into the drive sprocket, jamming it. Chap is not a substitute for safe operating procedures. It is the buyer's responsibility to determine if this product will be adequate protection.

Measure length from waist down.



Also available in Orange

2600-28"  
2600-32"

2600-36"  
2600-40"

## Chainsaw Gloves

### CSG-3

Grain pig leather palm. Back is 1-ply Kevlar® jersey and 3-ply ballistic Kevlar®.

Available in sizes XS-XL.



## Metatarsal Guard



### LW-800

Wear with steel toe safety shoes to extend impact protection to instep. Aluminum alloy with rubber padding.

## Foot Guard



### LW-200

Protect entire front of foot from impact hazards. Aluminum alloy, rubber strap, rubber toe clip.

## Steel Toe Guards



### LW-702

Steel guard for maximum toe protection. Quick fastener, adjustable web strap.

## Shin Guard



### LW-303

Aluminum alloy, padded top and bottom, fastened with web straps.

## Shin-Instep Guard



### LW-323

Aluminum alloy, padded with sponge rubber. Fastened with web straps.

## Knee-Shin-Instep Guard



### LW-334

Plastic, padded with sponge rubber. Fastened with web straps.

## Plastic Toe Guard



### LW-505

Lightweight toe protection. Does not replace steel toe shoe protection.



## PVC

13 oz. polyester with green PVC coating. See chemical guideline chart below.

**CHEM-0647**  
Hood  
(shown)

**CHEM-618**  
Bib Overall  
(shown)

**CHEM-SHROUD**  
Shroud  
(shown below)

**CHEM-548**  
Apron 35" x 45"  
(not shown)

**CHEM-600**  
Jacket 30"  
(shown)



## Hycar®

Hycar® (not FR), nitrile medium weight. Very durable, provides good resistance to many acids, solvents and oils. Available in black (shown), yellow, and white.

**545-HY-(Color)** 45" Apron

**548-HY-(Color)** 48" Apron (shown)

**593-HY-AB** 18" Sleeve (shown)



## Neoprene

Neoprene coated nylon provides good resistance to many acids, hydrocarbons and oils. Available in yellow only.

**545-NEO** 45" Apron

**548-NEO** 48" Apron (shown)

**593-NEO-AA** 18" Sleeve (shown)

**564-NEO-50"** Surgical style gown

Call our customer service department for information on our full line of Hycar® and Neoprene Protection

### Penetration Summary – Green PVC Material

Chemical	Average Sample Thickness (mm)	Test Temperature (Celsius)	Indicator	Result
Hydrochloric Acid	0.382	22.8	pH paper	Pass
	0.392	22.9		Pass
	0.394	23.2		Pass
Sulfuric Acid	0.383	23.2	pH paper	Pass
	0.378	23.2		Pass
	0.383	23		Pass

# Non FR Work Apparel/Storage Bags

## Coveralls

### WK-605-PC (shown)

65% polyester/35% cotton. Pre-shrunk permanent press. Bi-swing back. Concealed 2-way brass zipper front. Seven pocket style with side openings for access to inner clothing. (7<sup>3</sup>/<sub>4</sub> oz.)

Specify color: white, charcoal, navy blue, spruce green, chocolate brown, postman blue.

### WK-605-C

100% cotton. Pre-shrunk. Plain back concealed brass button front. Seven-pocket style with side openings for access to inner clothing. (8<sup>1</sup>/<sub>2</sub> oz.)

Specify color: charcoal, chocolate brown, white, natural, navy blue, spruce green, suntan, postman blue, Fisher herringbone stripe (10 oz.).

WK605-PC

1700

1600



## Office, Lab and Shop Coat

1600 (30")

Office Coat (shown)

1700 (40")

Lab Coat (shown)

5<sup>1</sup>/<sub>2</sub> oz. poly-cotton. Three-pocket style. Matching pearl buttons. Specify color: white, light blue, navy blue.

### PC-1800 (42") Shop Coat,

7<sup>3</sup>/<sub>4</sub> oz. poly-cotton

Specify color: white, navy blue, postman blue, and white with navy blue trim.

### C-1800 (42") Shop Coat,

8<sup>1</sup>/<sub>2</sub> oz. 100% cotton

Four-pocket style. Concealed brass button front. Specify color: white, navy blue, postman blue, white with navy blue trim, suntan, spruce green, and 10 oz. Fisher Herringbone.



## Duffel Bags

907	General Use	18"W x 9 <sup>1</sup> / <sub>2</sub> "H x 9 <sup>1</sup> / <sub>2</sub> "D
909-J	Jumbo Style	24"W x 13 <sup>1</sup> / <sub>2</sub> "H x 13 <sup>1</sup> / <sub>2</sub> "D
909	Fire Fighter's Bag	23"W x 11"H x 13 <sup>1</sup> / <sub>2</sub> "D

Available with or without shoulder straps.

All bags are available in your choice of Cordura® nylon, nylon on vinyl or vinyl-coated polyester. See Price List for colors.



## Storage and Respirator Bags

900	Half Face Respirator	6 <sup>3</sup> / <sub>4</sub> "W x 8"H x 4 <sup>1</sup> / <sub>2</sub> "D
901	Full Face Respirator	9"W x 12"H x 6"D
902	Goggle Cover	6 <sup>3</sup> / <sub>4</sub> "W x 4 <sup>1</sup> / <sub>2</sub> "H x 3 <sup>1</sup> / <sub>2</sub> "D

Respirator bags come standard with belt loops. Shoulder strap or waist belt available.





# Welding Screens

## One-Panel Screens (with legs)

Available sizes (width x height):

- 5' x 4'
- 6' x 4'
- 6' x 5'
- 6' x 6' (most popular, shown)
- 8' x 5'
- 8' x 6'
- 8' x 8'



## Two-Panel Screens (platform legs optional)

Available sizes (width x width x height):

- 4' x 4' x 4'
- 5' x 5' x 5'
- 6' x 6' x 6' (shown)
- 8' x 8' x 6'
- 8' x 8' x 8'



## Three-Panel Screens (platform legs optional)

Available sizes (width x width x width x height):

- 2' x 4' x 2' x 4'
- 4' x 4' x 4' x 4'
- 3' x 4' x 3' x 5'
- 3' x 6' x 3' x 5'
- 5' x 5' x 5' x 5'
- 4' x 4' x 4' x 6'
- 6' x 6' x 6' x 6' (shown)
- 8' x 8' x 8' x 8'



## Four-Panel Screens (with legs)

Available sizes (width x width x width x width x height):

- 6' x 6' x 6' x 6' (shown)
- 6' x 8' x 6' x 8' x 6'
- 8' x 8' x 8' x 8' x 6'
- 8' x 8' x 8' x 8' x 8'



## Weld Strip Doors Replacement Strips and Bulk Rolls

When ordering, please specify material color number.

- Amber (31)
- Aztec Red (32)
- Charcoal (33)

### BULK ROLLS

Size	Stock #	Length
8" x .080"	C8	300
12" x .120"	C12	200

### CUT STRIPS (full foot increments — pkg. of 5)

Size	Stock #
8" x .080"	C8-1
12" x .120"	C12-1

Improve the levels of safety and productivity at your facility. Choose a system that will protect you from welding and grinding hazards.

All fabrics available as screen inserts. Most popular fabrics are:

12 oz. olive drab, 13 mil. Weldview in assorted colors, fiberglass (plain or coated), and aluminized fabrics.

Screens are attached to frames with nylon beaded ties. Platform legs available for all screens. Casters available, two casters per platform leg.

## Ready Roll Curtains 14 mil. TRANSPARENT (RR-14)

When ordering please specify material color number.

- Yellow (02)
- Orange (03)
- Grey (04)
- Blue (05)
- Green (06)



Rolls are 25 yards long with grommets on 12" centers. Maximum height 64". Easy attachment to any hook system, cut as needed with any utility knife.

## Welding Strip Curtains

For high traffic areas, these PVC Strip Curtains use universal pre-studded, zinc-plated hardware that can economically solve your OSHA and regulatory problems.

When ordering, please specify material color number:

- Amber (31)
- Aztec Red (32)
- Charcoal (33)



### 8" x .080" 50% OVERLAP

Door Size
4' x 7'
4' x 8'
5' x 7'
6' x 7'
6' x 8'

### 12" x .120" 67% OVERLAP

Door Size
8' x 8'
8' x 10'
10' x 10'
10' x 12'
12' x 12'

# Welding Blankets

Curtains	Material	Weight	Description	Roll Width
	<b>Olive Drab Duck</b>	<b>OD-12 oz.</b> <b>OD-10 oz.</b> <b>OD-14.9 oz.</b>	General use flame, water and mildew resistant. Treated cotton duck. Most economical. 12 oz. is standard. 10 oz and 14.9 oz. are available.	36" 48" 60" 72"
	<b>Weldview</b>	<b>WV - 13-14 mil.</b> Yellow, orange, grey, green and blue	Translucent vinyl, filters most U.V. Reduces visible flash and allows light in work areas. CFM approved.	62"
Blankets	Material	Weight	Description	Roll Width
	<b>Heat Cleaned Glass</b>	<b>HCG-18 oz.</b>	Most economical, lightweight, fiberglass. Melting temperature of 1000°F. Good for light welding protection.	40" 60" 72"
	<b>Generic Glass Cloth – Heavy</b>	<b>GGCH - 35 oz.</b>	Heavier weight fiberglass. Melting temperature of 1000°F. Good for stress relief and moderate molten splash or sparks.	40" 48" 60" 72"
	<b>Blackflex</b>	<b>BF - 23 oz.</b>	Durable material with proprietary coating on two sides. Fiberglass base. 400°F working temperature, 1000°F melting temperature. Good for sparks and slag. Will take higher heats when used on a vertical plane.	40" 60" 72"
	<b>Goldenglass</b>	<b>GLG - 24 oz.</b>	Durable material with proprietary coating on one side. 400°F working temperature, 1000°F melting temperature. Good for sparks and slag.	40" 60" 72"
	<b>Silica Cloth</b>	<b>SC-18 - 18 oz.</b> <b>SC-36 - 36 oz.</b>	Protects from sparks, splatter, and molten metal. Up to 1800°F working temperature. Melting temperature near 3000°F. Good for stress relief. Not recommended for areas with high abrasion.	36"
	<b>Silicone-Coated Fiberglass</b>	<b>SCF - 30 oz.</b>	General purpose, sheds oils, sparks and splatter. Working temperature up to 500°F. Melting temperature of 1000°F. Good abrasion resistance.	60"
	<b>Leather Welding Blanket</b>	<b>CL - 3½ oz. per sq. ft.</b>	Abrasion resistant and durable with good flexibility. Protects from moderate sparks and splatter.	—
	<b>Aluminized Kevlar® Blend</b>	<b>AKV - 19 oz.</b>	Reflects up to 2000°F radiant heat. When used in work area, can minimize heat transmission and provide a more comfortable work environment. Will protect from sparks and splatter when used on a vertical plane.	40"

**Vests**

See Price List for complete vest information.

**Hi-Vis**

- Hi-Vis back
- Goat skin palm and fingers
- Style # MX-80-(size), available S-2XL



**Indura Vest**

**ESV-VEST**

Economy style with no reflective stripes.  
Size large.



**Nomex Vest**

**STD-VEST-SIZE**

2" vertical striping on front, 2" horizontal striping on back. Velcro™ front, elastic side closure.



**Fire Canister**

**20H**

Fire blanket storage canister. 20 gauge red metal mounts on wall with two screws. Specify if blanket is required.



**Wall Bag**

**E-30-H**

High-visibility fire blanket wall bag. Grommets at top allow bag to be mounted to wall. Specify if blanket is required.



**Hi-Vis Covers**

Bright fluorescent color pinpoints locations of fire extinguishers and hoses. See price list for sizes and styles.



**Hi-Vis Lights**

Patented light strip offers best visual protection. Capable of blinking or steady light. Velcros onto clothing. Magnetic strip allows attachment to vehicle. (Battery included.)



**Fire Blankets**

**Wool (62" x 84")**

First aid, FR wool blanket fits inside both wall bag and canister.

**NPN (60" x 80")**

Needle punch Nomex® blanket fits inside both wall bag and canister.




**Arm Band**



Illuminating bands reflect lights of oncoming vehicles after dark. Wear on ankle or arm. Velcro™ closure.

**UPS Ground**  
**Guaranteed Day-Definite Delivery**  
 For commercial shipments originating in 60076



Jackets, Coats & Coveralls (Chest Sizes)

S	M	L	XL	XXL	XXXL	XXXXL	XXXXXL
36-38	40-42	44-46	48-50	52-54	56-58	60-62	64-66

Pants (Waist Sizes)


S	M	L	XL	XXL	XXXL	XXXXL	XXXXXL
28-30	32-34	36-38	40-42	44-46	48-50	52-54	56-58

Guide to measuring for proper fit of garments

- W (Waist) .....Keep tape snug, not too tight.
- SL (Sleeve length) .....Base of neck to wrist with arm extended outward.
- C (Chest) .....Measure broadest part with tape up under arms.
- IS (Inseam) .....Crotch to top of shoe (not boot) inside of leg.
- OS (Outseam) .....Waist to top of shoe (not boot), outside of leg.
- CL (Coat length).....Base of collar at back of neck to desired length.


**Request our other catalogs to help complete your safety product lines.**

**Arc Flash Protection**



- NFPA 70E/ASTM F1506
- Arc Flash Kits
- Insulated Gloves
- Face Shields
- Work Wear
- +Much More!

**The Power of CarbonX®**




- Undergarments
- Work Wear
- Sleeves
- Hoods
- Blankets
- +Much More!

**MechFlex™**



- Mechanics' Gloves
- Ultimate Comfort
- Ultimate Dexterity
- Professional Performance
- Custom Designs
- +Much More!

**Ronco**



- Storage Bags
- Respirator Bags
- Duffel Bags
- Gear Bags
- Fanny Packs
- Utility Belt Pouch
- Pocket Pouch
- Haz-Mat Bags
- +Much More!

**LIABILITY STATEMENT AND DISCLAIMER OF WARRANTIES**

Seller's and manufacturer's only obligation shall be to replace such quantity of the product proven to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith. Therefore, the buyer should make a careful analysis of the use for which these products are purchased. It will be the buyer's responsibility to determine whether these products will adequately protect the wearer in the environment in which they are to be used.

We cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. Users are advised to make their own test to determine the safety and suitability of each such product or product combination for their own safety purposes. Swatches are available for testing purposes. Temperatures, where stated, are merely guidelines, as each application varies in duration of exposure.

Statements or recommendations not contained herein shall have no force or effect unless in an agreement signed by officers of seller and manufacturer.

Glacier Wear™, Mechflex™ and Fireguard® are trade marks of Chicago Protective Apparel Inc., Crosstech® and Crosstech® Direct Grip® are registered trademarks of W.L. Gore & Associates. Kevlar®, Cordura®, and Nomex® are registered trademarks of E.I. Dupont DeNemours & Co. Zetex® and Zetex Plus® are registered trademarks of Newtex Industries. PBI® is a registered trademark of Hoechst Celanese Corporation. Velcro® is a registered trademark of Velcro USA Companies. Fiberglass is a registered trademark of Owens Corning Corporation. Indura®, Indura® Ultra Soft®, Modaquilt® Vinex® and FR-7A® are registered trademarks of Westex Inc. Proban® is a registered trademark of Albright & Wilson Ltd. Lexan® is a registered trademark of General Electric Company. Vertex® is a registered trademark of AmateX. Hot Not® is a registered trademark of ESP Inc. Zirpro™ is a trademark of Mt. Jefferson Woolen Division of Delong Sportswear Inc. CarbonX® is a registered trademark of Chapman Innovations.



## Chicago Protective Apparel, Inc.

3425 Cleveland Street

Skokie, Illinois 60076

Phone 847-674-7900

Local Fax 847-674-7906

Long Distance Fax 800-845-6833

sales@chicagoprotective.com

find us on | [facebook](#)

follow us | [twitter](#)



[www.chicagoprotective.com](http://www.chicagoprotective.com)