

17002A

6" IC Airtight Housing

Product Description

Suitable for new construction in residential and commercial applications. IC rated, suitable for direct contact with insulation. Compact fluorescents also approved for use with 17002A trims.

Housing

Airtight housing limits the exchange of air between ceiling plenum and heated/cooled areas. Washington State Energy Code approved to meet restricted airflow requirements. Transformer includes integral thermal protector, guards against improper lamping and misuse of insulation materials. Adjustable socket bracket assures proper and consistent lamp positioning. 7 1/2" height allows use in 2" x 8" joist construction.

Plaster Frame

Housing is secured to plaster frame with screws and can be removed for access to junction box. Housing adjusts from 1/2" to 1 1/2" to accommodate ceiling thickness.

Junction Box

Listed for through branch circuit wiring and includes several 3/4" knockouts. Supplied with three quick connect push-in wire connectors. Four pry-outs with integral strain relief simplify Romex installation.

Hanger Bars

Heavy-gauge NICOR captive hanger bars provide greater stability, allowing housing to be positioned at any point within a 24" joist span, then locked in place with set screws. Unique hanger bar lip design helps align can to joist. Four double-headed captive nails provide for ease of installation.

Bars can be repositioned 90° on plaster frame without tools.

Bars fit onto T-bar spine for quick alignment and can be permanently secured.

Score lines allow bars to be shortened without tools to accommodate a 12" joist span.

Ordering Information

| Catalog Number | Description |
|----------------|------------------------|
| 17002A | 6" IC Airtight Housing |

Project

Catalog

Type

