



Kingston™ | K-25100-RA

Toilet tank, 1.28 gpf

Features

- Ideal for commercial installations
- 1.28 gpf (4.8 lpf)
- Durable metal right-hand Polished Chrome trip lever
- Combines with a K-25076 or K-25076-SS bowl to create a complete K-25077-RA or K-25077-SSRA Kingston two-piece toilet
- Class Five® canister optimizes the flow out of the tank, harnessing gravity and the natural, powerful reducing cascade of water to increase the power and effectiveness of the flush



Sustainability



Available Colors/Finishes

Color tiles intended for reference only.

- 0 White



1-800-4KOHLER (1-800-456-4537)
Kohler Co. reserves the right to make revisions without notice to product specifications.
For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.
4-22-2026 10:3 - US-CA

THE BOLD LOOK
OF **KOHLER**®

Codes/Standards

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.



ASME A112.19.2/CSA B45.1
EPA WaterSense®

Technical Information

Flush Type: Class Five
Flush Rate: 1.28 gpf (4.8 lpf)

Recommended Products/Accessories

K-23726 Drain treatment

Warranty

See website for detailed warranty information.

KOHLER® Toilets and Seats Limited Warranty



No image available.

This product is a component and not intended to be a standalone installation.

Installation

- Three-bolt quick-connect installation
 - Supply line sold separately
-

Installation Notes

Install this product according to the installation instructions.

Product dimensions are nominal and may vary per ASME A112.19.2 tolerances.

