

## Non UL Flexcon™ Super-Flexible Steel (5100 Series)



FLEXIBLE METAL CONDUITS - STEEL

### Description

AFC Cable Systems, Inc. FLEXCON EXTRA-FLEXIBLE STEEL CONDUIT is manufactured from one continuous length of high grade steel, hot dipped in a zinc bath for protection against the normal effects of corrosion. The steel strip is formed into interlocking convolutions firmly joined to assure a rugged yet very flexible conduit which provides exceptional flexibility for tight U-bend applications. The convolutions are manufactured to insure smoother interior and exterior surfaces, which facilitate both cable and conduit pulling. The FlexCon installs easily with standard armored cable or flexible metal conduit connectors. The product is designed to be used for specific applications where Underwriters Laboratories Inc. or other agency approvals are not required.

- Made in USA of US and/or imported materials

ORDERING INFORMATION				PRODUCT DIMENSIONS/BEND RADIUS			
Product Code	Trade Size (inches)	Trade Size (mm)	Coil Length (feet)	Approx. Weight/ 100 feet (pounds)	Internal Diameter (min/max) inches	External Diameter (min/max) inches	Bend Radius inches (mm)
5101-24-00	3/8	12	50	11.8	0.375/0.400	0.520/0.540	1.250
5101-30-00	3/8	12	100	11.8	0.375/0.400	0.520/0.540	1.250
5101-42-00	3/8	12	250	11.8	0.375/0.400	0.520/0.540	1.250
5102-24-00	1/2	16	50	14.3	0.500/0.525	0.640/0.665	1.750
5102-30-00	1/2	16	100	14.3	0.500/0.525	0.640/0.665	1.750
5103-24-00	3/4	21	50	19.9	0.750/0.775	0.890/0.915	2.000
5103-30-00	3/4	21	100	19.9	0.750/0.775	0.890/0.915	2.000

NOTE: All dimensions and weights are subject to normal manufacturing tolerances.