

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : PLASTIK 70 SUPER  
 UFI : C06X-98SK-H00T-VC5F  
 Product code : BDS001209BU

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses

Main use category : Professional use  
 Use of the substance/mixture : Anti Corrosion Products

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

CRC Industries Europe B.V.  
 Touwslagerstraat 1  
 9240 Zele  
 Belgium  
 T +32(0)52/45.60.11, F +32(0)52/45.00.34  
[hse@crcind.com](mailto:hse@crcind.com), [www.crcind.com](http://www.crcind.com)

#### 1.4. Emergency telephone number

Emergency number : +32(0)52/45.60.11  
 Office hours: 9-17h CET

Country/Area	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Brussels	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225  
 Serious eye damage/eye irritation, Category 2 H319  
 Skin sensitisation, Category 1 H317  
 Specific target organ toxicity – Single exposure, Category 3, H336  
 Narcosis  
 Specific target organ toxicity – Single exposure, Category 3, H335  
 Respiratory tract irritation  
 Aspiration hazard, Category 1 H304  
 Hazardous to the aquatic environment – Chronic Hazard, H411  
 Category 2

Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

May cause drowsiness or dizziness. May cause respiratory irritation. May cause an allergic skin reaction. Causes serious eye irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

# PLASTIK 70 SUPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

GHS09

Signal word (CLP) :

Danger

Contains :

n-butyl acetate; propan-2-ol; isopropyl alcohol; isopropanol; Hydrocarbons, C9, aromatics; n-butyl acrylate; octhilinone (ISO); 2-octyl-2H-isothiazol-3-one; xylene

Hazard statements (CLP) :

H225 - Highly flammable liquid and vapour.  
H304 - May be fatal if swallowed and enters airways.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H335 - May cause respiratory irritation.  
H336 - May cause drowsiness or dizziness.  
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) :

P102 - Keep out of reach of children.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective gloves/eye protection.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P405 - Store locked up.  
P501 - Dispose of contents/container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements :

EUH066 - Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
n-butyl acetate substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	25 – 50	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
propan-2-ol; isopropyl alcohol; isopropanol substance with national workplace exposure limit(s) (BE)	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558-25	25 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Hydrocarbons, C9, aromatics	CAS-No.: 128601-23-0 EC-No.: 918-668-5 REACH-no: 01-2119455851-35	10 – 25	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

# PLASTIK 70 SUPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
xylene substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32	1 – 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=1,5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
n-butyl acrylate substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 141-32-2 EC-No.: 205-480-7 EC Index-No.: 607-062-00-3 REACH-no: 01-2119453155-43	< 0,5	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=1,5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 3, H412
Terbutryn	CAS-No.: 886-50-0 EC-No.: 212-950-5	< 0,1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Sens. 1B, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)
oethylinone (ISO); 2-octyl-2H-isothiazol-3-one	CAS-No.: 26530-20-1 EC-No.: 247-761-7 EC Index-No.: 613-112-00-5	< 0,1	Acute Tox. 2 (Inhalation:dust,mist), H330 (ATE=0,27 mg/l) Acute Tox. 3 (Dermal), H311 (ATE=311 mg/kg bodyweight) Acute Tox. 3 (Oral), H301 (ATE=125 mg/kg bodyweight) Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071

### Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
Terbutryn	CAS-No.: 886-50-0 EC-No.: 212-950-5	(3 ≤ C < 100) Skin Sens. 1B; H317
oethylinone (ISO); 2-octyl-2H-isothiazol-3-one	CAS-No.: 26530-20-1 EC-No.: 247-761-7 EC Index-No.: 613-112-00-5	(0,0015 ≤ C ≤ 100) Skin Sens. 1A; H317

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures general : Call a physician immediately.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell. If signs/symptoms develop, get medical attention.

# PLASTIK 70 SUPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention. Seek medical attention if irritation develops.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Seek medical attention if irritation develops.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately. Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: Risk of lung oedema.

### 4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: During fire, gases hazardous to health may be formed.
--	---

### 5.3. Advice for firefighters

Firefighting instructions	: Move containers from fire area if it can be done without personal risk. Use standard firefighting procedures and consider the hazards of other involved materials.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Protective equipment	: Wear appropriate protective equipment and clothing during clean-up.
Emergency procedures	: Ventilate spillage area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

#### For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Ventilate area.

### 6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

### 6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to remove residual contamination.
Other information	: Dispose of materials or solid residues at an authorized site.

# PLASTIK 70 SUPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 6.4. Reference to other sections

For disposal of contaminated materials refer to section 13 : "Disposal considerations".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid prolonged exposure. Handle in accordance with good industrial hygiene and safety procedures.
Hygiene measures	: Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Keep container closed when not in use.
--------------------	---

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### National occupational exposure and biological limit values

n-butyl acetate (123-86-4)	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	n-Butyl acetate
IOEL TWA	241 mg/m <sup>3</sup>
	50 ppm
IOEL STEL	723 mg/m <sup>3</sup>
	150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Acétate de n-butyle # n-Butylacetaat
OEL TWA	238 mg/m <sup>3</sup>
	50 ppm
OEL STEL	712 mg/m <sup>3</sup>
	150 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
<b>propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)</b>	
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Alcool isopropylique # Isopropylalcohol
OEL TWA	500 mg/m <sup>3</sup>
	200 ppm

# PLASTIK 70 SUPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)</b>	
OEL STEL	1000 mg/m <sup>3</sup>
	400 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
<b>n-butyl acrylate (141-32-2)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	n-Butylacrylate
IOEL TWA	11 mg/m <sup>3</sup>
	2 ppm
IOEL STEL	53 mg/m <sup>3</sup>
	10 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Acrylate de n-butyle # n-Butylacrylaat
OEL TWA	11 mg/m <sup>3</sup>
	2 ppm
OEL STEL	53 mg/m <sup>3</sup>
	10 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
<b>xylene (1330-20-7)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Xylene, mixed isomers, pure
IOEL TWA	221 mg/m <sup>3</sup>
	50 ppm
IOEL STEL	442 mg/m <sup>3</sup>
	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Xylène, isomères mixtes, purs # Xyleen, mengsel van isomeren, zuiver
OEL TWA	221 mg/m <sup>3</sup>
	50 ppm
OEL STEL	442 mg/m <sup>3</sup>
	100 ppm
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als aanwezigheid in de lucht.
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023

# PLASTIK 70 SUPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### DNEL and PNEC

<b>n-butyl acetate (123-86-4)</b>	
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0,18 mg/l
PNEC aqua (marine water)	0,018 mg/l
PNEC aqua (intermittent, freshwater)	0,36 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	0,981 mg/kg dwt
PNEC sediment (marine water)	0,0981 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0,0903 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	35,6 mg/l
<b>propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	888 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	500 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	26 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	89 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	319 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	140,9 mg/l
PNEC aqua (marine water)	140,9 mg/l
PNEC aqua (intermittent, freshwater)	140,9 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	552 mg/kg dwt
PNEC sediment (marine water)	552 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	28 mg/kg dwt
<b>PNEC (Oral)</b>	
PNEC oral (secondary poisoning)	160 mg/kg food
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	2251 mg/l
<b>Hydrocarbons, C9, aromatics (128601-23-0)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	25 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	150 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	11 mg/kg bodyweight/day

# PLASTIK 70 SUPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>Hydrocarbons, C9, aromatics (128601-23-0)</b>	
Long-term - systemic effects, inhalation	32 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	11 mg/kg bodyweight/day
<b>n-butyl acrylate (141-32-2)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - local effects, inhalation	11 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0,00272 mg/l
PNEC aqua (marine water)	0,000272 mg/l
PNEC aqua (intermittent, freshwater)	0,011 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	0,0338 mg/kg dwt
PNEC sediment (marine water)	0,00338 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	1 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	3,5 mg/l
<b>octhilinone (ISO); 2-octyl-2H-isothiazol-3-one (26530-20-1)</b>	
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	2,2 µg/l
PNEC aqua (marine water)	0,22 µg/l
PNEC aqua (intermittent, freshwater)	1,22 µg/l
PNEC aqua (intermittent, marine water)	0,122 µg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	47,5 µg/kg dw
PNEC sediment (marine water)	4,75 µg/kg dw
<b>PNEC (Soil)</b>	
PNEC soil	8,2 µg/kg dw
<b>xylene (1330-20-7)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, inhalation	442 mg/m <sup>3</sup>
Acute - local effects, inhalation	442 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	212 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	221 mg/m <sup>3</sup>
Long-term - local effects, inhalation	221 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, inhalation	260 mg/m <sup>3</sup>
Acute - local effects, inhalation	260 mg/m <sup>3</sup>
Long-term - systemic effects,oral	12,5 mg/kg bodyweight/day

# PLASTIK 70 SUPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>xylene (1330-20-7)</b>	
Long-term - systemic effects, inhalation	65,3 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	125 mg/kg bodyweight/day
Long-term - local effects, inhalation	65,3 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0,327 mg/l
PNEC aqua (marine water)	0,327 mg/l
PNEC aqua (intermittent, freshwater)	0,327 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	12,46 mg/kg dwt
PNEC sediment (marine water)	12,46 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	2,31 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	6,58 mg/l

## 8.2. Exposure controls

### Appropriate engineering controls

#### Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Personal protection equipment

#### Personal protective equipment symbol(s):



### Eye and face protection

#### Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

### Skin protection

#### Skin and body protection:

Wear suitable protective clothing

### Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. VITON gloves. . Breakthrough time : > 30 min

### Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: A

### Thermal hazards

#### Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

# PLASTIK 70 SUPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: colourless to yellow.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: > 61 °C
Flammability	: Non flammable.
Lower explosion limit	: 1,2 vol %
Upper explosion limit	: 8 vol %
Flash point	: 12 °C (closed cup)
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: Not available
pH	: Not applicable
Viscosity, kinematic	: 12,7 mm <sup>2</sup> /s at 40 °C
Viscosity, dynamic	: 17,3 mPa·s at 20 °C
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not applicable
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 0,88 g/cm <sup>3</sup> at 20 °C
Relative density	: 0,88 at 20 °C
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### Other safety characteristics

VOC content : 730 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Avoid temperatures exceeding the flash point.

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO<sub>2</sub>).

# PLASTIK 70 SUPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity (oral)** : Not classified (Based on available data, the classification criteria are not met)

**Acute toxicity (dermal)** : Not classified (Based on available data, the classification criteria are not met)

**Acute toxicity (inhalation)** : Not classified (Based on available data, the classification criteria are not met)

<b>n-butyl acetate (123-86-4)</b>	
LD50 oral rat	10760 mg/kg
LD50 dermal rabbit	> 17600 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	23,4 mg/l/4h

<b>propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)</b>	
LD50 oral rat	5840 mg/kg bodyweight

<b>Hydrocarbons, C9, aromatics (128601-23-0)</b>	
LD50 oral rat	3592 mg/kg
LD50 dermal rabbit	> 3160 mg/kg bodyweight
LC50 Inhalation - Rat	> 6,193 mg/l/4h

<b>n-butyl acrylate (141-32-2)</b>	
LD50 oral rat	3150 mg/kg bodyweight
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	10,3 mg/l/4h

<b>octhilinone (ISO); 2-octyl-2H-isothiazol-3-one (26530-20-1)</b>	
LD50 oral rat	125 mg/kg bodyweight
LD50 dermal rabbit	690 mg/kg

<b>xylene (1330-20-7)</b>	
LD50 oral	4300 mg/kg bodyweight
LD50 dermal rabbit	12126 mg/kg bodyweight
LC50 Inhalation - Rat [ppm]	> ppm

**Skin corrosion/irritation** : Not classified (Based on available data, the classification criteria are not met)  
pH: Not applicable

<b>n-butyl acetate (123-86-4)</b>	
pH	6,2

**Serious eye damage/irritation** : Causes serious eye irritation.  
pH: Not applicable

<b>n-butyl acetate (123-86-4)</b>	
pH	6,2

**Respiratory or skin sensitisation** : May cause an allergic skin reaction.

**Germ cell mutagenicity** : Not classified (Based on available data, the classification criteria are not met)

**Carcinogenicity** : Not classified (Based on available data, the classification criteria are not met)

**Reproductive toxicity** : Not classified (Based on available data, the classification criteria are not met)

**STOT-single exposure** : May cause drowsiness or dizziness. May cause respiratory irritation.

<b>n-butyl acetate (123-86-4)</b>	
STOT-single exposure	May cause drowsiness or dizziness.

# PLASTIK 70 SUPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>Hydrocarbons, C9, aromatics (128601-23-0)</b>	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
<b>n-butyl acrylate (141-32-2)</b>	
STOT-single exposure	May cause respiratory irritation.
<b>xylene (1330-20-7)</b>	
STOT-single exposure	May cause respiratory irritation.
<b>STOT-repeated exposure</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>n-butyl acetate (123-86-4)</b>	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
<b>Hydrocarbons, C9, aromatics (128601-23-0)</b>	
NOAEL (oral, rat, 90 days)	600 mg/kg bodyweight
<b>xylene (1330-20-7)</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	: May be fatal if swallowed and enters airways.
<b>PLASTIK 70 SUPER</b>	
Viscosity, kinematic	12,7 mm <sup>2</sup> /s at 40 °C
<b>n-butyl acetate (123-86-4)</b>	
Viscosity, kinematic	0,83 mm <sup>2</sup> /s
<b>11.2. Information on other hazards</b>	
<b>Endocrine disrupting properties</b>	
Adverse health effects caused by endocrine disrupting properties	: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %
<b>SECTION 12: Ecological information</b>	
<b>12.1. Toxicity</b>	
Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.
<b>n-butyl acetate (123-86-4)</b>	
LC50 - Fish [1]	18 mg/l
EC50 - Crustacea [1]	44 mg/l
EC50 72h - Algae [1]	674,7 mg/l
LOEC (chronic)	47,6 mg/l

# PLASTIK 70 SUPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>n-butyl acetate (123-86-4)</b>	
NOEC (chronic)	23,2 mg/l
NOEC chronic algae	200 mg/l
<b>propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)</b>	
LC50 - Fish [1]	10000 mg/l
LC50 - Fish [2]	9640 mg/l
<b>Hydrocarbons, C9, aromatics (128601-23-0)</b>	
LC50 - Fish [1]	9,2 mg/l
EC50 - Crustacea [1]	3,2 mg/l
EC50 72h - Algae [1]	2,6 – 2,9 mg/l
<b>n-butyl acrylate (141-32-2)</b>	
LC50 - Fish [1]	> 5,2 mg/l
EC50 - Crustacea [1]	8,2 mg/l Daphnia magna (Water flea)
EC50 96h - Algae [1]	2,65 mg/l
<b>Terbutryn (886-50-0)</b>	
LC50 - Fish [1]	1,9 mg/l
EC50 - Crustacea [1]	6,4 mg/l Daphnia magna (Water flea)
EC50 72h - Algae [1]	0,0067 mg/l
NOEC chronic fish	0,073 mg/l (28d)
<b>octhilinone (ISO); 2-octyl-2H-isothiazol-3-one (26530-20-1)</b>	
LC50 - Fish [1]	0,122 mg/l
EC50 - Crustacea [1]	0,107 – 0,32 mg/l
EC50 96h - Algae [1]	0,15 mg/l
<b>12.2. Persistence and degradability</b>	
<b>PLASTIK 70 SUPER</b>	
Persistence and degradability	Not established. No data is available on the degradability of this product.
<b>12.3. Bioaccumulative potential</b>	
<b>PLASTIK 70 SUPER</b>	
Partition coefficient n-octanol/water (Log Kow)	Not applicable
<b>n-butyl acetate (123-86-4)</b>	
Partition coefficient n-octanol/water (Log Pow)	2,3
<b>n-butyl acrylate (141-32-2)</b>	
Partition coefficient n-octanol/water (Log Pow)	2,36
<b>Terbutryn (886-50-0)</b>	
Partition coefficient n-octanol/water (Log Pow)	3,74
<b>octhilinone (ISO); 2-octyl-2H-isothiazol-3-one (26530-20-1)</b>	
Partition coefficient n-octanol/water (Log Pow)	2,9

# PLASTIK 70 SUPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### xylene (1330-20-7)

Partition coefficient n-octanol/water (Log Pow) 3,1

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

#### PLASTIK 70 SUPER

Results of PBT assessment Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

### 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

### 12.7. Other adverse effects

Additional information : No other effects known






## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
European List of Waste (LoW, EC 2000/532) : According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263
<b>14.2. UN proper shipping name</b>				
PAINT (Solvent naphtha)	PAINT (Solvent naphtha)	Paint (Solvent naphtha)	PAINT (Solvent naphtha)	PAINT (Solvent naphtha)
<b>Transport document description</b>				
UN 1263 PAINT (Solvent naphtha), 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT (Solvent naphtha), 3, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1263 Paint (Solvent naphtha), 3, II, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT (Solvent naphtha), 3, II, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT (Solvent naphtha), 3, II, ENVIRONMENTALLY HAZARDOUS
<b>14.3. Transport hazard class(es)</b>				
3	3	3	3	3
				

# PLASTIK 70 SUPER


## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
<b>14.4. Packing group</b>				
II	II	II	II	II
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-E EmS-No. (Spillage): S-E	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 163, 367, 640C, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP8, TP28
Tank code (ADR)	: L1.5BN
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33
Orange plates	: 
Tunnel restriction code (ADR)	: D/E

#### Transport by sea

Special provisions (IMDG)	: 163, 367
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP8, TP28
Stowage category (IMDG)	: B
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

#### Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

# PLASTIK 70 SUPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 163, 367, 640C, 650
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E2
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1

### Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 163, 367, 640C, 650
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP8, TP28
Tank codes for RID tanks (RID)	: L1.5BN
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE7
Hazard identification number (RID)	: 33

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

##### Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

##### VOC Directive (2004/42)

VOC content : 730 g/l

##### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

# PLASTIK 70 SUPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Indication of changes		
Section	Changed item	Comments
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Modified
2.2	Hazard statements (CLP)	Modified

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet

# PLASTIK 70 SUPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Abbreviations and acronyms:

STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

### Full text of H- and EUH-statements:

Acute Tox. 2 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

# PLASTIK 70 SUPER

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Corr. 1	Skin corrosion/irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.