

## FROGTAPE ADVANCED™ PAINTER'S TAPE

### TYPICAL APPLICATIONS

- For interior or exterior use on cured painted walls, wood trim, glass and metal; including curved surfaces

### PRODUCT FEATURES

- Ultra-premium grade, multi-surface FrogTape® brand painter's tape treated with PaintBlock® Technology for super sharp paint lines
- Medium adhesion
- Washi paper backing is two times stronger than crepe paper painter's tape\* for better conformability, shred-resistance and tear-free removal
- 28-day indoor clean removal and ability to withstand direct outdoor sunlight for up to 7 days with Nano Technology, which absorbs and scatters penetrating UV light, protecting the adhesive from degradation
- Solvent-free, high performance Quick Stick Adhesive bonds to the surface 60x faster than leading competitors for painting immediately after application
- \*As compared to FrogTape® Multi-Surface Painter's Tape, based on internal testing
- \*\*Test before use on all surfaces and when using solvent-based coatings; FrogTape® was designed for use with latex paint

### CONSTRUCTION

Backing: Washi paper backing

Adhesive: Synthetic rubber-based adhesive

### STANDARD WIDTHS

0.94 in; 1.41 in; 1.88 in

24 mm; 36 mm; 48 mm

### STANDARD LENGTH

45 yd

41 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

### STANDARD CORE SIZE

3 in

### APPLICABLE STANDARDS

NA

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR



### PHYSICAL PROPERTIES

Adhesion to Stainless Steel

Elongation

Tensile

Thickness

### STANDARD

43 oz/in width

8%

24 lbs/in width

4.1 mils

### METRIC

4.71 N/10 mm

8%

42 N/10mm

0.1 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



The mark of responsible forestry  
FSC® C154304