



PDU13102 | BASIC PDU SERIES



Deliver reliable power to electronic equipment, servers, and network/telecom devices

Deliver reliable unfiltered power to connected equipment with the CyberPower PDU13102 basic 3-Phase PDU. Designed for data centers and other electrically demanding applications, this unit features rugged, industrial-grade metal housing, network-grade outlets and operates in high temperatures up to 140°F (60°C).

The PDU13102 supports a 208V 20A input, includes 27 outlets, and provides a maximum output load of 5.7kW. The CyberPower PDU13102 is protected by a three-year limited warranty.

TYPICAL APPLICATIONS

- Data Centers
- Corporate Servers
- Network Closets

FEATURES

- Phase: 3-Phase
- Amps: 20A (Derated to 16A)
- Volts: 208V
- Max. Output Load: 5.7kW
- Frequency: 50/60Hz
- Input plug type: NEMA L21-20P
- Outlets: 21 x NEMA 5-20R + 6 x NEMA L6-20R
- Size: 0U Rackmount
- Cord Length (ft): 10
- Dimensions (in): 2.2W x 70.5H x 2.2D
- Warranty: Three-Year

SPECIFICATIONS

INPUT	
Cord Length	10 ft (3.0 m)
Derated Input Current	16 A
Input Frequency Range	50 Hz - 60 Hz
Input Plug Type	NEMA L21-20P
Maximum Input Current	20 A
Nominal Input Voltage	208 VAC
Phase	3-Phase

OUTPUT	
Nominal Output Voltage	120 - 208 VAC
Outlet Type	21 x NEMA 5-20R 6 x NEMA L6-20R
Outlets - Total	27
Overload Protection	None

PDU13102

BASIC PDU SERIES

SPECIFICATIONS CONT.

PHYSICAL	
Adjustable Mounting Brackets	1 Set
Color	Black
Cord Retention Tray/ Cord Organizers	Yes
Form Factors Supported	OU Vertical Rackmount
Material of Construction	Metal
Rack Height	OU

PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	5.59 x 179.07 x 5.59 cm
Physical Dimensions - Width/Height/Depth (mm)	56 x 1791 x 56 mm
Physical Dimensions - Width/Height/Depth (in.)	2.2 x 70.5 x 2.2 in.
Weight (kg)	5.62 kg
Weight (lbs.)	12.4 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	201.3 x 15.24 x 17.15 cm
Shipping Dimensions - Width/Height/Depth (mm)	2012.95 x 152.4 x 171.45 mm
Shipping Dimensions - Width/Height/Depth (in.)	79.25 x 6 x 6.75 in.
Shipping Weight (kg)	8.98 kg
Shipping Weight (lbs.)	19.8 lbs.

ENVIRONMENTAL	
Operating Elevation	0 - 11,480 ft (0 - 3,499 m)
Operating Relative Humidity	0 - 95 % (non-condensing)
Operating Temperature	23 - 140 °F (-5 - 60 °C)

CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL 60950-1 FCC Class A

WARRANTY	
Product Warranty	Three-Year Limited