

# Specifications



Photo is representative



## Eaton LRTP615

Eaton Cooper Power series loadbreak reducing tap plug, EPDM rubber, 15 kV, Phase to ground: 8.3 kV, AC 1 min: 34 kV, DC 15 min: 53 kV, BIL: 95 kV, Corona: 11 kV, 600 A, T-OP II, Bulk pack 10

### General specifications

PRODUCT NAME	Eaton Cooper Power series T-OP II loadbreak reducing tap plug
CATALOG NUMBER	LRTP615
UPC	194006017213
PRODUCT HEIGHT	10.8 in
PRODUCT DIAMETER	3.2 in
PRODUCT WEIGHT	0.001 lb
COMPLIANCES	Not Applicable
CERTIFICATIONS	IEEE Std 386



Powering Business Worldwide

Additional Specifications	
PACKAGING	Bulk pack 10
TYPE	T-OP II Loadbreak reducing tap plug

Electrical Ratings	
AC 1 MINUTE VOLTAGE WITHSTAND	34 kV
BASIC IMPULSE LEVEL	95 kV
CURRENT RATING	600 A
MAXIMUM RATING PHASE-TO-GROUND	8.3 kV
STANDARD VOLTAGE CLASS	15 kV

Descriptions	
MATERIAL	EPDM rubber
STUD TYPE	T-OP II

Resources	
SPECIFICATIONS AND DATASHEETS	<a href="#">Eaton Specification Sheet - L RTP615</a>
	<a href="#">Line installation and protective equipment specifiers guide</a>

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark. Follow us on social media to get the latest product and support information.  
All other trademarks are property of their respective owners.

