

INDUSTRIAL GRADE FILAMENT TAPE



DESCRIPTION

A high strength filament tape consisting of glass filaments laminated to polypropylene film and coated with an aggressive high tack adhesive. It is water and moisture resistant.

MAIN FEATURES

- Strength.
- Ease of handling.
- Suits most applications.
- High tack.
- Water resistant.

APPLICATIONS

- Palletizing of boxes in warehousing to conserve floor space.
- Strapping rods, moulding, tubes plywood without danger of scratching, staining or damaging.
- Reinforcing cartons, protecting contents from pilferage.
- Holding doors, loose parts on stoves, refrigerators while in transit.
- Available in 329m Rolls for L-Clip Application.

STRENGTH

HIGH TACK

TECHNICAL DATA

Colour	Translucent Ivory
Backing	Polypropylene film laminated to fiberglass filament
Adhesive	Thermoplastic rubber
Thickness	5 mil
Adhesion	95 oz/in
Tensile Strength.....	160 lb/in
Elongation	6%
Temperature Resistance	-30°C to 55°C (-22°F to 130°F)

Please note:

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness.

The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded.

No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.