

# SW-610-24P-R DATASHEET

**ProWatch™**  
**-INTEGRATED-**



## 24 PoE+ Ports (370W Power Budget) Layer 2 and Layer 3 Functionality Optimized for AV Over IP Applications

The Luxul 24-Port Gigabit PoE+ L2/L3 Managed AV Series Switch (SW-610-24P-R) is an excellent choice for expanding your network when using PoE-enabled devices such as Touch Panels, IP cameras and Wireless Access Points. The 24-port Gigabit switch includes 24 Gigabit PoE+ Ethernet ports and four 10 Gigabit SFP+ expansion ports. SFP+ ports can be aggregated for up to a 40Gb connection. With PoE+ you can use standard Ethernet cable to deliver both power and high speed data to 802.3af/at-compliant devices, with a total power budget of 370 Watts. The advanced Layer 2/Layer 3 features and simple-to-use management interface allows easy configuration to meet the needs of simple to sophisticated systems.

## Features

### 24 GIGABIT 802.3AF/AT PoE+ PORTS (370W POWER BUDGET)

#### CONFIGURATION

- Luxul ProWatch Integrated
- Four 10Gbps SFP+ ports
- Layer 2+ and L3 Static Route Support
- 802.1Q VLAN (with Trunking)
- QoS Support
- Plug-and-Play Installation with Intuitive Management

#### POWER

- Simple Power Management of PoE-Enabled Devices (370W Power Budget)
- PoE Self-Healing
- PoE stays active with soft reboot

#### INSTALLATION

- Standard 1U 19" Rack- Mount Enclosure
- Low Noise Variable Speed Fans
- Three Year Limited Warranty

## Ordering Information

24-Port Gigabit PoE+ L2/L3 Managed AV Switch	<b>North America</b> SW-610-24P-R	<b>Australia</b> SW-610-24P-R-A	<b>Europe</b> SW-610-24P-R-E	<b>UK</b> SW-610-24P-R-U
--	--------------------------------------	------------------------------------	---------------------------------	-----------------------------

# SW-610-24P-R

## Technical Specifications

Protocols and Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3af/ at, IEEE 802.3x, IEEE 802.3ad, IEEE 802.3az, IEEE 802.1ab, IEEE 802.1d, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1v, IEEE 802.1w, IEEE 802.1X,
Forwarding Capacity	95.2Mpps (64 byte packets)
Switching Capacity	128Gbps
MAC Table	Up to 32K (32768) MAC addresses
Jumbo Frames	Frame sizes up to 10240 Bytes
Interface Options	RJ45: 10BASE-T 100BASE-TX 1000BASE-T SFP+: up to 10Gbps
VLAN	802.1Q max 4095 VIDs & VLAN Trunking Supports 1 Management VLAN
Surge Protection	The RJ45 port surge protection is tested to: EN61000-4-5 (for RJ45 Port, Surge 6KV)
Quality of Service (QoS)	8 Hardware Queues Queue Scheduling: Strict Priority and Weighted Round Robin (WRR) VLAN priority based Layer 2 CoS QoS Port based Layer 3 DSCP QoS Port based bandwidth control
Network Data Transfer Rate	Ethernet: 10Mbps (Half-duplex) Ethernet: 20Mbps (Full-duplex) Fast Ethernet: 100Mbps (Half-duplex) Fast Ethernet: 200Mbps (Full-duplex) Gigabit Ethernet: 1000Mbps (Half-duplex) Gigabit Ethernet: 2000Mbps (Full-duplex) SFP+: 10Gbps
LED	Per Unit: System, Link/Act or PoE status Per Port: Link/Activity and POE
Power Budget	370W
Max Power Consumption	459W @ 100VAC, 448W @ 240VAC
Power Supply	Internal Switched Power, AC 100-240V, 50-60Hz input
Operating Temperature	32°F to 122°F (0°C to 50°C)
Operating Humidity	10% to 90% (Non-condensing)
Dimensions LxWxH in. (mm)	17.4"x8.3"x1.75" (442 x 211 x 44mm)
Weight lbs (kg)	8.4 (3.8)
Certifications	FCC Part 15 Class A, IC, CE-EMC, CE-LVD, CB(IEC 62368-1:2014), RCM, VCCI, RoHS