

# 8.8W (60W Replacement) Selectable Color A60 B22 Base LED Bulbs (6-Pack)



- Get 2700K/3000K/4000K/5000K/6500K light with a flip of a switch
- Versatile A60 bulb suitable for a variety of fixtures and lighting applications
- Dimmable design lets you create the right environment in any room

## Product Specifications

Item Number: **CEOM60/5CCT/6/UK**

Lighting technology used	LED
Non-directional or directional	Non-Directional
Light source cap-type (or other electric interface)	B22
Correction factor C depending on light source characteristics-Main or non-mains	Non-Main
Connected light source (CLS):	N/A
Useful luminous flux(Lm)*	806
Correlated colour temperature (K) *	2700/3000/4000/5000/6500
Chromaticity coordinate (x):	0.3094
Chromaticity coordinate (y):	0.3333
The beam angel or range of beam angles(0)*	N/A
Beam angle correspondence : Sphere or wide cone or narrow cone	Wide Cone
Electrical interface details*	220-240V 50/60Hz
The L70B50 life time expressed in hours	15,000
The on-mode power (Pon) expressed in W	8.8
Lamp Dimensions(mm)	119*60
The standby power (Psb) expressed in W	N/A
The networked standby power (Pnet) for CLS expressed in W	N/A
The Colour rendering index 80	84.8
Survival factor (Max value =1)	1
Lumen maintenance factor (Max value =1)	971%
Displacement factor (Max value =1)	0.95
Colour consistency in McAdam ellipses (Max value =9)	2.6
Flicker metric (Max value =9.9)	1
Stroboscopic effect metric (Max value =9.9)	0.05
Spectral power distribution in the range 250 nm to 800 nm, at full-load (File to be uploaded)	
If the light source is designed for optimum use in nonstandard conditions (such as ambient temperature Ta ≠ 25 0C or specific thermal management is necessary)	N/A
A warning if the light source cannot be dimmed or can be dimmed only with specific dimmers or with specific wired or wireless dimming methods	Non-Dimmable
Mercury content x,x mg (if applition) 0,0	0
Energy consumption in on-mode (KWh/1000h):	
Energy Efficacy Class	F