


James

BY SONANCE

POWERPIPE X SERIES DATA SHEET



TECHNICAL SPECIFICATIONS

SKU	PPX8-M 60665 - Each
Woofers	8" (205mm) anodized aluminum cone, rubber surround, high excursion
Frequency Response	44Hz - 130Hz +/-3dB
Impedance	4 ohms nominal
Sensitivity (2.83V/1m)	91dB SPL
Enclosure	Marine-Grade Aluminum
Finish	Textured Black
Recommended Power	300 watts
Recommended Amplifiers	Blaze Powerzone Connect 1002 2004 4008 Sonance DSP 2-750 MKIII
Tube Inside Diameter	4.02" (102mm)
Tube Length	21.65" (550mm)
Product Dims w/ Feet (WxHxD)	11.81" x 12.42" x 11.5" (300mm x 315mm x 292mm)
Product Dims w/o Feet (WxHxD)	11.81" x 11.81" x 11.5" (300mm x 300mm x 292mm)
Product Weight	30.56 lbs. (13.86kg)
Shipping Weight	36.38 lbs. (16.5kg)

ACCESSORIES

PPX-4to6-90-ADAPTER | 93792
PPX 4" to 6" 90-Degree Adapter

PPX-4to6-STR-ADAPTER | 93791
PPX 4" to 6" Straight Adapter

PPX-8R | 93796
PPX 8" XPC Grille Connector

PPX-6R | 93795
PPX 6" XPC Grille Connector

PPX-4R | 93794
PPX 4" XPC Grille Connector

PPX-3.5x16-2-STR | 93790
PPX Straight Toekick Connector and Grille

PPX-3.5x16-2-90 | 93789
PPX 90-Degree Toekick Connector and Grille

PPX TOEKICK REPLACEMENT GRILLE | 93799
Straight or 90-Degree Toekick Connector Required