

## CSA HYDROTITE™ “COM-BLUE” (6300 Series)



### Description

- Corrosion resistant hot-dipped galvanized zinc steel core
- FT-4 rated PVC jacket
- Integral bond wire inserted between the convolutions of the spiral wound metal armor for Trade Sizes 12 (3/8) – 35 (1-1/4)
- UV resistant
- Flexible in cold weather
- Sequential Print in meters printed on jacket

### Applications

- Computer rooms
- OEM's
- Equipment builders
- CSA Equipment
- Where flexible connections are required

### Specifications

- Available with custom print up to 200 characters long
- Temperature rating 75°C dry, 75°C oil
- Standard color blue (custom colors available upon request)
- CSA Certified to CSA C22.2 No.56 under Files 51593 and MC157782
- CEC Hazardous locations: Class I Div. 2, Class II Div. 1 18-202 (4)(b), Class II Div. 2 18-252 (4), Class III Div. 1 18-302 (4), Class III Div. 2 18-352
- Meets -30°C Flexibility Test
- Meets -25°C Cold Impact Test

ORDERING INFORMATION						PRODUCT DIMENSIONS/BEND RADIUS			
Product Code	Catalog Number	Trade Size in. (mm)	Coil Length (meters)	Reel Length (meters)	Approximate Weight (kg/meter)	Internal Diameter Min. mm(in.)	External Diameter Min. mm(in.)	External Diameter Max. mm(in.)	Bend Radius mm(in.)
6301-21-00	CM4D0375M0030C	3/8 (12)	30	–	0.33	12.29 (0.484)	17.50 (0.690)	18.00 (0.710)	102 (4.0)
6301-80-00	CM4D0375M0300R	3/8 (12)	–	300	0.33	12.29 (0.484)	17.50 (0.690)	18.00 (0.710)	102 (4.0)
6302-21-00	CM4D0500M0030C	1/2 (16)	30	–	0.40	15.80 (0.622)	20.80 (0.820)	21.30 (0.840)	152 (6.0)
6302-35-00	CM4D0500M0150R	1/2 (16)	–	150	0.40	15.80 (0.622)	20.80 (0.820)	21.30 (0.840)	152 (6.0)
6302-80-00	CM4D0500M0300R	1/2 (16)	–	300	0.40	15.80 (0.622)	20.80 (0.820)	21.30 (0.840)	152 (6.0)
6303-21-00	CM4D0750M0030C	3/4 (21)	30	–	0.53	20.83 (0.820)	25.20 (1.030)	26.70 (1.050)	203 (8.0)
6303-35-00	CM4D0750M0150R	3/4 (21)	–	150	0.53	20.83 (0.820)	25.20 (1.030)	26.70 (1.050)	203 (8.0)
6303-80-00	CM4D0750M0300R	3/4 (21)	–	300	0.53	20.83 (0.820)	25.20 (1.030)	26.70 (1.050)	203 (8.0)
6304-21-00	CM4D1000M0030C	1 (27)	30	–	0.73	26.44 (1.041)	32.80 (1.290)	33.40 (1.315)	254 (10.0)
6304-35-00	CM4D1000M0150R	2 (27)	–	150	0.73	26.44 (1.041)	32.80 (1.290)	33.40 (1.315)	254 (10.0)
6305-15-00	CM4D1250M0015C	1-1/4 (35)	15	–	1.06	35.05 (1.380)	41.40 (1.630)	42.20 (1.660)	318 (12.5)
6305-75-00	CM4D1250M0075R	1-1/4 (35)	–	75	1.06	35.05 (1.380)	41.40 (1.630)	42.20 (1.660)	318 (12.5)
6306-15-00	CM4D1500M0015C	1-1/2 (41)	15	–	1.33	40.01 (1.575)	47.40 (1.865)	48.30 (1.900)	381 (15.0)
6306-57-00	CM4D1500M0045R	1-1/2 (41)	–	45	1.33	40.01 (1.575)	47.40 (1.865)	48.30 (1.900)	381 (15.0)
6307-15-00	CM4D2000M0015C	2 (53)	15	–	1.46	51.31 (2.020)	59.40 (2.340)	60.30 (2.375)	508 (20.0)
6307-21-00	CM4D2000M0030R	2 (53)	–	30	1.46	51.31 (2.020)	59.40 (2.340)	60.30 (2.375)	508 (20.0)
6308-08-00	CM4D2500M0008C	2-1/2 (63)	8	–	1.80	62.99 (2.480)	72.10 (2.840)	73.00 (2.875)	635 (25.0)
6309-08-00	CM4D3000M0008C	3 (78)	8	–	2.20	77.98 (3.070)	87.90 (3.460)	88.90 (3.500)	762 (30.0)
6310-08-00	CM4D4000M0008C	4 (103)	8	–	6.30	101.60 (4.000)	113.30 (4.460)	114.30 (4.500)	1016 (40.0)