# Passive LCR Soundbar

SBR1.2



## FEATURES

4" two-way, Red Label LCR passive soundbar

40 mm Air Motion Transformer (AMT) tweeters with Kapton diaphragm and neodymium magnet

4" PP + mica cone woofers with rubber surround

45 Hz ~ 20 kHz (± 3 dB) frequency response, 2.7 kHz crossover

40 W - 100 W recommended amplifier power, 89 dB sensitivity

MDF P2 enclosure with matte black finish

Magnetic steel grille

6-pin Phoenix input terminals; table top or on-wall mounting

# SPECIFICATIONS

| Specification | SBR1.2 |
|---|---|
| **GENERAL** | |
| **Description** | 4" Two-Way, Red Label LCR Passive Soundbar |
| **Enclosure Material & Finish** | MDF P2 with Matte Black finish |
| **Grille Material** | Magnetic, steel grille |
| **Mounting Style** | Table top or on wall |
| **TWEETER** | |
| **Tweeter Type & Size** | Air Motion Transformer (AMT), 40 mm |
| **Tweeter Material** | Kapton |
| **Tweeter Magnet Material** | Neodymium |
| **WOOFER** | |
| **Woofer Size** | 4 inch |
| **Woofer Cone Material** | PP + Mica |
| **Woofer Surround Material** | Rubber |
| **Woofer Voice-Coil Size** | Φ25.5 mm |
| **Woofer Magnet Weight** | 430 g |
| **AUDIO** | |
| **Frequency Response** | 45 Hz ~ 20 kHz ± 3 dB |
| **Crossover Frequency** | 2.7 kHz |
| **Recommended Amplifier Power** | 40 W - 100 W max |
| **Rated Impedance** | L & R: 8 Ohms; Center: 6 Ohms |
| **Sensitivity (Efficiency, 2.83V @ 1M)** | 89 dB |
| **Input Terminals** | 6-pin Phoenix |
| **PHYSICAL** | |
| **Dimensions (H x W x D)** | 5.22" x 55.98" x 2.83" (132.5 x 1422 x 72 mm) |
| **Net Weight** | 25.35 lb (11.5 kg) |
| **Gross Weight** | 31.96 lb (14.5 kg) |

## DIMENSIONS

SBR1.2 dimensions: 5.22" H x 55.98" W x 2.83" D (132.5 x 1422 x 72 mm).




