




YC2C4, Copper C-Shape Connector

By Burndy
Catalog # YC2C4



CU Compression C Shape Compression Connector

Features

- Range-taking connector lowering inventory requirements
- Compact size, easy to tape and insulate connection
- High conductivity wrought copper provides low resistance and excellent electrical conductivity

Application

For Range Of Copper And Making Tap Or Parallel Copper Connections

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	• UL 486A • UL486B
Buy America(n) Qualified	TAA Compliant (All status valid till December 2026)
Certification - ETL	No
Standards - Industry Standards Met	• UL 486A • UL486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	Yes

Conductor

Conductor - Copper Solid Run	• 4 AWG • 2 AWG
Conductor - Copper Solid Run Range	4 AWG-2 AWG
Conductor - Copper Solid Tap	• 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG
Conductor - Copper Solid Tap Range	8 AWG-4 AWG

Conductor - Copper Str Run	2 AWG
Conductor - Copper Str Run Range	4 Sol. - 2 Str
Conductor - Copper Str Tap	• 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG
Conductor - Copper Str Tap Range	8 Sol. - 4 Str
Conductor Type	Cu C Sol-Size

Dimensions

Dimension - L Length Overall	17 mm
Dimension - Height inch	0.98 in
Dimension - Height mm	0 mm
Dimension - Length Overall	0.67 in

General

Die Index	C
Trade Name	CRIMPIT™
Sub Brand	CRIMPIT
Plated	N
Type	YC-C Series
UPC 12 Digit	781810112250
UPC 14 Digit GTIN	00781810112250
Material	Copper
Plating Type	Unplated
UPC	781810112250

Logistics

Minimum Pack Quantity	1
Carton Quantity	100
Pallet Quantity	23200

Product Assets

[Catalog \[English\]](#)