

Product data sheet

Specifications



APC Back-UPS 600VA, 120V, 1 USB charging port, 7 NEMA outlets (2 surge)

BE600M1

Product availability: Non-Stock - Not normally stocked in distribution facility

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	120 V AC 1 phase
Input Connection Type	NEMA 5-15P
Efficiency at full load	92...139 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Output voltage	120 V AC 1 phase
Rated power in W	330 W
rated power in VA	600 VA
output connection type	5 NEMA 5-15R 2 NEMA 5-15R surge
USB Charging Port	USB type A
Maximum configurable power in VA	600 VA
Max Configurable Power (Watts)	330 W
Transfer Time	6ms typical : 10ms maximum
Topology	Standby
Waveform Type	Stepped approximation to a sinewave
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Replacement battery	APCRBC154

Graphs

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph

Complementary

Battery Size	Lead-acid internal included
Control panel	LED Status display with On Line : On Battery
Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
UPS connectivity	USB port
Let Through Voltage Rating	5 V

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Surge energy rating	490 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m
Cable length	5 ft (1.5 m)
color	Black
Height	5.5 in (139 mm)
Width	10.8 in (274 mm)
Depth	4.1 in (105 mm)
Product Weight	7.69 lb(US) (3.49 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Mounting mode	Tower
Provided equipment	User Manual
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Range of Product	Back-UPS
Product or Component Type	Uninterruptible power supply (UPS)

Environment

Product Certifications	California (CEC) Battery Charger cTUVus NOM
Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...5000 ft (0...1524 m)
Relative Humidity	0...90 %
Storage Relative Humidity	0...95 %
Acoustic level	35 dBA
Online Thermal Dissipation	16 Btu/h
Operating altitude	0...3000 ft

Batteries & Runtime

Battery Type	Lead-Acid battery
Battery Voltage	12 V
Extendable Run Time	0
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	10 h
RBC Quantity	1

Battery Life	3...5 year(s)
Battery Charge Power (Watts)	7 W rated

Ordering and shipping details

Category	11309-APC RESALE PRODUCTS
Discount Schedule	APC1
GTIN	731304325116
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	7.7 in (19.6 cm)
Package 1 Width	6.6 in (16.8 cm)
Package 1 Length	14.3 in (36.3 cm)
Package weight(Lbs)	8.40 lb(US) (3.81 kg)
SCC14	10731304325113

Contractual warranty

Warranty (in months)	12 Battery 36 UPS
----------------------	-------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Total lifecycle Carbon footprint	136 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	37 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.4 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	98 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.3 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

 Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Longer

 Lifetime extension	
Repair	No

Use Again

 Repack and remanufacture	
Recyclability potential, in %	62
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes

Technical Illustration

Dimensions



Offer Marketing Illustration

Product benefits / Features

Life Is On | Schneider Electric

APC

APC Back-UPS

Reliable battery backup to keep you connected during prolonged power outages





Long battery runtime



Reliable surge protection



7 outlets



Portable, lightweight design



1 USB Charging Port


Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features



Power goes out. You stay connected to what matters
Enjoy uninterrupted internet connection for your entertainment, smart home and security devices.

Offer Marketing Illustration

Product benefits / Features



Robust battery to keep you on track

Reliable runtime allows you to continue digital activities when the power is out.

Image of product / Alternate images

Alternative



