



T-423G

2 Piece, Standard Port, Expansion Pex Connection, Stainless Steel Trim with Drain, 400 WOG

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
LEVER HANDLE				
104-543PG	1/2"	120	10	51
104-544PG	3/4"	100	10	63
104-545PG	1"	54	6	49
T-HANDLE				
104-543PG-TH	1/2"	120	10	40
104-544PG-TH	3/4"	100	10	40

- Dezincification Resistant Brass Alloy
- Gland Follower and Single O-Ring Stem Design
- Drop Ears for Easy Installation
- Blow-Out Proof Stem
- 100% Leak Tested
- IAPMO Certified - NSF 61 & NSF 372 & NSF 14
- ASTM F1960
- Wetted Surfaces Contain Less than .25% Lead Content




T-412G

2 Piece, Standard Port, Crimp Pex Connection, 400 WOG

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
LEVER HANDLE				
103-523PG	1/2"	120	10	35
103-524PG	3/4"	120	10	54
103-525PG	1"	54	6	35
103-526PG	1-1/4"	60	10	57
103-527PG	1-1/2"	24	4	34
103-528PG	2"	12	2	29
T-HANDLE				
103-523PG-TH	1/2"	120	10	28
103-524PG-TH	3/4"	120	10	49
103-525PG-TH	1"	54	6	33

- Dezincification Resistant Brass Alloy
- Gland Follower and Single O-Ring Stem Design
- Blow-Out Proof Stem
- 100% Leak Tested
- IAPMO Certified - NSF 61 & NSF 372 & NSF 14
- ASTM F1807
- Wetted Surfaces Contain Less than .25% Lead Content



S-412G

2 Piece, Standard Port, Solder x Crimp Pex Connection, 400 WOG

PART NUMBER	SIZE	CASE	CARTON	WEIGHT
LEVER HANDLE				
103-533PG	1/2"	120	10	31
103-534PG	3/4"	120	10	54
103-535PG	1"	54	6	40
T-HANDLE				
103-533PG-TH	1/2"	120	10	25
103-534PG-TH	3/4"	120	10	49
103-535PG-TH	1"	54	6	33

- Dezincification Resistant Brass Alloy
- Gland Follower and Single O-Ring Stem Design
- Blow-Out Proof Stem
- 100% Leak Tested
- IAPMO Certified - NSF 61 & NSF 372 & NSF 14
- ASTM F1807
- Wetted Surfaces Contain Less than .25% Lead Content

