



MATERIAL

PLASTIC HOUSING : ABS high-impact UL94V-0 thermoplastic
INSERT: Brass 3604 surface gold plating

PHYSICAL CHARACTERISTICS

OPERATING TEMPERATURE RANGE : -10 C TO 60 C
STORAGE TEMPERATURE RANGE : -40 C TO 68 C
HUMIDITY : 10%~90%RH

ELECTRICAL

IMPEDANCE: 75 ohm
FREQUENCY RANGE: 0~3 GHz
WORKING VOLTAGE: 250 VRMS max.
DIELECTRIC WITHSTANDING VOLTAGE: 500VRMS min.
VSWR: 1.35 max
CONTACT RESISTANCE: 1.Center Contact: 5 Milliohms Max.
2.Outer Contact: 1 Milliohms Max.
INSULATOR RESISTANCE: 1000 Megohms min.

Colors Available: White

Scale		1.5:1		All Copy Rights Reserved	
3rd Angle Projection				F FEMALE TO RCA INSERT (for subwoofer)	
Unit		mm		SCP P/N	
Date		2015-09-16		247-XX	
Tolerance					
~20	~50	~150	150~	ANGLE	Drawn by
±0.2	±0.4	±0.5	±1.5	±2°	FHL
				Checked by	
				Santiago	