




Copper Cable, category 5e, 25 Pair, UTP, 100 MHz, CMR rated, 24 AWG, 4000 ft reel, slate

This product will be discontinued on: November 30, 2026

Product Classification

Regional Availability	Asia
Portfolio	CommScope®
Product Type	Twisted pair cable

General Specifications

Product Number	1061F
ANSI/TIA Category	5e
Cable Component Type	Horizontal
Cable Type	U/UTP (unshielded)
Conductor Type, singles	Solid
Conductors, quantity	50
Jacket Color	Slate
Pairs, quantity	25
Transmission Standards	ANSI/TIA-568.2-D CENELEC EN 50288-6-1 ISO/IEC 11801 Class D

Dimensions

Cable Length	1,219.2 m 4000 ft
Diameter Over Jacket, nominal	12.7 mm 0.5 in

Conductor Gauge, singles24 AWG

Electrical Specifications

Operating Voltage, maximum80 V

Remote PoweringFully complies with the recommendations set forth by IEEE 802.3bt (Type 4) for the safe delivery of power over LAN cable when installed according to ISO/IEC 14763-2, CENELEC EN 50174-1, CENELEC EN 50174-2 or TIA TSB-184-A

Safety Voltage Rating300 V

Material Specifications

Conductor MaterialBare copper

Insulation MaterialHigh density polyethylene (HDPE)

Jacket MaterialPVC

Environmental Specifications

Operating Temperature-20 °C to +60 °C (-4 °F to +140 °F)

Environmental SpaceNon-plenum

Packaging and Weights

Cable weight199.414 kg/km | 134 lb/kft

Packaging TypeReel

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant

UK-ROHS

Compliant

