

Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	200 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Bolt-on
Number of Poles	2P
Circuit Breaker Type	Standard
Electrical Connection	Lugs
Frame Size	QOM2

Complementary

Interrupt Rating	22 KA 120/240 V AC 22 kA 120 V AC
Wire Size	AWG 4...300 kcmil aluminium/copper
Tightening Torque	53.1 lbf.in (6 N.m) 0.006...0.1 in ² (4...65 mm ²) (AWG 12...AWG 2/0)
Height	5.6 in (142 mm)
Width	3.6 in (91 mm)
Depth	5.08 in (129 mm)
Product Weight	2.568 lb(US) (1.165 kg)
Load Center Type	Main breaker
Number of Phases	1 phase
For Use With	QO load center[RETURN]Homeline load center
Breaker compatibility	Load center QO Load center Homeline

Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	US1DE3A00100
Discount Schedule	DE3A
GTIN	785901004066
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.40 in (11.176 cm)
Package 1 Width	5.50 in (13.970 cm)
Package 1 Length	6.50 in (16.510 cm)
Package 1 Weight	2.568 lb(US) (1.165 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	208

Package 2 Height	21.00 in (53.340 cm)
Package 2 Width	40.00 in (101.600 cm)
Package 2 Length	48.00 in (121.920 cm)
Package 2 Weight	534.143 lb(US) (242.283 kg)

Offer Sustainability

Packaging without single use plastic	No
Packaging made with recycled cardboard	No
California proposition 65	"WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov "
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
Take-back	No
Carbon footprint (kg CO2 eq, Total Life cycle)	254

Contractual warranty

Warranty	18 months
----------	-----------