

Material

- Wall-mount
- KOHLER finishes resist corrosion and tarnishing.
- Single-function 54-nozzle body spray delivers a soothing spray.
- Fully adjustable sprayface pivots for targeted hydromassage.
- MasterClean™ sprayface is easy to clean.
- Low-profile design complements any décor.
- 2.5 gal/min (9.5 l/min) flow rate.
- 1/2" NPT connection.
- Single-function 54-nozzle body spray delivers a soothing spray.
- Fully adjustable sprayface pivots for targeted hydromassage.
- Low-profile design complements any decor.
- MasterClean™ sprayface is easy to clean.
- 2.5 gpm (gallons per minute) flow rate.
- 1/2-inch NPT connection
- KOHLER finishes resist corrosion and tarnishing.
- Wall-mount



Codes/Standards













ASME A112.18.1/CSA B125.1


KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	CP	Polished Chrome
	SN	Vibrant® Polished Nickel
	AF	Vibrant® French Gold
	PGD	Vibrant® Moderne Polished Gold
	BGD	Vibrant® Moderne Brushed Gold
	G	Brushed Chrome
	BN	Vibrant® Brushed Nickel
	BV	Vibrant® Brushed Bronze
	BRZ	Oil-Rubbed Bronze
	2BZ	Oil-Rubbed Bronze
	TT	Titanium
	VNT	Vintage Nickel



Technical Information

All product dimensions are nominal.

Notes

For use with automatic compensating valves rated at 2.5 gal/min (9.5 l/min) or less.

Install this product according to the installation guide.