

STONE THEORY™

GLAZED PORCELAIN FLOOR, GLAZED CERAMIC WALL AND MOSAIC,
AND ANTIQUED MIRROR & GLASS MOSAICS

AMERICAN OLEAN®



STONE LOOK



AMERICAN OLEAN®
PROVEN IN TILE™

STONE THEORY™

Stone Theory™ blends nature with a contemporary flair. Inspired by the fusion of marble and quartzite, the three neutral colors are offered in popular large format sizes for both floor and wall applications, including a modernized 6x18 wall tile. A stunning tiffany glass and antiqued mirror mosaic, inspired by the Art Deco period, accentuates its intriguing stone visuals and contrasting veins. Add a striking yet calming ambiance to any space with Stone Theory.



Cover photo feature Stone Theory Notion 12 x 24 on the floor and Gem Arrow Glass & Antiqued Mirror Mosaic on the wall.
Above photo features Stone Theory Notion 18 x 18 on the floor, Notion 6 x 18 on the shower wall and Notion 2 x 2 mosaic on the shower floor.

STONE THEORY™

GLAZED PORCELAIN FLOOR, GLAZED CERAMIC WALL AND MOSAIC, AND ANTIQUED MIRROR & GLASS MOSAICS

AMERICAN OLEAN®

FINISHES: MATTE | GLOSSY

USAGE	MATERIAL	PRICING	SPECIAL FEATURES
<p>FLOOR WALL COUNTERTOP SHOWER FLOOR EXTERIOR FLOOR</p>	<p>PG GLAZED PORCELAIN CG GLAZED CERAMIC G GLASS</p>	<p>LOW HIGH</p>	<p>STEPWISE™ TRUE EDGE™ MADE IN THE U.S.A. LARGE FORMAT MOSAIC/DECO ENCAUSTIC TERRAZZO PAVER CUSTOMIZE</p>

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

STONE LOOK

GLAZED PORCELAIN FLOOR TILE - MATTE



NOTION ST86



METAMORPHIC ST87



FORMATION ST88


GLAZED CERAMIC WALL TILE - MATTE



NOTION ST86



METAMORPHIC ST87



FORMATION ST88

GLAZED CERAMIC 2 x 2 MOSAIC - MATTE



NOTION ST86



METAMORPHIC ST87




FORMATION ST88

STACK GLASS & ANTIQUED MIRROR MOSAIC - GLOSSY



GEO STACK MOSAIC ST89




GEM STACK MOSAICS ST96

ARROW GLASS & ANTIQUED MIRROR MOSAIC - GLOSSY



GEO ARROW MOSAIC ST89



GEM ARROW MOSAIC ST96

CHEVRON GLASS & ANTIQUED MIRROR MOSAIC - GLOSSY



GEO CHEVRON MOSAIC ST89



GEM CHEVRON MOSAIC ST96



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT
Not Applicable to Mesh-Mounted Mosaic



CLIMATEPRO™



SIMPLICLEAN™

VISIT AMERICANOLEAN.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

STONE THEORY™

GLAZED PORCELAIN FLOOR, GLAZED CERAMIC WALL AND MOSAIC, AND ANTIQUED MIRROR & GLASS MOSAICS

AMERICAN OLEAN®

FINISHES: MATTE | GLOSSY


USAGE




MATERIAL



PRICING



SPECIAL FEATURES



NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	12 x 24 Floor Tile	11-13/16" x 23-13/16" (30.00 cm x 60.48 cm)	5/16"	15.60	8
	18 x 18 Floor Tile	17-3/4" x 17-3/4" (45.20 cm x 45.20 cm)	5/16"	17.60	8
	6 x 18 Wall Tile	6" x 18" (15.26 cm x 45.77 cm)	3/8"	11.25	15
	2 x 2 Mosaic (Dot-mounted)	12" x 24" Sheet (30.48 cm x 60.96 cm Sheet)	1/4"	24.00	12
	Arrow Glass & Antiqued Mirror Mosaic (Mesh-mounted)	13-15/16" x 11-1/2" Sheet (35.51 cm x 29.31 cm Sheet)	3/16"	19.60	20
	Chevron Glass & Antiqued Mirror Mosaic (Mesh-mounted)	14-1/16" x 12" Sheet (35.71 cm x 30.48 cm Sheet)	3/16"	20.00	20
	Stack Glass & Antiqued Mirror Mosaic (Mesh-mounted)	13-15/16" x 12-1/4" Sheet (35.51 cm x 31.00 cm Sheet)	3/16"	20.20	20

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●*
Wet & Level – Interior Floor	≥ 0.42	●*
Shower Floors (Residential or Light Commercial)	≥ 0.42	●**
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●*
Pool Linings	N/A	●**

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Floor tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Wall tile and 2 x 2 mosaic suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

* Wall tile and Antiqued Glass & Mirror Mosaics not suitable for this application.

** 2 x 2 Mosaic tile only.

FEATURES



888.AOT.TILE



AMERICAN OLEAN®
PROVEN IN TILE™



All or select items within this series meet the requirements for these qualifications. For more information visit americanolean.com.

AMERICANOLEAN.COM

©2021 AMERICAN OLEAN (10/21)

LEARN MORE

STONE LOOK

TRIM

			NUMBER	PIECES/ CARTON
	Floor Bullnose	3 x 12	P43C9	30
	12" Jolly	1/2 x 12	S1/212J	6 CARDS*

* 4 Pieces per card.

INSTALLATION

Grout Joint Recommendation	Shade Variation
<p>Floor: 3/16" (Overlap should not exceed 33% when installing tile with length 15" or greater in a staggered brick-joint pattern.)</p> <p>Wall: 1/16" (1/8" when rectangular sizes are used in a staggered brick-joint pattern, where the overlap does not exceed 33%)</p> <p>Mosaic: 1/8"</p>	<p>MEDIUM (V2)</p>

PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT	WALL RESULT	2 x 2 MOSAIC RESULT	GLASS AND ANTIQUED MIRROR MOSAIC RESULT
Water Absorption	C373	< 0.5%	< 20.0%	< 3.0%	< 0.5%
Breaking Strength	C648	> 275 lbs.	120 - 230 lbs.	> 250 lbs.	> 100 lbs.
Scratch Hardness	MOHS	8.0	4.0 - 6.0	7.0	4.0
Chemical Resistance	C650	Resistant	Resistant	Resistant	Resistant

For additional information on test results, visit us at: americanolean.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.