# **Product Specifications**



# #8 Zinc Alloy Walldriller Anchor Kit w/ Pan Head Combo Drive Screws

Part Number WDK8 Category Number 4730 UPC 781002297864

The WDK8 contains #8 Zinc Anchors and #8 Phillips/Slotted Drive Sheet Metal Screws. The Wall Board Anchor is manufactured with a fine centered point that helps guide the anchor into the material. It features a unique sharp thread design that allows it to screw directly into drywall with no pre-drilling. It is also a reusable anchor that can be easily installed with a screwdriver or power driven screwdriver.



# **Physical Characteristics**

| Bit              | IB2P             |
|------------------|------------------|
| Anchor Type      | Wall Board       |
| Style            | Self Drilling    |
| Drive Type       | Phillips/Slotted |
| Head Type        | Pan              |
| Screw Size       | #8 x 1-1/4"      |
| Anchor Diameter  | 5/8"             |
| Anchor Length    | 1-1/2"           |
| Material         | Zamac Alloy      |
| Number of Pieces | 50               |

#### **Packaging Details**

| Kit Contains   | (50) Wall Board Anchors, (50) #8 x 1-1/4" Phillips/Slotted<br>Sheet Metal Screw, (1) #2 Insert Bit |
|----------------|--|
| Standard Qty   | 1  |
| Master Qty     | 10   |
| Price Per      | 1  |
| Package Length | 7.00   |
| Package Width  | 3.30   |
| Package Height | 1.60   |
| Net Weight     | 1.23   |
| Package Weight | 1.23   |
| Package Type   | Two Compartment Box  |

# **Performance Data**

| Tension Strength  | 3/8" Drywall: 46lbs, 1/2" Drywall: 50lbs, 5/8" Drywall: 76lbs                                     |
|-------------------|---|
| Safe Tension Load | 3/8" Drywall: 20lbs, 1/2" Drywall: 23lbs, 5/8" Drywall: 30lbs                                     |
| Shear Strength    | 3/8" Drywall: 100lbs, 1/2" Drywall: 123lbs, 5/8" Drywall: 166lbs                                  |
| Safe Shear Load   | 3/8" Drywall: 50lbs, 1/2" Drywall: 63lbs, 5/8" Drywall: 83lbs                                     |
| Applications      | For Walls, Not Reccomended For Ceilings   |
| Special Features  | Superior Pullout and Shear, Self Drilling, No Drill Bit Needed,<br>Sharp Profile Thread Cuts Deep |

# Certifications

| RoHS Compliant | Yes |
|----------------|-----|
|                |     |