



CP350COM STANDBY UPS SYSTEM

Offers energy savings, battery backup and surge protection.

The CyberPower Standby CP350COM uninterruptible power supply (UPS) safeguards PCs and other electronics (monitors, cable DSL/ modems, VoIP routers, fax machines, and home theater equipment) from blackouts, brownouts, surges, spikes, sags, and other power abnormalities.

This UPS system is ENERGY STAR® qualified with patented GreenPower UPS™ High Efficiency circuitry to save on energy costs by reducing energy consumption and heat buildup.

A Three-Year Warranty ensures that this UPS has passed our highest quality standards in design, assembly, material and workmanship, further protection is offered by a \$75,000 Connected Equipment Guarantee.



TYPICAL APPLICATIONS

- Desktop Computers
- Home Networking/VoIP
- Personal Electronics

FEATURES

- 350 VA/225 W
- Standby Topology
- GreenPower UPS™
- ENERGY STAR® Qualified
- Full-time Surge Protection and Battery Backup
- Compact Form Factor
- 6 Outlets
- EMI/RFI Filters
- Three-Year Warranty

SPECIFICATIONS

GENERAL		OUTPUT	
UPS Topology	Standby	VA	350
Energy Saving	GreenPower UPS™ High Efficiency	Watts	255
ENERGY STAR® Qualified	Yes	On Battery Voltage	120 V ± 5%
INPUT		On Battery Frequency	50/60 Hz ± 1%
Voltage	96 V-140 V	On Battery Waveform	Simulated Sine Wave
Frequency	47 Hz - 63 Hz	Outlets - Total	6
Circuit Breaker	10 Amp	Outlets - Type	NEMA 5-15R
Plug Type	NEMA 5-15P	Outlets - Battery & Surge Protected	3
Plug STyle	Right Angle, 45° Offset Right	OUTlets - Surge-Only Protected	3
Cord Length	5'	Outlets - Widely Spaced	2

CP350COM STANDBY UPS SYSTEM



SPECIFICATIONS CONT.

OUTPUT CONT.

Overload Protection	Internal Circuitry Limiting/ Circuit Breaker
Transfer Time	4ms

BATTERY

Runtime at Half Load (min)	8
Runtime at Full Load (min)	2
Battery Type	Sealed Lead-Acid
Battery Size	12 V/3.6 Ah
Battery Quantity	1
User Replaceable	No
Typical Recharge Time	8 Hours

SURGE PROTECTION & FILTERING

Surge Suppression	810 Joules
EMI/RFI Filtration	Yes

MANAGEMENT & COMMUNICATIONS

HID Compliant USB Port	No
Serial Port	No
Cable Management	None
LED Indicators	Power On, Wiring Fault

MANAGEMENT & COMMUNICATIONS CONT.

Audible Alarms	On Battery, Low Battery, Overload, UPS Fault, Replace Battery
Software	None

PHYSICAL

Form Factor	Compact
Keyhole Mounting Slots	No
Dimensions (WxHxD) (in.)	7.1 x 4.3 x 3.2
Weight (lbs.)	3.5

ENVIRONMENTAL

Operating Temperature	32°F to 104°F/0°C to 40°C
Operating Relative Humidity	0%-90% (Non-condensing)

CERTIFICATIONS

Safety	UL1778, cUL 107.3, FCC DOC Class B
Environmental	RoHS Compliant

WARRANTY

Product Warranty	Three-Years Limited
Connected Equipment Guarantee	Lifetime
CEG Amount	\$75,000