



GE APPLIANCES

Top-Discharge Heat Pumps



Easier To: Do The Job



R454B Refrigerant

A lower Global Warming Potential (GWP), eco-friendly option that meets updated refrigerant guidelines while maintaining high efficiency.



Durable 45-Degree Service Valves

Our units feature 45-degree service valves, ensuring convenient gauge access and minimizing bending and twisting – allowing you to get the job done faster and more comfortably.



Longer Service Valve Connections

Longer service valves provide the flexibility to make connections your way. Whether you prefer mechanical or brazed connections, our units are designed to accommodate both.



Easy Servicing with Ordinary, Readily Available Screws

Featuring standard 5/16" and 1/4" screws across all platforms, allowing you to use the same tools consistently across GE HVAC products.



Removable Wire Fan Guard

Move from one job to the next faster with our removable wire fan guard, designed for quick and easy removal and servicing.



Compatible with Standard TXVs

With fewer electronic parts, our system offers simpler diagnostics, easier replacement, and trusted performance.



24V Thermostat Compatible

Enjoy the flexibility to choose from popular 24V thermostats, thanks to logic controlled in the equipment's control boards. No expensive, proprietary controls required.

Easier To: Close The Sale



Quiet Operation

The world is noisy. Homes shouldn't be. From absorbing loud vibrations to lowering fan speeds, GE units are designed to keep quiet.



Anti-Corrosion Coils

Durable, tube and fin aluminum alloy coils help ward off corrosion and can extend the life of the unit.



Optimal Airflow

A unique louver design and swept-wing blade create optimal airflow, enhancing performance even in extreme conditions.



Ten-Year Limited Warranty

Homeowners can double the standard five-year warranty by registering the unit. Translation: peace of mind for your homeowners. See warranty documentation for complete details.

Brought to you by



GE APPLIANCES
a Haier company

AIR&WATER
SOLUTIONS

Top-Discharge Heat Pumps Specifications



GE APPLIANCES



NS21H Inverter Heat Pumps

Model	Cooling			Heating				Sound Power*	Dimensions (H" x W" x D")	Approx. Unit Weight (lbs)
	SEER2	EER2	AHRI Rated Capacity BTU/hr	BTU _h @ 17°F	COP @ 5°F	HSPF2	BTU _h @ 47°F			
NS21H24MA5	20.5	13	24,000	22,400	2.30	10.2	27,400	68	45.375 x 35.75 x 39.75	263
NS21H36MA5	20	12.2	34,800	31,800	2.46	10.4	34,600	72	45.375 x 35.75 x 39.75	263
NS21H48MA5	20.5	12.6	48,000	42,000	2.20	9.6	51,000	75	39.375 x 35.75 x 39.75	284
NS21H60MA5	20.5	12	56,000	46,000	2.16	9	55,500	78	45.375 x 35.75 x 39.75	318



NS19H Inverter Heat Pumps

Model	Cooling			Heating				Sound Power*	Dimensions (H" x W" x D")	Approx. Unit Weight (lbs)
	SEER2	EER2	AHRI Rated Capacity BTU/hr	BTU _h @ 17°F	COP @ 5°F	HSPF2	BTU _h @ 47°F			
NS19H36MA5	20	13.2	36,000	22,600	2.20	8.5	36,800	61 - 72 [†]	33.75 x 29.38 x 31.25	215
NS19H60MA5	18.5	12	57,500	38,500	2.26	9	60,000	66 - 78 [†]	43.75 x 29.38 x 31.25	272



NS16H Single-Stage Heat Pumps

Model	Cooling			Heating				Sound Power*	Dimensions (H" x W" x D")	Approx. Unit Weight (lbs)
	SEER2	EER2	AHRI Rated Capacity BTU/hr	BTU _h @ 17°F	COP @ 5°F	HSPF2	BTU _h @ 47°F			
NS16H18SA5	16.5	14.2	18,000	11,400	2.05	7.8	18,000	74	43.25 x 28.25 x 28.25	213
NS16H24SA5	16	13.8	24,000	14,900	2.20	8.2	23,200	74	43.25 x 28.25 x 28.25	213
NS16H30SA5	16	13.4	29,600	18,700	2.12	8.2	29,600	74	33.25 x 28.25 x 28.25	213
NS16H36SA5	16	13.4	36,000	20,800	2.06	8.0	36,000	75	33.25 x 32.25 x 32.25	229
NS16H42SA5	15.5	13.2	42,000	27,600	2.14	8.2	42,000	78	37.25 x 32.25 x 32.25	272
NS16H48SA5	15.5	13	48,000	31,400	2.20	8.2	48,000	79	37.25 x 32.25 x 32.25	273
NS16H60SA5	14.7	12.4	58,000	36,600	2.26	8.1	59,500	79	43.25 x 32.25 x 32.25	295

Note: Maximum efficiency and capacity performance ratings shown. Actual performance may vary by equipment matchup selection.

*Rating in accordance with AHRI standard 270 (2015). AHRI Standard 270 establishes a method of rating outdoor unitary equipment in terms of sound power.

† Sound Rating Number Range (dBA), higher tonnage has broader range in both high and low.

©Copyright 2026 GE Appliances, a Haier Company. GE is a trademark of the General Electric Company. Manufactured under trademark license. GE Appliances has a policy of continuous improvement of its products and reserves the right to change materials and specifications without notice.

Appliance Park Louisville, KY 40225
Pub No. 26-DHPS01 Rev. 07-10-2026