# SONANCE

## SMALL APERTURE DATA SHEET

### **SA4-66 SPEAKER ENCLOSURE & MODULE**

#### TECHNICAL SPECIFICATIONS

#### **SA4-66 SPEAKER ENCLOSURE AND SPEAKER MODULE**

**UOM** 

Wide Bandwidth Driver 2.0" (50mm) Aluminum cone, rubber surround Woofer 6.5" (165mm) Aluminum cone, rubber surround

Frequency Response 45Hz - 22kHz +/-3dB 35Hz-25kHz +/-10dB Frequency Range

8 ohms nominal: 6 ohms minimum Impedance Power Handling (RMS) 5 watts minimum; 125 watts maximum

Sensitivity (2.83V/1m) 82dB SPI

**Overload Protection** Two independent self-resetting poly switches

Enclosure Only (WxHxD) 22.95" x 10.2" x 6.38" (583mm x 258.5mm x 162mm) Enclosure With Bracket (WxHxD) 25.9" x 10.2" x 6.38" (658mm x 258.5mm x 162mm) Installation Width 10.2" (258.5mm) Minimum; 25.5" (649.1mm) Maximum

Flush Round Grille (Dia) 4.02" (102.0mm)

Flush Square Grille (HxW) 4.02" x 4.02" (102.0mm x 102.0mm)

Micro Trim Round Grille (Dia) 4.62" (117.4mm)


Micro Trim Square Grille (HxW) 4.62" X 4.62 (117.4mm x 117.4mm)

**Enclosure Weight** 19.73 lbs (8.95kg) Module Weight 0.80 lbs (0.35kg) Kit Shipping Weight\* 34.17lbs (15.5kg)

#### DIMENSIONAL DRAWINGS




**Enclosure Width Front View** 





Enclosure + Brackets Width

Side View **Top View** 





<sup>\*</sup> SA4-66 Complete Kit ships with installation accessories for Micro Trim applications into drywall or solid surfaces. For complete kit, order sku 93729

LIMITED LIFETIME WARRANTY Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/ Distributor, will be free from defective workmanship and materials for the life of the Product, except for the grille, which is warranted for five (5) years. Sonance will at its option and expense either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. @2025 Sonance. All rights reserved. Sonance is a registered trademarks of Dana Innovations. Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product specification information visit our website at www.sonance.com.