

# Location:



1-217-FS  
Tub/Shower/Hand Shower System  
**Specification Submittal**



Model Numbers	Feature Highlights
<input type="checkbox"/> <b>1-215-X</b> Tub and Shower System with Symmons Safetymix pressure balancing mixing valve	<ul style="list-style-type: none"> <li>• Safetymix® Pressure-Balancing mixing valve with lever handle</li> <li>• Adjustable stop screw to limit handle turn</li> <li>• Super shower head with arm and flange</li> <li>• Lever diverter with integral volume control</li> <li>• Tub spout</li> <li>• Wall/hand shower with flexible 5' metal hose</li> <li>• In-line vacuum breaker</li> <li>• Wall connection and flange</li> <li>• Wall hook for hand shower mounting</li> <li>• Standard flow rate 2.0 gpm (7.6 L/min)</li> </ul>
Options/ Modifications	
<input type="checkbox"/> <b>72</b> 72" hose in place of 60" hose <input type="checkbox"/> <b>TRM</b> Trim only, valve body ordered separately <input type="checkbox"/> <b>NS</b> Non-shared diverter valve <input type="checkbox"/> <b>X</b> Integral stops - allows water shut off at valve for service. Recommended for use on all multiple commercial installations <input type="checkbox"/> <b>X-CHKS</b> Integral check stops - for use in installations where a positive shut-off device is used downstream of mixing valve <input type="checkbox"/> <b>1.5</b> 1.5 (5.7 L/min) Flow rate restrictor	
<p><b>Note:</b> Append appropriate -suffix to model number.</p>	Warranty
Compliance	<p><b>Limited Lifetime</b> - to the original end purchaser in consumer/residential installations.  <b>10 Years</b> - for commercial/industrial installations. Refer to <a href="http://www.symmons.com/warranty">www.symmons.com/warranty</a> for complete warranty information.</p> 
<p>- ASME A112.18.1/CSA B125.1</p> 	

## Architectural/ Engineering Specification

Symmons Safetymix Tub and Shower and Hand Shower System \_\_\_\_\_ Includes Safetymix Pressure-Balancing mixing valve with lever handle, Adjustable stop screw to limit handle turn, Super shower head with arm and flange, Lever diverter with integral volume control, Tub spout, Wall/hand shower with flexible 5' metal hose, In-line vacuum breaker, Wall connection and flange, Wall hook for hand shower mounting, Standard flow rate 2.0 gpm (7.6 L/min). 10 Year Commercial Warranty. ASME A112.18.1/CSA B125.1 compliant. Available options: "72 - 72" hose in place of 60" hose", "TRM - Trim only, valve body ordered separately", "NS - Non-shared diverter valve", "X - Integral stops - allows water shut off at valve for service. Recommended for use on all multiple commercial installations", "X-CHKS - Integral check stops - for use in installations where a positive shut-off device is used downstream of mixing valve", "1.5 - 1.5 (5.7 L/min) Flow rate restrictor".



1-217-FS

## Dimensions

