



TECHNICAL INFORMATION



V2 Slight Variation



Import
Stock



Recommend offset
pattern $\leq 33\%$



PEI Rating 4-5



DCOF: ≥ 0.42



Frost Resistant



Water Absorption:
 $\leq 0.1\%$




Made in Italy

COLORS



In Ivory
MED ICII



Contro Ivory
MED ICCI



In Cream
MED ICIC



Contro Cream
MED ICCC




Contro Grey
MED ICCG



In Grey
MED ICIG




In Ivory
MED ICII



Contro Ivory
MED ICCI



In Cream
MED ICIC



Contro Cream
MED ICCC



Contro Grey
MED ICCG



In Grey
MED ICIG



In Ivory
MED ICII



Contro Ivory
MED ICCI



In Cream
MED ICIC



Contro Cream
MED ICCC



Contro Grey
MED ICCG



In Grey
MED ICIG



In Ivory
MED ICII



In Cream
MED ICIC



In Grey
MED ICIG

Field

48" x 48" x 9.5mm Rectified
40" x 40" x 8.5mm Rectified
Matte, Bush-hammered & Semi-polished
24" x 48" x 9.5mm Rectified
Matte & Semi-polished
24" x 24" x 9.5mm Rectified
Matte, Bush-hammered & Semi-polished
12" x 24" x 9.5mm Rectified
Matte & Bush-hammered

Mosaic and Deco

11" x 13" x 9.5mm Hexagon Mosaic
Rectified Matte
2" x 2" x 9.5mm Mosaic
Rectified Matte
24" x 48" x 9.5mm Lines Decorative
Rectified Matte



Tiles, Mosaic and Trim*

SIZE	ACTUAL	THICKNESS	FINISH
48" x 48" Rectified	47.24" x 47.24"	9.5mm	Matte/Natural
40" x 40" Rectified	39.37" x 39.37"	8.5mm	Matte/Natural -Bush hammered -Light or Semi-Polished
24" x 48" Rectified	23.62" x 47.24"	9.5mm	Matte/Natural -Light or Semi-Polished
24" x 24" Rectified	23.62" x 23.62"	9.5mm	Matte/Natural -Bush hammered -Light or Semi-Polished
12" x 24" Rectified	11.81" x 23.62"	9.5mm	Matte/Natural -Bush hammered
24" x 48" Lines Decorative Rectified	23.62" x 47.24"	9.5mm	Matte/Natural
11" x 13" Hexagon Mosaic Rectified	11.02" x 12.59"	9.5mm	Matte/Natural
2" x 2" Mosaic Rectified	11.81" x 11.81"	9.5mm	Matte/Natural
3" x 24" Bullnose Rectified	2.55" x 243.62"	9.5mm	N/A

* Not all sizes are available in all colors and finishes.

Performance Characteristics

Breaking Strength	≥ 1300N
Chemical Resistance	A-HA-LA
DCOF	≥ 0.42
Deep Scratch Resistance - Unglazed	N/A
Frost Resistance	Resistant
Mohs Hardness - EN101	6
Water Absorption	≤ 0.1%
Certifications	N/A
Country of Origin	Italy
Shade Variation Code	V2

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	•

** These recommendations are not defined by ANSI Standards

