## INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions as you may need them a later date.

## CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct

fixture in order to prevent possible shock. Turn off the main power at the circuit breaker before installing the

## GENERAL

wiring connections obtain the services of a qualified electrician Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical that no parts are missing by referencing the illustration. Remove the fixture and the mounting package from the box and make sure All electrical connections must be in accordance with local and National

## **ASSEMBLY AND INSTALLATION**

- 1. Take the fixture out of the package.
- Take the cage (5) and arm (9) carefully out of box.

rubber washer (17) from arm (9). Remove top cage screw (10).bottom cage screw(12) and

Make sure all four pieces of glass are fixed before proceeding to the next press the glass sheet tightly with top and bottom clips

installation step.

2.Secure the cage (5) onto the back plate in two steps

- --Secure the cage (5) onto the arm (9) with top cage screws(10) and rubber washer(17).
- ---Thread the bottom cage screw(12) into the provided holes(11) of the back plate.
- Mounting the Hardware
- --- Position the mounting bracket (2) on the wall and mark location of the four holes for anchors. Drill the holes on the wall and insert the anchors (1).
- —Secure the mounting bracket (2) to the outlet box with the outlet box screw (4).
- --Screw the wood screw (3) into anchor(1).
- Hang the safety cable into the holes of mounting bracket

Pull out the wires and ground wire from the Outlet Box.

- Make wire connections with Wire nut(14):
- ---White wire from light to White Wire from power source
- ---Attach the Ground Wire to Mounting bracket with a Ground Screw ---Black wire from light to Black Wire from power source.
- Connect Ground Wire from light to Ground Wire from power source.
- 5.Place the back plate(16) of the fixture body onto mounting bracket (2).
- Secure the back plate(16) into place by using rubber washer(15) and flat screw (7)
- 6.Install bulbs (8) (bulbs not included, Make sure they do not exceed the maximum wattage specified on the fixture's wattage rating label.).
- 7. To prevent moisture from entering the outlet box and the fixtures mounting plate causing a short, apply a bead of clear caulk to outline the outside of the fixtures mounting plate where it meets the wall.

Leave a small space at the bottom to allow any condensation or moistureto escape.

