

		Product Name: OS-55M	
Regulatory Information: UN 1H2/Y150/S (Test Report P253)	Bill of Materials: Body: OS-55M, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE) Cover: Plain, one 2" opening, or two 2" openings available, NPS bungs, HDPE. Vented bungs are available as an option. (NPS = National Pipe Straight thread) Lockband: Side lever (SLL) or Bolt	Product Illustration:	
			
Nominal Capacity: 55.0 U.S. Gallons	Outage: 2.7 U.S. Gallons	Opening I.D.: 19.3 inches	Total Weight: 22.5 lbs.
Maximum Capacity: 57.7 U.S. Gallons	Outage %: 5.0 %	Nominal O.D.: 23.1 inches	Body Weight: 17.3 lbs.
Export Cubes: 10.72 cu. ft.	Overall Height: 35.6 inches	Min. Wall Thickness: 0.135 inches	Chime Height: 0.480 inches
Min. Blocking Diameter: 23.1 inches	Body Height: 35.3 inches	Mid Panel Height: 10.8 inches	
Special Notes: 1) Maximum filling temperature 150 F for all foods and other FDA regulated substances. 160 F for all non-foods and other substances that are not regulated by FDA. When filled at these recommended maximum filling temperatures drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability. 2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 800 lbs. each. Pallets should be of good quality that provides adequate support for plastic drums. 3) Handle with parrotbeak, side grabber, and sling. 4) Recycle symbol embossed on bottom. 5) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.			

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DWG20368

DESCRIPTION:

55 Gallon HDPE Straight Side OH Drum & Cover,
UN Rated