

Maximal Series

Single P/S Access Power Controllers (PTC)

Description

Maximal Access Power/Controllers distribute and switch power to access control systems and accessories. They convert a 115VAC, 60Hz input into sixteen (16) independently controlled 12VDC or 24VDC Class 2 Rated PTC protected power-limited auto-resettable outputs. The outputs are activated by an open collector sink or normally open (NO) dry trigger input from an Access Control System, Keypad, Push Button, REX PIR, etc. Units will route power to a variety of access control hardware devices including: Mag Locks, Electric Strikes, Magnetic Door Holders, etc. The FACP Interface enables Emergency Egress, Alarm Monitoring, or may be used to trigger other auxiliary devices. The fire alarm disconnect feature is individually selectable for any or all of the sixteen (16) outputs.



Maximal7D

Key Features

- Sixteen (16) independently controlled Fail-Safe and/or Fail-Secure Class 2 Rated PTC protected power-limited outputs.
- Sixteen (16) auxiliary power outputs (unswitched).
- Output PTCs are rated @ 2.5A.
- Filtered and electronically regulated outputs.
- Supervision:
 - AC Fail
 - Battery Fail and Battery Presence.
- Fire Alarm disconnect (latching or non-latching) is individually selectable for any or all of the sixteen (16) outputs.
- Alarm output relay indicates that FACP input is triggered.
- Fire Alarm disconnect input options:
 - a) Normally open (NO) or normally closed (NC) dry contact input
 - b) Polarity reversal input from FACP signaling circuit.
- Built-in charger for sealed lead acid or gel type batteries.
- Instantaneous transfer to stand-by batteries.
- UL Listed in the U.S. and Canada.
- Lifetime Warranty / Made in the U.S.A.

Maximal Single Power Supply Series Configuration Reference Chart

Altronix Model Number	Power Supply Board Output Voltage Options	PTC Protected Class 2 Rated Power-Limited Outputs (auto-resettable)	Maximum Current Per ACM8CB Output	115VAC 60Hz Input (current draw)	Power Supply Board Input Fuse Rating	Power Supply Board Battery Fuse Rating
Maximal3D	12VDC @ 5A or 24VDC @ 5.4A	16	2.5A	3.5A	5A/250V	—
Maximal5D	12VDC @ 9A			2.6A		15A/32V
Maximal7D	24VDC @ 9.4A			4.4A	6.3A/250V	15A/32V

Lifetime Warranty / Made in the U.S.A.

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA

phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com



Maximal Series

Single P/S Access Power Controllers (PTC)



Specifications

Input

Voltage	115VAC, 60Hz.
Input Fuse	Varies, see Reference Chart.

Outputs

Class 2 Rated power-limited PTC Protected Outputs (auto-resettable).

Voltage	12VDC or 24VDC, see Reference Chart.
Current	Varies, see Reference Chart.
Protection	PTC 2.5A.
Auxiliary	2.5A (unswitched).
Other	Overvoltage protection. Filtered and regulated outputs.

Back-up Battery *(not included)*

Capacity	12AH / 12VDC (up to 4 within enclosure). 40 AH / 65 AH (requires separate enclosure).
Type	Sealed lead acid or gel type.
Fuse Rating	15A @ 32VDC Maximal3D does not have a battery fuse.
Failover	Upon AC loss, instantaneous.

Fire Alarm Disconnect

Latching or non-latching,
individually selectable for any or all of
the sixteen (16) outputs.

Supervision

AC Failure	Form "C" contacts.
Battery	Form "C" contacts.

Indicators (LED)

Input	115VAC is present.
DC Output	Powered.
Battery	Discharged or not connected.
Relays	Individual LEDs indicate outputs are triggered (relays energized).
FACP	Indicates FACP disconnect is triggered.

Agency Listings

UL:

UL294	Access Control System Units.
-------	------------------------------

cUL:

C22.2 No.205-M1983	General Signaling Equipment;
CSFM	California State Fire Marshall Approved.

Physical and Environmental

Dimensions (H x W x D)

26" x 19" x 6.25" (660.4mm x 482.6mm x 158.75mm).

Weight (approx.)

Model	Product Weight	Shipping Weight
Maximal3D	30.8 lb. (14.0 kg)	37.8 lb. (17.2 kg)
Maximal5D	31.8 lb. (14.4 kg)	38.85 lb. (17.6 kg)
Maximal7D	32.25 lb. (14.6 kg)	39.25 lb. (17.8 kg)

Temperature

Operating	0°C to 49°C (32°F to 120°F).
Storage	-20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

BTU/Hr. (approx.):

Model	12VDC	24VDC
Maximal3D	31	67
Maximal5D	55	N/A
Maximal7D	N/A	115

Lifetime Warranty / Made in the U.S.A.

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA

phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com