

Esplanade® embodies the earthy aesthetic of travertine in a durable porcelain tile. Nuanced color variation lends a natural aesthetic. Large format and mosaic tiles allow for a range of design applications.

ESPLANADE®

Glazed Porcelain



FLOOR / WALL  RESIDENTIAL  COMMERCIAL  INDOOR 



Alley (Available in Matte & Polished)



Hall



Pass



Trail

Mosaics



Alley








Hall



Pass



Trail

Sizes	 12"x24" 11.81"x23.62"	 11"x23" (Alley Only) 11.42"x23.23"	 12"x12" Mesh 11.81"x11.81"	 3"x12" (M) Floor SBN	 3"x11" (P) (Alley Only) Floor SBN		
Thickness	7mm	7mm	9.8mm	9.5mm	10mm		
Faces	16	16	N/A	N/A	N/A		
Finish	Matte	Polished	Matte	Matte	Polished		
Edge	Pressed	Rectified	Cut	Cut/Rounded	Cut/Rounded		
Grout Joint Recommendation	3/16"	1/8"	3/16"	3/16"	3/16"		
Testing	Abrasion Resistance C1027	Breaking Strength C648	Chemical Resistance C650	Water Absorption C373	DCOF ANSI A1371	Scratch Hardness MOHS	Shade Variation Rating
Results*	III (Matte) II (Polished)	>250 lbf	Resistant	<0.50%	>0.42 (Matte) <0.42 (Polished)	5 (Matte) 4 (Polished)	V2

Product and Installation Details | ANSI A108.02
Section 4.3.8.2 - For running bond/brick joint patterns utilizing tiles (square or rectangular) where the side being offset is greater than 18" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the tile manufacturer. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage.



 Sustainability Attributes

- Red List Free
- Health Product Declaration (HPD) provided upon request
- Product Packaging is 100% recyclable
- VOC Free

*For more information visit www.emser.com. Always consult a professional for proper usage and installation.