



4700 W. 160th St.
Cleveland, OH 44135
PH:800-321-9532
FX:800-321-9535
www.oatey.com

TECHNICAL SPECIFICATION

METAL STUD INSULATING PIPE CLAMPS



TECHNICAL SPECIFICATION: Oatey Metal Stud Insulating Pipe Clamps can be installed to isolate piping away from the stud and reduce water line noise and vibration in metal stud installations. Metal Stud Insulating Pipe Clamps snap into 1-3/8" punched hole and can be used on 18 Gauge or lighter weight metal studs. Metal Stud Insulating Pipe Clamps can be used on hydronic heating systems.



APPROVALS AND LISTINGS



IAPMO Listed

PHYSICAL/CHEMICAL PROPERTIES

Material Polypropylene
Color Gray

DIRECTIONS FOR USE

Punch 1-3/8" hole in metal stud. Snap clamp into hole. Clamp is offset to allow for adjustment of centers from stud to stud. 1/2" clamp allows for 1/4" and 3/8" tubing installation through secondary holes in clamp. Check with local codes to ensure proper spacing requirements for piping support.

PRECAUTIONS

Read cautions and directions on packaging carefully before using this product. KEEP OUT OF REACH OF CHILDREN.

COMMON APPLICATIONS

Oatey Metal Stud Insulating Pipe Clamps can be installed to isolate piping away from the stud and reduce water line noise and vibration in metal stud installations. *U.S. Patent #6,598,835.*

Consult Oatey Technical Department for applications not specifically referenced above.

PRODUCT NUMBER	DESCRIPTION	PACK	CARTON WEIGHT
33856	1/2" Metal Stud Clamp (50 in polybag)	250	2.5 lbs.
33857	3/4" Metal Stud Clamp (50 in polybag)	250	2.5 lbs.
33858	1" Metal Clamp (25 in polybag)	250	2.5 lbs.