

Rods with Eyenuts

Features

- Power hub anchor rod and eyenut are assembled at the factory
- Used with solid hub or socket drive power hub screw anchors
- One catalog number for both the rod and eyenut simplifies material handling
- All parts hot dip galvanized

5/8" Diameter

16,000 Lb Ultimate Tensile Strength			
Catalog Number	**Length (Ft)**	**Eyenut Type**	**Wt Ea (Lb)**
D623 1/2 S	3.5	Single Guy Eye	4.6
D623 1/2 D		Double Guy Eye	5.4
D623 1/2 T		Triple Guy Eye	6.0
D62S	7	Single Guy Eye	8.2
D62D		Double Guy Eye	9.1
D62T		Triple Guy Eye	9.4

3/4" Diameter

23,000 Lb Ultimate Tensile Strength			
D7531/2S	3.5	Single Guy Eye	6.9
D7531/2D		Double Guy Eye	6.8
D7531/2T		Triple Guy Eye	7.2
D75S	7	Single Guy Eye	11.2
D75D		Double Guy Eye	11.1
D75T		Triple Guy Eye	11.5

1" Diameter

36,000 Lb Ultimate Tensile Strength			
D10031/2S	3.5	Single Guy Eye	11.5
D10031/2D		Double Guy Eye	11.4
D10031/2T		Triple Guy Eye	11.8
D100S	7	Single Guy Eye	17.4
D100D		Double Guy Eye	17.4
D100T		Triple Guy Eye	17.7

Rods Only

Features

- Power hub anchor rod used with solid hub or socket drive power hub screw anchors



5/8" Diameter

16,000 Lb Ultimate Tensile Strength		
Catalog Number	**Length (Ft)**	**Wt Ea (Lb)**
D6231/2	3.5	3.6
D62	7	7.3

3/4" Diameter

23,000 Lb Ultimate Tensile Strength		
D7531/2	3.5	5.0
D75	7	9.3

1" Diameter

36,000 Lb Ultimate Tensile Strength		
D10031/2	3.5	9.6
D100	7	15.5



Rod Extensions with Coupling

Features

- Power hub anchor rod and coupling are assembled at the factory
- Used with solid hub or socket drive power hub screw anchors
- One catalog number for both the rod and coupling simplifies material handling

5/8" Diameter

16,000 Lb Ultimate Tensile Strength		
Catalog Number	**Length (Ft)**	**Wt Ea (Lb)**
D6231/2C	3.5	4.1
D62C	7	7.7

3/4" Diameter

23,000 Lb Ultimate Tensile Strength		
D7531/2C	3.5	5.5
D75C	7	9.8

1" Diameter

36,000 Lb Ultimate Tensile Strength		
D10031/2C	3.5	10.1
D100C	7	16.0



Eyenuts Only

Features

- Used with power hub rods for solid hub or socket drive power hub screw anchors

5/8" Diameter

16,000 Lb Ultimate Tensile Strength		
Catalog Number	**Eyenut Type**	**Wt Ea (Lb)**
D6510A	Single Guy Eye	1.0
D6560A	Double Guy Eye	1.8
D6565	Triple Guy Eye	2.2

3/4" & 1" Diameter

36,000 Lb Ultimate Tensile Strength		
D6512	Single Guy Eye	1.9
D6562A	Double Guy Eye	1.8
D6567	Triple Guy Eye	2.2



Couplings Only

Features

- These couplings are used with all power hub rods when additional rods must be installed

5/8" Diameter

16,000 Lb Ultimate Tensile Strength	
Catalog Number	**Wt Ea (Lb)**
D352	0.5

3/4" and 1" Diameter

36,000 Lb Ultimate Tensile Strength	
D354	0.5

© Copyright 2010 MacLean Power Systems
Issued: May 2010
Supercedes: n/a

11411 Addison Avenue, Franklin Park, IL 60131
T: 847.455.0014 F: 847.455.0029
www.macleanpower.com