

Product data sheet

Specifications



APC Smart-UPS, Line Interactive,
1500VA, Tower, 120V, 8x NEMA
5-15R outlets, SmartConnect
Port+SmartSlot, AVR, LCD

SMT1500C

Product availability: Non-Stock - Not normally stocked in distribution facility

Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually Ships within 2 Weeks

Main

Main Input Voltage	120 V AC 1 phase
Other Input Voltages	110 V 125 V
Input Connection Type	NEMA 5-15P
Efficiency at full load	75...154 V adjustable 82...144 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Output voltage	120 V AC 1 phase
Other Output Voltages	110 V 125 V
Rated power in W	1000 W
rated power in VA	1440 VA
output connection type	8 NEMA 5-15R
Harmonic distortion	Less than 5%
Maximum configurable power in VA	1440 VA
Max Configurable Power (Watts)	1000 W
Transfer Time	6ms typical : 10ms maximum
Topology	Line Interactive
Waveform Type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Replacement battery	RBC7

Graphs

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph

Complementary

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Battery Size	Lead-acid internal included
Control panel	Multi-function LCD status and control console
Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
UPS connectivity	Serial port USB port SmartConnect port Available expansion slot
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Software package	SmartConnect software for remote power monitoring feature availability varies by terms of use
Surge energy rating	680 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m
Cable length	6 ft (1.8 m)
Number of cables	1
color	Black
Height	8.6 in (219 mm)
Width	6.7 in (171 mm)
Depth	17.3 in (439 mm)
Product Weight	54.2 lb(US) (24.6 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Mounting mode	Tower
Provided equipment	Installation guide USB cable
Number of power module	0
Number of power module filled slots	0
Number of power module free slots	0
Additional specification	Cloud-enabled monitoring
Redundant	No
Range of Product	Smart-UPS
Product or Component Type	Uninterruptible power supply (UPS)

Environment

Product Certifications	cULus ENERGY STAR V2.0 (USA)
Equipment protection policy	Lifetime : \$150000
Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)

Storage altitude	0...50000 ft (0...15240 m)
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %
Acoustic level	45 dBA
Online Thermal Dissipation	225 Btu/h
Operating altitude	0...10000 ft

Batteries & Runtime

Battery Type	Lead-Acid battery
Extendable Run Time	0
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	3 h
RBC Quantity	1
Battery Life	3...5 year(s)
Battery Charge Power (Watts)	136 W rated

Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	731304322795
Returnability	No
Country of origin	VN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	13.0 in (33 cm)
Package 1 Width	23.2 in (59 cm)
Package 1 Length	13.0 in (33 cm)
Package weight(Lbs)	59.92 lb(US) (27.18 kg)

Contractual warranty

Warranty (in months)	36 UPS 24 Battery
----------------------	-------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Total lifecycle Carbon footprint	998 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	744 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	18 kg CO2 eq.
Carbon footprint of the installation phase [A5]	5 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	204 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	27 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	B2b22a56-41f2-497e-9ea6-cf093b3b8bd3
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

 Energy efficiency	
Optimized Energy Efficiency	Energy efficient product
 ENERGY STAR®	ENERGY STAR UPS V2.0 (USA)

Use Longer

 Lifetime extension	
Repair	No

Use Again

 Repack and remanufacture	
Recyclability potential, in %	51
Circularity Profile	End of Life Information

Removable battery	User replaceable
Take-back	Yes
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Technical Illustration

Dimensions



Offer Marketing Illustration

Product benefits / Features

Runtime

Support your sensitive electronics with battery power during utility power outages.

23 min



At half load

6 min



At full load



Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features

Save on utility and cooling costs
while reducing your business's
carbon footprint

98.9%
Online Efficiency



ENERGY STAR
V2.0 Certified



Offer Marketing Illustration

Product benefits / Features

Premium Power Protection

Maintain business continuity and positive customer experience while avoiding revenue loss due to power and voltage disruptions.



Offer Marketing Illustration

Product benefits / Features

Peace of Mind

Ensure that your equipment remains powered, protected and available in any scenario.

3-year

Warranty on UPS

2-year

Warranty on battery

\$150K

Equipment protection policy



Apr 10, 2026

Life Is On | Schneider Electric

11

Offer Marketing Illustration

Product benefits / Features

Intelligent battery management



Battery replacement recommendations



Temperature-compensated charging



Periodic battery self-test



Disconnect battery notifications



Offer Marketing Illustration

Product benefits / Features

SmartConnect Ethernet Port

Out-of-box cloud-based remote power monitoring

- 

UPS firmware upgrades
- 

Remote diagnostics
- 

Proactive email notifications
- 

Recommended actions



Select features may be subject to tier-based licensing. Terms on the Smart-UPS Web Portal.

Offer Marketing Illustration

Product benefits / Features

Peace of mind at home or office with
PowerChute™ Serial Shutdown Software

UPS management, graceful shutdown, and
energy management software for :



Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features



1500V
/1000W



Intelligent Battery
Management



Pure sine
wave output

Offer Marketing Illustration

Product benefits / Features

AVR : Automatic Voltage Regulation

Voltage fluctuations put your devices at risk. AVR instantly corrects variances in incoming voltage, ensuring stable and consistent power to your connected devices.



Benefits of AVR

Increased battery life

Protection against system crash

Protection against data loss

Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features



Image of product / Alternate images

Alternative



