



INCANDESCENT / LED 12V HYBRID PATH & SPREAD



	15410 AZT, BE - DOME PATH LIGHT	15470 AZT, BBR, BE, BKT - 6" DOME PATH LIGHT																																								
<b>Description</b>	A shorter version of our popular 15310 designed for use with lower planting and smaller garden areas. Coordinates with our 15310 & 15470 Domed Roof series.	A popular look with a smaller 6" shade. Coordinates with our 15310 & 15410 Domed Roof series.																																								
<b>Ordering Guide &amp; Finish</b>	15410 AZT - Textured Architectural Bronze 15410 BE - Beach	15470 AZT - Textured Architectural Bronze 15470 BBR - Bronzed Brass 15470 BE - Beach 15470 BKT - Textured Black																																								
<b>Housing</b>	Cast Aluminum	Cast Aluminum, Cast Brass																																								
<b>Lamp Base</b>	12V T5 wedge base socket 	12V T5 wedge base socket 																																								
<b>Supplied Lamp</b>	16.25-W(VA) 921X (17025) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)	16.25-W(VA) 921X (17025) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)																																								
<b>Incandescent Lamp Options</b>	11.6-W(VA) 912X (17023) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)	11.6-W(VA) 912X (17023) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)																																								
<b>LED Lamp Options</b>	2W (18039-13041) see page 159 Compares up to 16W Xenon	2W (18039-13041) see page 159 Compares up to 16W Xenon																																								
<b>Wiring</b>	30" of usable #18-2, SPT-1-W leads. Cable connector supplied	24" of usable #18-2, SPT-1W leads. Cable connector supplied																																								
<b>Mounting Acces. Included</b>	8" In-ground stake	8" In-ground stake																																								
<b>Optional Acces.</b>	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket																																								
<b>Integrated LED Option</b>	15811 - on Page 17	15870 - on Page 16																																								
<b>Photometric with Supplied Lamp</b>	<table border="1"> <tr> <td>Distance from Light</td> <td>0'</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>22.0</td><td>9.6</td><td>4.0</td><td>1.1</td><td>.03</td><td>0.1</td><td>-</td><td>-</td><td>-</td> </tr> </table>	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	22.0	9.6	4.0	1.1	.03	0.1	-	-	-	<table border="1"> <tr> <td>Distance from Light</td> <td>0'</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>6.17</td><td>4.85</td><td>4.34</td><td>2.51</td><td>1.58</td><td>1.35</td><td>0.77</td><td>0.43</td><td>0.28</td> </tr> </table>	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	6.17	4.85	4.34	2.51	1.58	1.35	0.77	0.43	0.28
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																	
Footcandles	22.0	9.6	4.0	1.1	.03	0.1	-	-	-																																	
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																	
Footcandles	6.17	4.85	4.34	2.51	1.58	1.35	0.77	0.43	0.28																																	

 Denotes fixture is compatible with incandescent or LED lamps.