



Z82300-XL-CP8

SINGLE CONTROL FAUCET

TAG _____

Architectural/Engineering Specification:

Polished chrome plated cast brass single control kitchen faucet with an integral 10" [245mm] cast swing spout, a ceramic disc cartridge and a temperature limit stop. Unit is furnished with a 2.2 GPM [8.3L] pressure compensating aerator (Complying with ANSI A112.18.1 Standard for flow), 8" [203] centers, cast metal chrome plated cover plate, a metal ADA compliant lever handle, stainless steel flex connection hoses and mounting hardware.

Zurn Lead Free products (-XL) is the line of durable, high quality brass faucets and fixtures that are designed and manufactured to comply with Section 1417 of the Safe Drinking Water Act (SDWA) which mandates the weighted average lead content of no more than 0.25% of the wetted surface.

Compliance and Certification:

- Complies with ASME A112.18.1/CSA B125.1
- Lead Free Compliant
- ADA Compliant



Aerator Options:

	Flow rate GPM [LpM]	Vandal Resistant	Pressure Compensation	Outlet Type
-2M	2.2[8.3]	✓	✓	Aerator
-3M	0.5[1.9]	✓	✓	Spray
-4M	2.2[8.3]	✓	✓	Laminar
-7M	1.0[3.8]		✓	Spray
-16M	1.0[3.8]	✓	✓	Spray
-17M	1.5[5.7]	✓	✓	Aerator
-18M	1.5[5.7]	✓	✓	Laminar
-19M	1.5[5.7]		✓	Laminar
-22M	1.0[3.8]	✓		Laminar
-23M	1.5[5.7]		✓	Aerator

Suffix Options:

- CST Copper Supply Tubes
- HS Hose and Spray
- HS6 6' [183cm] Hose and Spray
- 18FH 18" [457mm] S.S. Braided Flex Hoses

Architectural/Engineering Approval

The information contained in this document is subject to change without notice.
Please contact Zurn for most up to date information.



Rough-in dimensions/Overview dimensions

